

**Novartis Singapore Manufacturing Pte Ltd
Tuas
Singapore**

**Equipment – IBC Blender
SP2000 Blender (B01)
Post Hoist (D01)
Mill (M01)**

**Buck Ref: G1951-B01/D01/M01
OPERATION & MAINTENANCE MANUAL**



Blank Page



DOCUMENT NUMBER

G1951-B01/D01/M01-OMM

Title Operation and Maintenance Manual: IBC Blender

Revision: R1

Issue Date: 07 August 2007

CUSTOMER: Novartis Singapore Manufacturing Pte Ltd
 Tuas,
 Singapore

Purchase Order:

Buck Systems Ref: G1951-B01/D01/M01

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems.

Blank Page

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems.

Buck Systems,
Wharfdale House,
257 Wharfdale Road,
Tyseley,
BIRMINGHAM,
B11 2DP.
Tel: 44 (0)121 765 5800 Fax: 44 (0)121 765 5802

This Manual describes the following equipment:

Designation: G1951-B01/D01/M01
Supplied to: Novartis Singapore Manufacturing Pte Ltd
Tuas, Singapore
Purchase Order No

- 1 – SP2000 Blender – G1951-B01-001
- 1 – PH600 Post Hoist – G1951-D01-001
- 1 – Comill U5 Mill with Hopper – G1951-M01-001

Revision History

Rev	Date	Revision Description	Prepared By (Signature)	Authorised by (Signature)
R0	05 June 07	Initial Issue	Barrie James	S. Eling
R1	07 Aug 07	As built	B Walmsley	S Eling
R2				
R3				
R4				
R5				

ABBREVIATIONS

The following abbreviations may be used within this document.

AFGB	Aeromatic-Fielder Ltd	IBC	Intermediate Bulk Container
AHU	Air Handling Unit	ICQ	Installation, Commissioning & Qualification
API	Active Pharmaceutical Ingredient	IQ	Installation Qualification
BSL	Buck Systems Limited	OIT	Operator Interface Terminal
C&I	Controls and Instrumentation	MP	Multi Processor
CIP	Clean In Place	N/A	Not Applicable
COSHH	Control of Substances Hazardous to Health	NWL	Narrow-Way Loaded
DQ	Design Qualification	OEM	Other Equipment Manufacturer
DSCR	Design Specification Change Request	OMM	Operation & Maintenance Manual
EMC	Electro-Magnetic Compatibility	OQ	Operation Qualification
FAT	Factory Acceptance Test	PC	Personal Computer
FBD	Fluid Bed Dryer	P & I D	Process & Instrumentation Diagram
FBGD	Fluid Bed Granulator Dryer	PLC	Programmable Logic Controller
FDS	Functional design Specification	PLS	Proximity Laser Scanner
FHU	Fluid Handling Unit	PM/PE	Project Manager / Engineer
FIBC	Flexible Intermediate Bulk Container	QASV	Quick Acting Safety Valve
FS	Functional Specification	QC	Quality Control
GAMP	Good Automated Manufacturing Practice	RMDU	Raw Material Dispensing Unit
HD	Head	SAT	Site Acceptance Test
HEX	Hexagonal	SG	Spray Granulation
HDS	Hardware Design Specification	SKT	Socket
HHT	Hand Held Terminal	SO	Shop Order
HMI	Human-Machine Interface	SWL	Safe Working Load
		VFC	Volt-Free Contact
		WIP	Wash in Place

CONTENTS

PRELIMINARY PAGES

SECTION PAGE

BUCK SYSTEMS SIGNATURE PAGE	II
ABBREVIATIONS	III
CONTENTS.....	IV

SAFETY AND GENERAL NOTICES

I. MACHINE USE DISCLAIMER	VI
II. SAFETY.....	VI
III. BUCK DETAILS	VIII
IV. SPARES AND SERVICE.....	VIII

SECTION 1 EQUIPMENT DESCRIPTION

1.1 OVERVIEW	3
1.2 DESCRIPTION	6
1.3 BUCK VALVE PRINCIPLE OF OPERATIONS	17
1.4 CONTROL.....	18
1.5 SEQUENCE OF OPERATION	19
1.5 INTERLOCKS.....	23
1.6 ALARMS/FAULTS	25
1.7 SERVICES	26

SECTION 2 OPERATING INSTRUCTIONS

2.1 OVERVIEW	3
2.2 MACHINE INITIAL SET-UP	7
2.3 AUTO MODE OPERATION	7
2.4 MANUAL OPERATION.....	11
2.5 SYSTEM TAGS.....	12
2.6 INTERLOCKS.....	14
2.6 PROCESS ALARMS	16
ANNEX 'A' ELECTRONIC RECORD & 21 CFR PART 11 COMPLIANCE	21

SECTION 3 INSTALLATION, MAINTENANCE & SPARES

3.1 MAINTENANCE SCHEDULES.....	3
3.2 SP2000 BLENDER (B01)	4
3.3 PH600 POST HOIST (D01)	9
3.4 MILL ASSEMBLY	13
3.5 RECOMMENDED SPARE PARTS	15

SECTION 4 SUPPLIER'S INFORMATION

SECTION 5 SIMPLIFIED PARTS LIST & DRAWINGS

SECTION 6 INSTALLATION

6.0 SAFETY.....	3
6.1 PH600 POST HOIST (D01) - INSTALLATION	3
6.2 BLENDER (B01).....	7
6.3 U5 MILL (M01).....	11

SECTION 7 CERTIFICATION

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems.

Blank Page

Safety and General Notices

I. Machine Use Disclaimer

These machines must NOT be used for purposes other than those for which they have been supplied under contract from Buck Systems. Failure to use the machines for the purposes as described in the contract nullifies any warranty or injury claim that could arise as a result of this misuse.

II. Safety

II.1 General

As automatic machines accessible to operators, the equipment described in this manual is potentially dangerous!

No attempt to install, run or maintain the equipment must be made before referring to this manual.

Ensure all personnel are clear of all rotating and hazardous parts before pressing reset, or releasing the emergency stop button.

Always turn off the main disconnect switch before approaching the active parts of the machine or performing any operation within reach of live or moving parts.

II.2 Guards & Interlocks

This equipment is guarded to prevent injury to operators. Do NOT attempt to run this equipment with any guards or panels removed (or incorrectly fitted) or with any of the safety interlocks overridden (either mechanically or electrically). Failure to observe this instruction may result in serious injury to personnel.

II.3 Guard against Electric Shock

All electrical connections must be made by a qualified electrician and must conform to local electrical codes and earthing (grounding) practices. Before connecting the machine to a power source, ensure the supply voltage is the same as specified in the electrical wiring diagrams, in Section 5 of this manual. Disconnect and lock out power before opening any electrical enclosures.

II.4 Safety Glasses

Industry approved safety glasses should be worn at all times while operating or maintaining any part of the equipment.

II.5 Hearing Protection

Industry approved hearing protection should be worn at all times while operating or maintaining any part of the equipment.

II.6 Clothing

Ensure that suitable protective clothing for the products being run is worn correctly at all times. Do NOT wear loose clothing, or have long hair or jewellery exposed when operating or maintaining the machine. All operators and maintenance personnel should wear non-slip footwear.

II.7 Warning Labels

Pay strict attention to the caution, warning and danger signs displayed on the machine.

II.8 Working Environment

Ensure all sides of the machine are easily accessible for maintenance.

Keep the floor around the machine clean and free from product, water or other objects. Clutter of all types MUST be kept to a minimum. Run the machine only when all personnel and foreign objects are clear.

II.9 Personnel

All operating and maintenance actions must be carried out by qualified personnel.

II.10 Cleaning

Protective clothing and hand and face protection must be worn to avoid injury to personnel during the cleaning of the machine.

II.11 Residual Risk

Before carrying out any preventive/ corrective maintenance to the machine, ensure the following;

- the machine has been shut down correctly,
- the main electrical supply has been switched off at the isolator,
- the main electrical isolator has been locked off,
- the pneumatic system has been de-pressurised.

II.12 COSHH

All oils and lubricants recommended for use on the equipment, as supplied under contract, are suitable for the purpose for which the equipment was supplied. The oils and lubricants are safe for use under the Terms and Conditions of the Substances Hazardous to Health (COSHH) Act, 2002.

II.13 De-Commissioning

Should you require to de-commission the machine as supplied under the contract, from Buck Systems, please contact us at the address listed below. Buck Systems is pleased to offer this service.

II.14 Safe Handling

In the interests of safety and for the general protection of the machine Buck Systems strongly recommend that all installation procedures (*i.e.* transportation in plant on initial machine delivery, positioning and connection of supplies) are supervised by Buck Systems personnel. In addition, should the machine require relocation at anytime this should also be supervised by Buck Systems personnel.

II.15 Lifting Heavy Weights

HEAVY WEIGHTS - Equipment weighing more than 20kg must be lifted using suitable mechanical lifting apparatus.

LIFTING APPARATUS – Lifting apparatus must only be used in accordance with the manufacturers instructions and local health and safety regulations. All lifting apparatus and slings must be approved.

II.16 Disposal

This equipment should be disposed of in accordance with local regulations. Electrical and electronic components used in this equipment may contain toxic or hazardous substances and must be disposed of in accordance with the equipment manufacturer's disposal instructions and local regulations for the disposal of hazardous waste.

III. Buck Details

If you do have any questions, please do not hesitate to contact us at the following address:

Buck Systems.,
Wharfdale House,
257 Wharfdale Road,
Tyseley,
Birmingham B11 2DP.

Tel: +44 (0) 121 - 765 5800
Fax: +44 (0) 870 622 0923
E-mail: engineering@buck-systems.com.

IV. Spares and Service

For spare parts or service queries, please do not hesitate to contact us at the above address:
or r mail: spares@buck-systems.com.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems.

Blank Page

SECTION 1

Equipment Description

1.1 Overview (Fig 1).....	2
1.1.1 General.....	2
1.1.2 Blender (G1951-B01).....	3
1.1.3 Post Hoist (G1951-D01).....	3
1.1.4 Mill Assembly.....	3
1.2 Description.....	5
1.2.1 SP2000 Blender (G1951-B01).....	5
1.2.2 PH600 Slewing Post Hoist (G1951-D01) (Figs 12 – 14).....	12
1.2.3 Mill Assembly (Figs 15 & 16).....	15
1.3 Buck Valve – Principles of Operation.....	16
1.4 Control (Figs 11, 17 & 18).....	17
1.4.1 General.....	17
1.4.2 Main Control Panel.....	17
1.4.3 Operator Control Panel.....	17
1.4.4 Hoist (Remote Buck ‘C’ Valve Control).....	17
1.4.5 Pneumatics Control Panel.....	17
1.4.6 Control Hardware.....	17
1.4.7 Trapped Key System (Fig 17).....	17
1.5 Services.....	18

SECTION 1

Equipment Description

1.1 Overview (Fig 1)

1.1.1 General

The IBC Blender suite consists of SP2000 Single Pedestal Blender (G1951-B01), PH600 Slewing Post Hoist (G1951-D01) and a Mill Assembly (G1951-M01). All machines are located within a safe zone protected by a 'Trapped Fortress Key' safety system.




Fig 1 - IBC Blending Suite

1.1.2 Blender (G1951-B01)

SP2000 Single Pedestal Blender (G1951-B01) is designed to mix homogeneous dry powder and granular materials contained within a sealed Intermediate Bulk Container (IBC). It allows large quantities of product to be blended in short time periods, and in completely hygienic conditions. The unit is a single pedestal, tumbling Blending Machine designed to handle standard Buck Systems' IBC with a footprint of 1200 mm x 1200 mm, and capacities of 750, 1500 or 2000 Litre.

The IBC is located and clamped in a cage, mounted on a rotating shaft. As the shaft turns, the IBC is rotated about one of its diagonals. At each rotation the product contained comes into contact with the following:

- One flat surface (top of container).
- Two edges (diagonals of container).
- One truncated pyramid (hopper of container).

The product turns on itself in a non-symmetrical way, thus ensuring effective blending. Rotation speed of the blender is in the range 2 to 15 RPM.

1.1.3 Post Hoist (G1951-D01)

The Post Hoist allows the G1951-M01 assembly (Comil U5 Mill with an 80 L. hopper and an active Buck 'C' valve) to be lifted and docked over the passive Buck 'C' valve of the inverted IBC clamped in the blender. This is to allow gravity discharge product from the IBC. The Post Hoist forks hold the U5 frame in position during the discharge sequence, thus eliminating the need for a complete discharge station.

1.1.4 Mill Assembly (G1951-M01)

The Mill Assembly allows the milling of the product contained within the hopper as it flows into the inverted IBC. A Buck 'C' Type Active Valve is fitted to the Mills discharge chute to provide an interface with the passive valve on the receiving IBC. The mill assembly is fitted with a dust extraction facility. A design function of the Mill Assembly enables avoidance of cross contamination between the product in the IBC and the product in the Hopper. Mill and Buck valve derive their service and control from the Post Hoist control system via a Harting connection.

Operation and Maintenance Manual
 SP2000 Blender, Post Hoist & Mill by Buck Systems




Fig 2 - SP2000 Blender – Construction Drawing (Plan & Side Views)

1.2 Description

1.2.1 SP2000 Blender (G1951-B01)

General

The SP2000 Blender, is illustrated in Figs 2 - 11,

The IBC is loaded onto the Blender's lift platen, by hand pallet truck, where it is raised and clamped in position by a pneumatic system, and screw jacks. Main drive for rotating the IBC is through a shaft mounted, inverter controlled, direct drive, 3 phase electrical gearmotor with brake.

Construction

In construction the SP2000 Blender comprises the following principle assemblies:

- Support Frame
- Drive Assembly
- Pneumatic System
- Rotating Cage with Swinging Arms Assembly
- Control Panels

The support frame is mounted outside the blending room and provides a 'Through the Wall' drive for the Rotating Cage (containing the IBC), which is inside the blending room.

Support Frame

A static frame supports the drive system and provides anchor points for fixing the complete machine to the floor. The support frame is made from grade BS EN 10088-1.4301 (304) stainless steel, rolled, hollow section, and is enclosed in a housing made from grade BS EN 10088-1.4301 (304) stainless steel plate. It houses the following sub-assemblies:

- Shaft-mounted, direct drive, gearmotor with brake and torque arm (Figs 2, 4, 6 & 7).
- Drive shaft and bearings (Figs 2, 4 & 6).
- Pneumatic control system (Fig 11).
- Electrical junction box (Fig 11).
- Stainless Steel Wall Plate (Fig 8).

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems




Fig 3 - Blender (G1951-B01) – Construction Diagram (end view)

Drive System

Two Plummer block bearings, mounted on the static frame, support the rotating cage's 100mm diameter shaft. The cage is driven via a shaft mounted, inverter controlled AC gearmotor. A torque arm prevents rotation of the drive unit (Figs 4, 6 & 7).

Three different sensors monitor Cage and IBC rotation:

- Cage Upright position is detected by a base-frame-mounted sensor, which senses the end of a long arm that rotates with the drive shaft (Fig 5).
- Number of rotations is detected by a base-frame mounted sensor that senses each passage of a target disc mounted on the drive shaft (Fig 5).
- Speed of rotation is detected by a base-frame mounted sensor, which senses the passage of teeth on a 30 tooth indexing wheel mounted on the drive shaft (Fig 6).

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems.




Fig 4 - Blender (right side) – Rotating Cage shaft, bearing blocks and gearmotor




Fig 5 - Blender – 'A' Cage position arm and 'B' indexing wheel/sensor




Fig 6 - Blender (left side) – Rotating Cage shaft, indexing wheel, gearmotor and bearing blocks




Fig 7 - Blender – Direct Drive Gearmotor Assembly & torque Arm

Rotating Cage

A rotating cage, made from BS EN 10088-1.4301 (304) stainless steel, is fixed to the main shaft. The cage clamps the container and supports it while the blending operation takes place. A screw jack system, driven by pneumatic (Air) motor, is used to actuate the clamping mechanism. When a 700 litre IBC is loaded onto the machine, a swinging arm assembly is activated, and lowered, to enable supplementary top clamp air bungs engage with the respective corner stops on the top side of the container. All moving parts are totally enclosed in the box section construction of the rotating cage (See Figs 2 - 4 & 8 – 10)



Fig 8 - Blender – Cage Assembly with IBC in position



Fig 9 - Blender Cage – Air motor Assembly




Fig 10 - Blender Cage – IBC Earthing Arrangement

Pneumatic Control System (Fig 11)

The pneumatic system has the following functions:

- To provide a clamping system mechanism, including activation of the Swinging Arm assembly for 700 litre IBC.
- To monitor container security in the cage by means of air check pressure sensing pads.

Plastic pipework and rotating unions are used to connect the pneumatic system through the support frame. The air supply is connected to machine via the filter/regulator assembly mounted on the base panel behind the motor. See Fig 11.




Fig 11 - Blender – Drive Motor, Pneumatics' Base Plate Assembly, Machine Junction Box

1.2.2 PH600 Slewing Post Hoist (G1951-D01) (Figs 12 – 14)

General

The PH600 Post Hoist enables an IBC be lifted and docked over the inlet of a downstream process. This allows gravity discharge of product from the IBC. The Post Hoist forks hold the IBC in position during discharge sequence, eliminating the need for a dedicated discharge station.

Construction

In construction, PH600 Post Hoist comprises the following principle assemblies:

- Lifting Column
- Slewing Base
- Lifting Forks
- Control Panel

The hoist is located within the secure zone alongside the Blender.

Lifting Column (Fig 12)

The basic hoist column construction consists of a carbon steel structure housed within a stainless steel shroud. Lift assemblies fitted to all hoists consist of a braked motor/gearbox assembly mounted at the top of the column which drives a double continuous chain loop connected to the lift carriage.

The Hoist utilises a 1.5 kW, inverter controlled lift motor complete with brake and fitted with thermistors. Any services required to or from the lifted load are passed through the carriage to the cable chain inside the column.

The normal lift assembly uses a white smooth fabric reinforced belt to pass through the carriage to close off the open front of the hoist column. This is fixed top and bottom.

Lift limit switches are mounted on a rail within the hoist column. These are mechanical limit switches which can be positioned anywhere in the lift height of the column. The position of the lower limit switch is the datum for the optical encoder system. See Section 5, G1951-D0`-901 P&I Drawing for the location, quantity/function of limit switches and encoded stops.

Slewing Base (Figs 12 & 13)

General

The slewing base consists of a base plate mounted slewing ring to which the slewing column is fastened. The hoist cannot be slewed more than 350°. The slewing end stops are mounted within the base unit on a continuous ring of mounted holes, allowing the end stops to be positioned anywhere within the slewing range of the hoist.

Powered Slew

Slewing is powered by a 0.18 kW, braked, motor/gearbox unit fitted with thermistors. Proximity switches mounted on the slewing ring's end stops to control the slew positions. Stops are inserted/released pneumatically.

Lifting Forks (Figs 12)

A standard fork assembly with 1450 mm reach is attached to the column by means of the carriage assembly. The forks are designed to handle Buck Systems' Intermediate Bulk Containers of up to 900 kg capacity.

Operation and Maintenance Manual
 SP2000 Blender, Post Hoist & Mill by Buck Systems.




Fig 12 - PH600 Post Hoist




Fig 13 - PH600 Post Hoist Powered Slewing Ring




Fig 14 - PH600 Post Hoist – Operating Positions

1.2.3 Mill Assembly (Figs 15 & 16)

General

The Mill assembly consists of a Comil U5 Mill unit with an additions hopper mounted on its infeed, and 250 mm dia. Buck Type 'C' Active Valve mounted on its discharge chute. The whole assembly is mounted on Trolley frame.

In construction:

The trolley assembly is fabricated from tubular stainless steel and is fitted with four wheels (two fixed and two castors).

The Ytron-Quadro U5 Comil, which is fabricated from stainless steel is attached to the trolley's mid support cross members. Buck 250 mm dia Type 'C' Active valve is flange-bolted to the mill's discharge chute.

A stainless steel hopper with lid and clamp assembly is mounted on the cross supports of the trolley and connected to the mill's infeed by means of 6" flexible joint, spool piece and clamps.

A junction box is mounted on the trolley frame to interface the Mill and Valves service and control requirement with the Post Hoist control panel, via a Harting connection.




Fig 15 - Mill Assembly (G1951-M01)

Buck 'C' Active Valve

Two x 250 mm dia. Buck 'C' Valve Assemblies, which include valve support plate, are flange-bolted respectively to the infeed and discharge chutes of the Frewitt Mill (The mill is mounted on a trolley assembly), with electrical pneumatic connection made to the Post Hoist Control Cabinet by means of Harting plug arrangements.

The following additional items are fitted as part of the Buck valve assembly:

- A 90° rotary actuator on the Buck valve that opens and closes the valve when it is docked with the receiving IBC.
- EPDM Seal and Compensator
- Vibroflow vibrator

Valve Docked & Safety Proximity Switches (Fig 16)

A proximity sensor detects the presence of the container when it is properly docked with the Buck Valve. A second (safety) switch, identified as 'Docking Over Travel', is activated if there is docking detection failure. This second switch is a hardwired interlock used to stop the hoist immediately.




Fig 16 - Mill Assembly (G1951-M01) – Buck Valve

1.3 Buck Valve – Principles of Operation

A 250 mm Dia Buck 'C' Type Active Valve is fitted to the Mill. The BUCK® valve consists of one active half flap mounted on the stationary equipment which docks with the appropriate passive half-flap mounted on an IBC. In operation, the BUCK® valve system ensures that product can be transferred between a process and an IBC with almost no contamination of the surrounding area. When closed, the two parts of the valve seal the product areas. The two halves are brought together in a docking manoeuvre, and clamped.

A vacuum generator is used to improve adhesion between the active and passive faces of the BUCK® valves during clamping operations. Vacuum pressure is monitored and if it rises above the nominal operating pressure prior to locking, the opening of the valve will be inhibited.

The combined valve can then be opened to allow passage of product. The design of the valve ensures that product flows over the inside surfaces of the valve halves, and does not touch the outside surfaces. This means that when the two halves of the valve are separated again, there should be no product to contaminate the surrounding area.

1.4 Control (Figs 11, 17 & 18)

1.4.1 General

The IBC Blender's control system consists of a Main Control Panel, Operators' Control Panel, and Pneumatics Control Panel. Two modes of operation are available to the Operator/Technician i.e. Auto and Manual which are selected via the Human Machine Interface (HMI). There are three levels of access to the control system, i.e. Operator, Supervisor and 'Configuration'. Access to each level is controlled by entering a four digit code via the HMI.

1.4.2 Main Control Panel

The control system comprises a painted, mild steel Main Control Panel, is located in a technical area. The panel and devices supplied are suitable for operation in a safe (non-hazardous) area. The panel houses the controlling PLC, the AC inverter for the drive motor and the associated control and protection equipment. An emergency stop pushbutton is fitted on the panel door which forms part of the hardwired safety circuit.

1.4.3 Operator Control Panel

The stainless steel, flush, wall mounted operator control panel, is mounted outside the blending room. The panel and devices supplied are suitable for operation in a safe (non-hazardous) area. An Industrial PC with Touch Screen (SCADA) is mounted within the panel, to provide the operator the means by which to interact with the machine. An emergency stop, local control pushbuttons /indicators and one of a dual trapped key safety system are fitted to the panel.

1.4.4 Hoist (Remote Buck 'C' Valve Control)

The control (opening and closing) of the IBC Buck 'C' valve is actuated by G1951-M01 via an umbilical line and Harting type plug and socket arrangement. The umbilical line will supply the services required to control the valve and provide feedback to the control system, when connected to the post hoist plug.

1.4.5 Pneumatics Control Panel

A panel mounted on the back plate, within the pedestal, includes the pneumatic controls for the blender.

1.4.6 Control Hardware

The PLC which is supplied to control the blender is a Siemens S7-300 series model which will interface via the Siemens MPI protocol to a Fanuc Industrial PC with Touch Screen. Drive motors are controlled via Siemens inverters.

1.4.7 Trapped Key System (Fig 17)

A trapped fortress key safety system is incorporated which will control access to specific functions or operations of the machine. The protected zone will be the room where the blender will be located. Access to the room will be via a locked door, which can only be opened via the safety key, which normally resides in the operator panel. With the Safety key located and operated in the operator panel, the machine will function normally and all the blender functionality can be facilitated. The Safety key is then transferred from the operator panel to the blender room access door. This action will unlock the door and access to the blending room will be granted. Upon completion of the IBC operations (load/unload IBC); the door may then be locked in the closed position, which will allow the removal of the Safety key, which is then transferred back to the operator panel. With the key back in the panel and operated, the blender functionality is again enabled after the controls circuits have been reset via a pushbutton.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems



Fig 17 - IBC Blender Suite – Operator Control Panel

1.5 Services

To function correctly the IBC Blender system requires the following services:

Electrical

Electrical supply voltage: Customer Supply – 400V +/- 10%, 3ph N + E, 50Hz.

Pneumatic

Compressed air at: Max I/P Pressure - 10 Barg
Working pressure - 5.5 Barg

Earthing

The customer is responsible for providing a good quality, noise-free earth supply, with sufficiently low, earth loop impedance. Failure to provide such a supply may render the machine out of compliance with the requirements of the EMC directive¹.

¹ Electromagnetic compatibility directive (89/336/EEC, as amended) of the European Economic Area as implemented by the UK EMC regulations 1992 (SI 1992/2372, as amended).

SECTION 2

OPERATING INSTRUCTIONS

Table of Contents

2.1 Operator Safety.....	3
2.2 Machine Initial Set-up.....	4
2.3 Auto Mode Operation.....	5
2.3.1 IBC Blending System - Loading Procedure	5
2.3.2 Blend Cycle.....	5
2.3.3 Product Addition Procedure (Hoist operation)	6
2.3.4 Unloading Procedure	8
2.4 Manual Operation.....	8
2.4.1 General.....	8
2.4.2 List of Manual operations:.....	8
2.5 System Tags.....	9
2.6 Interlocks	11
2.6.1 General.....	11
2.6.2 Hardwired Safety Interlocks	11
2.6.3 System Interlocks.....	12
2.7 Process Alarms.....	13
2.7.1 General.....	13
2.7.2 Alarm Conditions.....	13
2.7.3 Alarm/Fault Summary	16
Appendix 'A' Electronic Records and 21 CFR Part 11 compliance	18

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Blank Page

SECTION 2

Operation

2.1 Operator Safety

Safety Notes

The IBC Blender and associated equipment must only be operated by persons trained to do so.

Do not stand or climb on any part of any machine.

Only start machines when:



All guards (as applicable) are in place and Control Panel doors are closed.

Nobody is in the immediate vicinity of the working area or will be endangered when the machine starts.

Check the machine for any obvious visible damage or defects before operating.

Any faults are to be reported and rectified immediately.

2.2 Machine Initial Set-up

WARNING

COLLISION HAZARD, ENSURE THAT THE BLENDER AREA IS CLEAR OF PERSONNEL, TOOLS AND OTHER PORTABLE EQUIPMENT.

Complete the following procedure:

At the Blender check/ensure:

- Air supplies are connected, turned ON and regulated to 5.5.BarG.
- Drive motor local Isolator set to ON.
- All guards/covers in place and secure.

At the Post Hoist check/ensure

- E.Stop push button set to 'restored' position (twist clockwise to release).
- Control Panel door closed and locked.
- Mains disconnect switch/local isolator set to ON

At the MCP check/ensure:

- Emergency Stop is in 'released' position (twist clockwise).
- Main power disconnect switch set to ON

At the OCP:

- Ensure 'Trapped Key' is in position on the panel.
- Check that the Emergency Stop is in 'released' position (twist clockwise).
- Press Controls ON/RESET push button – integral indicator will illuminate and the control circuit is activated.
If the indicator fails to illuminate request technical assistance.
- Fanuc PC is active with default screen displayed.

The IBC Blender System is now ready for operation in Automatic or Manual mode.

2.3 Auto Mode Operation

To operate the Blender in 'Auto mode' complete the procedure outline in Paras 2.3.1 to 2.3.3.

2.3.1 IBC Blending System - Loading Procedure

The blender access door is opened following the transfer of the Safety key from the operator panel. The IBC is loaded, via a pallet truck onto the lifting platen of the blender. The door is closed and locked, and the key returned to the operator panel. The blend recipe is selected from the SCADA, the parameters reviewed by the operator and provided the operator is satisfied, the cycle is initiated.

2.3.2 Blend Cycle

The operator manually enters in the SCADA the blend recipe ID indicated by a 3rd. party terminal, and a 10 character alpha-numeric batch number. The operator then checks the following three points:

- Nobody is in the process room
- No objects potentially interfering in the machine operation
- There is IBC in the blender (waiting to be clamped)
- The Mill assembly is loaded onto the hoist forks (only if recipe requires product addition)
- The Harting plug is connected (only if recipe requires product addition)
- Displayed parameters are correct

Provided the operator is satisfied with all six checks, command to start is given by means of the "Start" softkey. This softkey is interlocked as follows:

- "Start" softkey disabled if IBC is not detected
- "Start" softkey disabled if Mill assembly (G1951-M01) is required but not detected
- "Start" softkey disabled if Mill assembly (G1951-M01) is required but Harting plug not connected

After the command to start the blend cycle has been received, an audible alarm beacon (HS xxx-9201) will warn during 5 seconds about the imminent start of machine operation. Once are these 5 seconds elapsed, the lifting platen will be raised by energising the raise solenoid valve (XV xxx-3000A), which in turn will drive the raise/lower air motor (M xxx-3000). An air check circuit is utilised to confirm the IBC is clamped. This is achieved by the IBC itself, sealing the venting air, which is normally escaping via a port within each of two rubber stoppers. As the IBC seals the ports, the pressure within the check unit rises, which in turn operates the cage clamped pressure switch (PS xxx-3300) to confirm the IBC is clamped. The switch is continually monitored in the software during blending processes to ensure the IBC remains clamped.

After a minimal delay, the brake is released by energising the brake contactor (JY xxx-2000B) and the drive motor forward run signal to the AC inverter drive will be energised, the blending cage will accelerate up to the speed referenced within the recipe. The controlled operating range of the blender is between 2-15 RPM, which is detected by a rotational

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

speed sensing switch (ST xxx-2102), fed back to the PLC and continuously monitored against a tolerance of $SP \pm 0,5$ RPM.

The blender will continue to run at this speed until the blend cycle timer has elapsed, which will result in the blender decelerating to creep speed, which is approximately 1 RPM. When the creep speed signal has been achieved, the blender will continue to rotate at creep speed until the cage upright proximity switch (XS xxx-2200) detects that the IBC is in the upright position within the cage. The IBC will continue to rotate as before, at creep speed, until an over run timer has elapsed within the PLC, which will de-energise the drive motor forward run signal. After a short delay, the drive motor reverse run signal will energise, and the blender will run at creep speed in the reverse direction until the cage upright switch is detected again. This will result in the inverter de-energising and the brake contactor (JY xxx-2000B) de-energising to stop the rotation of the blender. The blend report will be automatically generated.

Since PDF files are also stored locally for backup purposes, the transfer failure of these files is not regarded as critical and the system will be able to carry on in the sequence regardless of the transfer check result. After the check, the blend cycle is considered complete and the system unloads the IBC as described within §3.3.3.

A facility is included on the blend cycle, which will permit the operator to hold the current blend cycle via the SCADA. Should the hold be selected during the cycle, the blender will decelerate and then stop at the upright position, which will also freeze the cycle timer.

When the blender has stopped, the SCADA will display options to either Abort or Continue the cycle.

If abort is selected, the batch report will be automatically generated, and once again, the operator will have the possibility to reprint it as many times as necessary, before clearing the batch data. If continue is selected, the cycle will continue from the point at which the cycle was stopped.

2.3.3 Product Addition Procedure (Hoist operation)

Note: If product addition is needed during the blending cycle, the Post Hoist will be used and therefore it needs to be prepared for operation before starting the blend cycle. The milling sequence will require two parameters the mill speed in % and a milling time in seconds. With the hoist at the Load/Unload position (ZS xxx-3510A) and at the Load/Unload Slew Position (XS xxx-3520), the operator will load the G1951-M01 assembly onto the Post Hoist by pedestrian truck. Once G1951-M01 assembly is loaded, the operator will connect the Harting plug, in order to make possible the Mill assembly operation by the system.

Upon completion of a blending phase, the system can perform an “Add product” action. This is according to the previously downloaded recipe, and fully automatically executed. To add product, the system decelerates the blending cage into creep speed and initiates the invert function. The blender will continue to rotate at creep speed until the cage inverted proximity switch (XS xxx-2201) detects that the IBC is in the inverted position within the cage. The IBC will continue to rotate at creep speed, until an over run timer has elapsed within the PLC, which will de-energise the drive motor forward run signal. After a short delay, the drive motor reverse run signal will energise, and the blender will run at creep speed in the reverse direction until the cage inverted proximity switch (XS xxx-2201) is detected again. This will result in the inverter de-energising and the brake contactor (JY xxx-2000B) de-energising to stop the rotation of the blender.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

At this point, the IBC is inverted, the Lift Motor run forward signal is energised and the Post Hoist will rise at fast speed to the pre-stop Slew Height (UA xxx-3511/2). The Inverter will then run at slow speed to the Slewing Height (UA xxx-3511/4). The Lift Motor run forward signal is then de-energised and the Lift Motor will stop. The Slew Motor run Forward Contactor (JY xxx-3502B) is energised and the Post Hoist will slew. The Post Hoist will Slew to the Discharge Slew position (XS xxx-3521), as confirmed by the SCADA status mimic 'Discharge Slew Position'. The Slew Motor run forward signal is then de-energised and the Slew Motor will stop. The Lift Motor run reverse signal is energised and the Post Hoist will lower at slow speed until docking is detected by the proximity switch (ZS xxx-4000) mounted in G1951-M01. The SCADA status mimic will display 'G1951-M01 Docked to IBC'. The Lift Motor run reverse signal is then de-energised and the Lift Motor will stop. Docking Overtravel position switch (YS xxx-4001/1,2) is a hardwired interlock utilised to stop the hoist, in the event of a docking detection failure.

Buck Valve Vacuum Generator solenoid (XV xxx-5203) is energised to generate vacuum between the two Buck valve disks and any hoist movement will be inhibited as long as vacuum is active. After a short delay, the Open Buck Valve solenoid (XV xxx-5000A) is energised to open the Buck 'C' valve, confirmed by (ZSO xxx-5100) and this feedback triggers the start signal for the mill to run at its fixed speed. The speed of the Mill will be displayed on the HMI screen in RPM. The time remaining for the milling sequence will also be displayed on the HMI screen in seconds.

When the recipe mill time elapses, the mill stops and the Buck Valve will close and de-dust in the following way. The Buck Valve solenoid (XV xxx-5000A) is de-energised to close the Buck 'C' valve, confirmed by (ZSC xxx-5100). Then the dust extract shroud vacuum generator (XV xxx-5204) will energise for ten seconds confirmed by the vacuum switch (PS xxx-5204). Then the Buck valve vacuum solenoid (XV xxx-5203) will de-energise to stop vacuum generation between the two Buck valve disks. With the dust extract complete the hoist raise function is no longer interlocked.

The Lift Motor run forward signal is energised and the Post Hoist will rise at slow speed to the Slew Height (UA xxx-3511/4), as confirmed by the SCADA status mimic 'Discharge Slew Position'. The Lift Motor run forward signal is de-energised and the Lift Motor will stop. The Slew Motor run reverse contactor (JY xxx-3502C) is energised and the Post Hoist will Slew to the Load/Unload Slew position, detected by XS xxx-3520, as confirmed by the SCADA status mimic 'Load/Unload Slew Position'. The Slew Motor run reverse signal is then de-energised and the Slewing Motor will stop. The lift motor run reverse signal is energised and the Post Hoist will lower at fast speed to the Pre-stop Load/Unload height (UA xxx-3511/1). The Inverter will then run at slow speed to the Load/Unload height detected by (ZS xxx-3510A). At this point, the SCADA status mimic will indicate 'Load/Unload Position', the Lift Motor run reverse signal is de-energised to stop the Lift Motor and the next blending phase will start.

The blender motor brake is released by energising the brake contactor (JY xxx-2000B). The drive motor forward run signal to the AC inverter drive will be energised and the blending cage will accelerate up to the speed referenced within the recipe and will follow the sequence already described in chapter 3.3.1. Blend Cycle.

2.3.4 Unloading Procedure

Once all Blend Phases are completed, the system initiates the unload sequence. The lifting platen is lowered by energising the lower solenoid valve (XV xxx-3000B) and driving the raise/lower air motor (M xxx-3000) in the reverse direction. A high signal detected for the cage-lowered proximity switch (XS xxx-3400) completes the lowering process. At this point in the process, the SCADA will display that the unload sequence is complete, and the IBC can be unloaded. After the operator has gained access to the blender room, the operator will unload the IBC from the blender platen to complete the blending process. The machine is then available for processing the next blend cycle.

2.4 Manual Operation

2.4.1 General

Manual operation for maintenance or diagnostic routines is only available to supervisors and configurators. All the functionality achieved by the automatic sequence is available via the manual operations facility, and the mode of operation is subject to the global machine interlocks. All the movements will be at the lowest speed available and executed by momentary action (soft keys need to be pressed and hold for continuous movement. If softkey is released, movement stops immediately, no latch).

2.4.2 List of Manual operations:

Equipment	Manual Action	Comment
Blender (B01)	Cage Raise	Nominal Speed (only speed available)
	Cage Lower	Nominal Speed (only speed available)
	Cage rotation forward	Low Speed (aprox. 1 RPM)
	Cage rotation reverse	Low Speed (aprox. 1 RPM)
Hoist (D01)	Hoist Raise	Low Speed
	Hoist Lower	Low Speed
	Hoist Slew to Process	Nominal Speed (only speed available)
	Hoist Slew to Load	Nominal Speed (only speed available)
Mill/Buck 'C' valve (M01)	Mill Rotate	Nominal Speed (only speed available)
	Open Buck 'C' valve	None
	Close Buck 'C' valve	None
	Generate Vacuum	None

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

2.5 System Tags

The system tags listed in the following table relate to P&I Diagrams G1951-B01-901, G1951-D01-901 and G1951-M01-901, which are contained in Section 5

TAG	Description
Main Control Panel	
PS XXX-9010	Main Air Pressure Switch
HSS XXX-8002	Emergency Stop
Operator Panel	
OIT XXX-8200	HMI (Fanuc Touch Screen PC)
HS XXX-9200	Controls ON reset button
YI XXX-9200	Controls ON lamp
HSS XXX-8260	Fortress Key
HSS XXX-8000	Emergency Stop
Hoist	
HSS XXX-3510	Emergency Stop
XS XXX-3521	Process Position Slew
XS XXX-3520	Load/Unload Position Slew
M XXX-3502	Slew Motor
HSS XXX-3502	Slew Motor Isolator
JY XXX-3502B	Forward Contactor
JY XXX-3502C	Reverse Contactor
JY XXX-3502A	Run Contactor
ISS XXX-3502	Slew Motor Circuit Breaker
TS XXX-3502	Slew Motor Thermostat
M XXX-3500	Lift Motor
HSS XXX-3500	Lift Motor Isolator
TS XXX-3500	Thermistor
SC XXX-3500	Lift Motor Inverter
JY XXX-3500A	Supply Contactor
JY XXX-3500B	Brake Contactor
ISS XXX-3500A	Lift Motor Circuit Breaker
ISS XXX-3500B	Lift Motor Brake Circuit Breaker
ZS XXX-3510A	Load/Unload Overtravel Switch
SE XXX-3511	Position Encoder
ZS XXX-3512/2	Overtravel Switch
XS XXX-4701	Mill in Position
YI XXX-3001	Power Supply Healthy
Blender	
PS XXX-9000	Main Air Pressure Switch
PS XXX-3300	Cage Clamped Pressure Switch
ZS XXX-3410	IBC in Position
XS XXX-3400	Cage Down Position Switch
XV XXX-3000A	Clamp Solenoid
XV XXX-3000B	Clamp Solenoid
XV XXX-3000C	Air Check Enabled Solenoid

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

XS XXX-2200	IBC Upright Position Switch
XS XXX-2201	IBC Inverted Position Switch
ST XXX-2102	Rotational Speed Sensing Switch
M XXX-3000	Clamp/ Clamp air motor
M XXX-2000	Rotation motor
JY XXX-2000B	Brake Contactor
ISS XXX-2000B	Circuit Breaker
TS XXX-2000	Thermistor
HSS XXX-2000	Rotation motor Isolator
JY XXX-2000A	Supply Contactor
ISS XXX-2000A	Circuit Breaker
SC XXX-2000	Rotation Motor Inverter
MILL ASSEMBLY	
M XXX-4000	Mill Motor
HSS XXX-4000	Mill Motor Isolator
TS XXX-4000	Mill Motor Thermistor
SC XXX-4000	Mill Motor Inverter
JY XXX-4000A	Mill Motor Supply Contactor
ISS XXX-4000A	Mill Motor Circuit Breaker
ST XXX-4000	Rotational Speed Sensing Switch
ZS XXX-4000	Docking Switch
YS XXX-4001	Safety Switch
XV XXX-5203	Buck 'C' Valve Vacuum Generator Solenoid
FE XXX-5203	Buck 'C' Valve Vacuum Generator
PS XXX-5203	Buck 'C' Valve Vacuum Generator Vacuum switch
XV XXX-5204	Dust Extract Shroud Vacuum Generator Solenoid
FE XXX-5204	Dust Extract Shroud Vacuum Generator
PS XXX-5204	Dust Extract Shroud Vacuum Generator Vacuum Switch
XV XXX-5000A	Buck 'C' Valve Open Solenoid
XV XXX-5000B	Buck 'C' Valve Close Solenoid
XU XXX-5100	Buck 'C' Valve Open/Close Rotary Actuator
ZSO XXX-5100	Buck 'C' Valve Open Signal
ZSC XXX-5100	Buck 'C' Valve Closed Signal
Miscellaneous	
HS XXX-9201	Audio/Visual Alarm
YI XXX-9201	Audio/Visual Alarm

2.6 Interlocks

2.6.1 General

Read this Sub-section in conjunction with P&I Diagrams G1951-B01-901, G1951-D01-901 and G1951-M01-901 in Section 5. Machine sequences, regardless of whether in 'automatic' or 'manual' mode, are interlocked as described below.

2.6.2 Hardwired Safety Interlocks

Operator Panel Emergency Stop (HSS xxx-8000)

An emergency stop button is located on the operator control panel and will initiate an emergency stop of the entire Blending Room (Blender, Hoist and Mill) if pressed. Alarm recovery depends on the status of the equipment prior to emergency stop. If blending, the blending head will stop within one revolution.

Main Panel Emergency Stop (HSS xxx-8002)

An emergency stop button is located on the main control panel and will initiate an emergency stop of the entire Blending Room (Blender, Hoist and Mill) if pressed. Alarm recovery depends on the status of the equipment prior to emergency stop. If blending, the blending head will stop within one revolution.

Hoist Mounted Emergency Stop (HSS xxx-8001)

An emergency stop button is located on the machine and will initiate an emergency stop of the entire Blending Room (Blender, Hoist and Mill) if pressed. Alarm recovery depends on the status of the equipment prior to emergency stop.

Hoist Junction Box Mounted Emergency Stop (HSS xxx-3510)

An emergency stop button is located on the hoist junction box and will initiate an emergency stop of the entire Blending Room (Blender, Hoist and Mill) if pressed. Alarm recovery depends on the status of the equipment prior to emergency stop.

Safety Interlock Key (HSS xxx-8260)

The blender is protected by a dual trapped key safety interlock system. When the Safety key is removed from the operator control panel, the operation of the system (Blender, Hoist and Mill) is inhibited.

Blender Motor Overload

The blender is protected from overload by the inverter (SC xxx-2000). The current required to operate system at safe working load is set at the inverter. If this current is exceeded the blender will stop and the brake will be applied.

Lift Motor Overtravel

The hoist is fitted with an over travel switch ZS xxx-3512/1 which is integrated into the lift motor

M xxx-3500 raise control circuit. If the switch is operated the raise contactor control circuit is interrupted and the raise command to the inverter will remain de-energised, regardless of the state of the post hoist controlling PLC.

Note: the signal from the switch is also input to the controlling PLC, for alarm purposes.

2.6.3 System Interlocks

Hoist operation

The hoist cannot be moved from the 'parked' position if the blender is active.

Blender Operation

Blending operations cannot be initiated if the hoist is not in the 'parked' position

Cage Clamped Pressure Switch (PS 3300)

The cage clamped pressure switch (PS xxx-3300) monitors the pressure within the air check circuit. If the switch detects a low state, the blender drive motor is inhibited from operation.

Blending Head Rotation

The blending head will only rotate when the cage is clamped confirmed by the clamped pressure switch (PS xxx-3300).

Lift Motor Interlocks

The lift motor will not raise or lower, unless the hoist is slewed to the Load/Unload Slew Position confirmed by XS xxx-3520 or the Discharge Slew Position confirmed by XS xxx-3521.

Slew Motor Interlocks

The slew motor will not slew in either direction, unless the hoist is at the correct slewing height, confirmed by UA xxx-3511/4.

Batch Start Interlocks

The command to start a batch cycle is given by the operator by pressing the "Start" softkey. This softkey will be interlocked if any of the following situations occurs:

"Start" softkey disabled if IBC is not detected

"Start" softkey disabled if Mill assembly (G1951-M01) is required but not detected

"Start" softkey disabled if Mill assembly (G1951-M01) is required but Harting plug not connected.

This is to avoid the start of a batch cycle if the operator forgot any batch start prerequisite.

2.7 Process Alarms

2.7.1 General

Alarm conditions are monitored at all times whilst power is applied to the machine. If a fault occurs, the cause of the fault is indicated at the SCADA.

If an alarm occurs the system is immediately shut down. In this state, all motors are stopped, and all valves revert to their default state.

Once the cause of the alarm has been rectified and the alarm has been acknowledged, operations may continue.

In the event of an alarm occurring during blending, the alarm is recorded on the batch report. Once the cause of the alarm has been rectified and the alarm has been acknowledged the operator is given the option of continuing or aborting the blend. If the operator continues the blend a single batch report is generated on completion detailing both blend cycles. If the cycle is aborted, this will be confirmed on the batch report.

If the cause of the alarm is not corrected, the alarm will be re-displayed.

2.7.2 Alarm Conditions

Blender (G1951-B01)

The single pedestal blender monitors the following fault conditions:

Emergency Stop Pressed

Critical alarm. Alarm instantly when any of the Emergency Stops (HSS xxx-8000, HSS xxx-8002, HSS xxx-3510 or HSS xxx-8001) are activated.

Safety Key

Critical alarm. Alarm instantly when safety key (HSS xxx-8260) is removed from the Operator Panel.

Main Air Pressure Low

Critical alarm. Alarm instantly if pressure switch (PS xxx-9000) indicates below 4.5 BarG.

Monitoring will be "fail-safe" (0 = Pressure fault / low, 1 = Pressure OK).

Clamping Pressure Fault

Critical alarm. Alarm instantly if the clamp pressure (P xxx-3300) switch signal is low whilst the blender is rotating.

Monitoring will be "fail-safe" (0 = Pressure fault / low, 1 = Pressure OK).

Clamp Failure

The Clamping system is monitored by a watchdog timer, which is initiated when (XV xxx-3000A) is energised. If pressure switch (PS xxx-3300) remains false on expiry of this timer solenoid valve (XV xxx-3000A) is de-energised and an alarm message is indicated on the SCADA.

Unclamp Failure

The Unclamping system is monitored by a watchdog timer, which is initiated when (XV xxx-3000B) is energised. If the cage lowered switch remains false on expiry of this timer solenoid valve (XV xxx-3000B) is de-energised and an alarm message is indicated on the SCADA.

Blender Inverter Circuit Breaker Tripped

Critical alarm. Alarm instantly on opening. Blender will stop within one revolution.

Blender Motor Brake Overload

Critical alarm. Alarm instantly on opening.

Blender Inverter Drive Fault

Critical alarm. Alarm instantly on opening. Blender will stop within one revolution.

Blender Failed To Reach Pre-set Speed

Critical alarm. Alarm if the blend set speed has not been achieved after a pre-set value of seconds after request to start.

Blender Deceleration Failure

Critical alarm. Alarm if the blend creep speed has not been achieved after a pre-set value of seconds after request.

Blender Low Speed

Critical alarm. Alarm if the blender speed falls below pre-set speed for longer than the pre-set value of seconds.

Blender High Speed

Critical alarm. Alarm if the blender speed rises above pre-set speed for longer than the pre-set value of seconds.

Stop Detect Fault

Critical alarm. Alarm if the rotating cage has failed to stop in the vertical position when requested, on completion of watchdog timer.

Blend Motor Disconnect Fault

Critical alarm. Alarm if the Motor Isolation switch is off.

Post Hoist (G1951-D01)

The Post Hoist monitors the following fault conditions:

Emergency Stop Operated

If an emergency stop operated is detected, then alarm immediately.

Controls Not On Fault

If the emergency stop relay is de-energised, but the emergency stop has not been operated, then alarm.

Lift Motor Over Temperature

If the lift motor thermistor relay detects an over-temperature condition, then alarm immediately.

Lift Motor Inverter Fault

If the lift motor inverter detects a fault, then alarm immediately.

Slew Motor Over Temperature

If the slew motor thermistor relay detects an over-temperature condition, then alarm immediately.

Slew Motor Circuit Breaker Tripped

If the system detects that the circuit breaker has tripped, then alarm immediately.

Lift Motor Raised Overtravel

If the raised overtravel switch has been operated, then alarm immediately.

Lift Motor Docked Overtravel

If the docked overtravel switch has been operated whilst in the discharge slew position, then alarm immediately.

Lift Motor Disconnect Fault

Critical alarm. Alarm if the Motor Isolation switch is OFF.

Slew Motor Disconnect Fault

Critical alarm. Alarm if the Motor Isolation switch is OFF.

Lift Motor Inverter Circuit Breaker Tripped

Critical alarm. Alarm instantly on opening. Blender will stop within one revolution.

Mill Assembly (G1951-M01)

The Mill will monitor the following alarms only when the Mill is detected as plugged in.

Mill Motor Disconnect Fault

Critical alarm. Alarm if the Motor Isolation switch is OFF.

Mill Low Speed

Critical alarm. Alarm if the Mill speed falls below pre-set speed for longer than the pre-set value of seconds.

Mill High Speed

Critical alarm. Alarm if the Mill speed rises above pre-set speed for longer than the pre-set value of seconds.

2.7.3 Alarm/Fault Summary

Alarm Message (Blender)	Type
Emergency Stop Pressed	Critical
Safety Key	Critical
Main Air Pressure Low	Critical
Clamping Pressure Fault	Critical
Clamp Failure	Critical
Unclamp Failure	Critical
Blender Inverter Circuit Breaker Tripped	Critical
Blender Motor Brake Overload	Critical
Blender Inverter Drive Fault	Critical
Blender Failed To Reach Pre-set Speed	Critical
Blender Deceleration Failure	Critical
Blender Low Speed	Critical
Blender High Speed	Critical
Stop Detect Fault	Critical
Blend Motor Disconnect Fault	Critical

Alarm Message (Hoist)	Type
Emergency Stop Operated	Critical
Controls Not On	Critical
Lift Motor Over temperature	Critical
Lift Motor Inverter Fault	Critical
Slew Motor Over temperature	Critical
Slew Motor Circuit Breaker	Critical
Lift Motor Raised Overtravel	Critical
Lift Motor Docking Overtravel	Critical
Lift Motor Inverter Circuit Breaker Tripped	Critical
Lift Motor Disconnect Fault	Critical
Slew Motor Disconnect Fault	Critical

Alarm Message (Mill)	Type
Mill Motor Disconnect Fault	Critical
Mill Low Speed	Critical
Mill High Speed	Critical

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems


BLANK PAGE

Appendix 'A

Electronic Records and 21 CFR Part 11 compliance

Data Flow

The data flow within the system is as indicated in the following diagram:



Machine Control Management

The system is batch orientated control software based on the ISA S88.01 standard for automation of batch process, designed to be compliant to the FDA 21 CFR Part 11 guideline.

Process automation offers manual operation, recipe handling, automatic operation, batch reporting and alarm reporting.

The software package to visualise and control the process takes into account the specific requirements of batch processing in the pharmaceutical industry.

In the Auto mode all process data will be recorded and stored to local hard drive. The system will give messages to the operator i.e. in case of error messages (text messages) or machine faults. This ensures very easy operation and quick understanding of the machine thus leading to a positive attitude and acceptance of the operator.

Recipe handling features creation of new recipes, modification of existing unused ones, create derivatives of existing recipes as well as export and download capability of recipes.

A recipe consists of the following process steps: IBC loading & clamping, IBC rotation speed, IBC rotation time, Milling Time & speed (if required), IBC unloading & clamping. Every process step is represented by a programmable recipe step with a specific set of parameters that can be arranged to compose a recipe. A recipe may contain up to 16

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

steps, the sequence of steps is not fixed. The same step may be selected several times without restriction. This ensures maximum flexibility to create recipes according to your requirements for the broadest range of products.

Automated processing means reproducible process conditions according to recipes. The process is controlled by the control software but permits intervention through the operator. Every intervention, fault etc. will be logged. The analogue process values are recorded and will be shown graphically on the screen. The only operator process steps will be to load the IBC on the Blender, plug the mill into the Hoist (once this is done it will not be required again, unless unplugged) and unload the IBC from the blender

Complete batch documentation is generated including log files and will be stored locally.

Four Emergency Stops are included in the systems which are hard wired to the safety circuit of the equipment. When operated all machinery stops and the machine must be reset via the operator control panel. All functionality is operated via the following Fanuc Touch screen PC.

Fanuc Panel

The operator panel also includes a graphical display showing the actual status of the unit. All operator screens are in English.

In case of failure, the control system generates alarm/failure messages that are shown on the screen. Alarm/failure messages will be in English.

The PC is to be installed in a non-explosion hazard Zone 2 clean area.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Blank Page

SECTION 3

Maintenance Information

Table of Contents

3.1 Maintenance Schedules	3
3.1.1 General	3
3.1.2 Schedule of Maintenance	3
3.2 SP2000 Blender(B01).....	4
3.2.1 Scheduled Maintenance	4
3.2.2 Maintenance Procedures.....	7
3.3 PH600 Post Hoist (D01)	9
3.3.1 Safety.....	9
3.3.2 Scheduled Maintenance	9
3.3.3 Lubrication Schedule.....	11
3.3.4 Hoist Chain Adjustment & Torque Values.....	11
3.3.5 Hoist Fault Finding	11
3.4 Mill Assembly	13
3.4.1 General	13
3.4.2 Maintenance Schedules	13
3.5 Recommended Spare Parts	15

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

This page intentionally blank

SECTION 3

Maintenance Information

3.1 Maintenance Schedules

3.1.1 General

All Buck Systems machinery uses components that are 'maintenance free' wherever possible. However, the following routine maintenance should be carried out at the intervals stated as regular planned maintenance will increase machine efficiency and reduce machine 'downtime'.

All maintenance actions must be carried out by alert, qualified personnel.

3.1.2 Schedule of Maintenance

The frequency of maintenance checks and replacements depends on the amount that the Single Pedestal Blender is used. The following table shows that frequency. If usage is irregular, then take the frequency of maintenance as the shortest appropriate.

Maintenance Schedule	Frequency of use	When the maintenance is to be done
A	More than once a day	At least once during the day.
	Otherwise	On every day of operation.
B	At least twice a week	Every week.
	At least twice a month	Every month.
	Less than twice a month	At the time of use and at least once a year.
C	At least twice a week	Every month.
	At least twice a month	Every three months.
	Less than twice a month	Every six months.
D	Intensively (many times a day)	Every three months.
	Less intensively but at least twice a month	Every six months.
	Less than twice a month	Every year.
E	Intensively (many times a day)	Every six months.
	Less intensively but at least twice a month	Every year.
	Less than twice a month	Every two years.
F	Any usage	Every two years.

WARNINGS

- 1. DANGER TO LIFE AND LIMB- ROTATING MACHINERY - THE MACHINE MUST BE INSTALLED IN AN ENCLOSED AREA WITH RESTRICTED ACCESS. INTERLOCK SYSTEMS AND LOCAL OPERATING PROCEDURES MUST ENSURE THAT NO PERSONNEL ARE WITHIN THE DANGER AREA WHEN THE MACHINE IS OPERATING.**
- 2. HEAVY WEIGHTS - EQUIPMENT WEIGHING MORE THAN 20KG MUST BE LIFTED USING SUITABLE MECHANICAL LIFTING APPARATUS.**
- 3. LIFTING APPARATUS – LIFTING APPARATUS MUST ONLY BE USED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS AND LOCAL HEALTH AND SAFETY REGULATIONS. ALL LIFTING APPARATUS AND SLINGS MUST BE APPROVED.**

3.2 SP2000 Blender (B01)

3.2.1 Scheduled Maintenance

Schedule A

The following operations should be done at least once a day for frequently used equipment, and once a day for each day the equipment is used otherwise. See *Schedule of Maintenance* above.

Step	Action
1	Check machine for signs of air leaks, lubricant leaks, loose fasteners or damage.
2	Check pneumatics supply pressure is 5.5 barG
3	Exhaust cleaner B18047/004. Check the level of the liquid in the sump. Discharge the trapped liquid from the drain cock before it reaches the element.
4.	Blender Room – Trapped Key Safety System: Check for correct operation. See <i>Section 2</i> .

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by **Buck Systems**

Schedule B

This schedule should be carried out every week for busy units and at least once a year in all cases. See *Schedule of Maintenance* above.

Step	Action
1	Check the oil level in the lubricator B18047/001 on the pneumatic panel inside the blender pedestal. If the level is low, fill with oil. See <i>Maintenance Procedures</i> on page 7.
2	Check all fittings in the pneumatic system for signs of air leakage. Check all hoses on the pneumatic system for signs of cracking, chafing or leakage, especially those adjacent to moving parts. Replace any hoses or fittings that are damaged.
3	Check machine holding down fixing for security

Schedule C

This schedule should be carried out every month for busy stations, and at least once a year in all cases. See *Schedule of Maintenance* above.

Step	Action
1	Check the condition of the filter/regulator B18047/001. Change filter if it appears clogged or damaged. See <i>Supplier's Information</i> in Section 4
2	Clean and check Earth Prod and Earthing spring.
3	SKF Bearing Seal, B18038/003: Check condition, replace if necessary.
4	Main drive motor B18038/001: Carry out periodic maintenance as described in Section 4, Suppliers Information.
5	Screw jack B01-004/003: Lubricate every 30 – 50 hours
6	Control Panel Fan & Filter unit (G1951-B01-610); Check Filter, replace if clogged.
7	Control Panel Outlet Filter (G1903-B01-610) unit; Check Filter, replace if clogged.
8	Exhaust Cleaner B18047/004: Check condition of element and replace if necessary.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Schedule D

This schedule should be carried out every three to six months for busy units, and at least once a year in all cases. See *Schedule of Maintenance* above. If extremely abrasive product is being used, shorten the frequency between checks.

Step	Action
1.	Inspect the machine thoroughly:
2.	Check/lubricate cage lifting equipment. See <i>Maintenance Procedures</i> on page 7).
3.	Check for endplay in the screw jack assembly. This should not exceed 1.8 mm of longitudinal float. If the nut has more play than this, it should be replaced.
4.	Check the drive belts on the lifting gear. Replace belts if they are worn or cracked.
5.	Visually check main shaft bearings. If they appear to be leaking, apply grease. See Maintenance Procedure at Page 14, and Schedule E maintenance procedure outlined below.
6.	Check the white rubber 'air check pressure pad bungs', B01-002/003, in the top of the blender cage. Replace them if they show any signs of wear or deformation. Failure to do this might affect the ability of cage to clamp container correctly.

Schedule E

This schedule should be carried out every six to twelve months for busy units, and at least once every two years in all cases. See *Schedule of Maintenance* above.

Step	Action
1	Filter/regulator B18047/001 (pneumatic pane): Overhaul unit and replace element.
2	Oil fog lubricator B18047/001: Clean.
3	Main shaft pillow block bearings: replace grease. Refer to SKF maintenance information in Section 4, <i>Supplier's Information</i>
4	Air motor: See <i>Supplier's Information</i> in Section 4

Schedule F

This schedule should be carried out at least every two years in all cases.

Step	Action
1.	Main drive motor B18038/001: Perform routine maintenance in accordance with motor manufacturer's instructions.

Note:

The worm gear box used on the lifting equipment is packed and life sealed. It should require no routine maintenance.

3.2.2 Maintenance Procedures

The following are maintenance procedures adapted from supplier's information, but which do not appear in Section 4, *Supplier's Information*.

Cleaning Filter/Regulators

Important: The container must be completely depressurised before removal. Wash the filter element using hot water with normal household detergents. Then blow compressed air from the inside to the outside and dry before refitting. Use only cold or hot water with normal household detergents for cleaning bowl and baffle plate.

Filling Lubricator

If the oil level is low in the lubricator on the pneumatic panel, follow this procedure to refill it.

1. Turn off the air supply.
2. Unscrew the lubricator bowl.
3. Fill with oil.
4. Refit bowl and turn air supply on.
5. Ensure that the lubricator delivers 10drops/minute (air motor requirement). This can be checked during the cage clamp/unclamp sequence. Adjust if necessary.

Recommended oil:

- BP Energol RD-E80
- Castrol RD oil light
- Esso Arox EP 56
- Gulf Gulfstone Oil 20
- Mobil Almo Oil 525

Equivalent grades of other suitable oils may also be used.

6. Unscrew the collection bowl on the silencer/re-classifier and empty out any oil residue collected there.

Lubricate Cage Lifting Equipment

Part of the regular maintenance is to check and lubricate the cage lifting equipment. Follow this procedure:

1. Remove the cage top covers and the air motor cover and inspect the universal joints.
2. The universal joints are fitted with rubber gaiters that are grease packed before leaving the Buck Systems works. If the gaiters are cracked or leaking, they should be replaced and re-packed with grease.
3. Using the "Unclamp/Clamp" control, raise the cage fully up.
4. Remove the nylon plugs in the cage legs.
5. Grease nipples are facing outwards, in line with the holes, and can be greased with a gun.

Recommended greases are as follows:

- Darmex 123
- Shell Alvania EP2
- Mobil Mobilplex46
- Texaco EP 00

Main Shaft Plummer Block Bearings

The grease in these bearings should be replaced periodically. As the shaft runs at slow rotational speeds, it is unlikely that the bearings will ever run dry or overheat. However the grease can oxidise if left for long periods. Replace the grease:

1. With the cage upright and the machine in local manual mode, using the "Unclamp/Clamp" control, lower the cage so that the lifting frame rests on the floor posts.
2. Dismantle the Plummer block, clean out the old grease and inspect the bearing. (See *Supplier's Information* in Section 4.).
3. Replace the bearing if it is damaged or worn: Otherwise, re-pack with fresh grease and replace the Plummer block cover.
4. Repeat the operation for the second bearing.

Electrical Maintenance

Always turn off the main control panel disconnect before approaching the active parts of the machine or performing any operation within reach of live or moving parts. Allow only qualified personnel access to the electrical enclosure.

Note: The inverter unit retains a charge for 5-10 minutes after disconnection.

3.3 PH600 Post Hoist (D01)

3.3.1 Safety

All maintenance actions must be carried out by, alert qualified personnel capable of recognising risks and dangers associated with maintenance operations. For maintenance tasks the following should be adhered to:



Do not climb on the machine, use approved climbing/access equipment.

Isolate power supply

Hang a sign on the machine isolator to clearly show that the machine is undergoing maintenance.

WARNING:

DUST CAN FORM AN EXPLOSIVE MIXTURE WITH AIR AND BE IGNITED BY A VARIETY OF METHODS. PARTICULAR ATTENTION MUST BE PAID TO REGULAR CLEANING PROCEDURES TO PREVENT ACCUMULATIONS OF HAZARDOUS DUST INTERNALLY AND EXTERNALLY.

3.3.2 Scheduled Maintenance

Schedule A

There is no specific routine daily maintenance for this equipment.

Schedule B

The following operations are to be carried out every week for busy units in all cases:

1. For self-testing equipment, perform a self-test at least once a week, or each time the equipment is used, if less frequent.
2. Check the Hoist drive chain for lubrication. If necessary, lubricate with suitable chain lubricant as listed in the supplier's information in Section 4.
3. Check for any signs of pneumatic leaks and rectify.
4. Check operation of the all sensors and encoder.
5. Run sequence to ensure all interlocks and movements are operating correctly
6. Check the condition of the hoist cover band for any wear and replace as required.
7. Clean the inside and outside of the Hoist to remove all deposits of potentially hazardous dust. Pay particular attention to the areas around both the top and bottom stops, which may be impacted in the event of an over-run fault, and the slewing stops, which may be impacted in the event of over-aggressive slewing action.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Schedule C

The following operations are to be carried out every three to six months for busy units, and at least once a year in all cases. If extremely abrasive product is being used, shorten the frequency between checks for all components that may come into contact with product:

1. Complete Schedule B checks in addition to below
2. Empty and clean the pneumatic supply line filter bowl.
3. Check all movements are smooth in operation.
4. Check condition of welds on all load bearing points.
5. Grease carriage guides, slew ring, slew gear teeth and pinion (where applicable).
6. Inspect and tighten if necessary slewing ring fasteners.
7. Inspect and tighten if necessary floor (and ceiling if applicable) mounting bolts.
8. Carry out checks on the electrical and mechanical operation of all 'position' switches inside the hoist. If there is any indication of hesitancy or erratic operation the switch must be replaced.

Schedule D

There are no Schedule 'D' tasks for hoist.

Schedule E

The following operations are to be carried out every six to twelve months for busy units, and at least once every two years in all cases.

1. Check for loose electrical connections and re-tighten as required.
2. Clean and replace oil or grease in all relevant systems.
3. Replace PLC Battery.

CAUTION...

To prevent the loss of programs or data, the battery is to be changed only when power is applied to the PLC.

4. Carry out all maintenance as for three to six monthly inspections
5. Check electrical connections for security.
6. Check the condition of the lift chain. Re-tension if necessary. Replace chain and sprockets if there is no further adjustment available.
8. Annual insurance inspection.

Schedule F

Remove the electric brake motor and have it inspected and cleaned by a qualified service company.

3.3.3 Lubrication Schedule

Use only the type and quantity of lubricant recommended. Damage to the equipment may result if an incorrect lubricant is used.

Old lubricants should always be disposed of in accordance with local statutory regulations.

Lubrication point	Hoist Model	Lubricant	Quantity
Lift Motor	PH600	Gearbox oil CLP H1 220 (See also manufacturer's recommendations)	3.6 litre
Slew Ring Gear & Pinion	ALL	NLGI 2 Lithium soap grease. See manufacturer's recommendation	
Slewing Ring Bearing	ALL	See manufacturer's recommendation	
Lift Chain	ALL	Any dedicated spray chain lubricant	
Latch Locking Assembly	PH600	NLGI 2 Lithium soap grease. See manufacturer's recommendation	

3.3.4 Hoist Chain Adjustment & Torque Values

Feature	Hoist Model	Value
Lift Chain Tension Adjustment		
Bolt Torque - Fork/attachment to lift carriage	PH600	200 Nm
Bolt Torque – Slewing Ring Fasteners	PH600	130 Nm

3.3.5 Hoist Fault Finding

See Table below for possible start up and operational faults for the hoist. Faults are to be dealt with only by someone trained and qualified in the use and maintenance of this machine.

NOTE . . .

Un-rectified faults may cause damage, or leave the machine in an unsafe condition! If in doubt, contact Buck Systems for technical assistance.

FAULT FINDING – PH600 Post Hoist

Fault	Possible Cause		Check	
When the hoist 'raise' or 'lower' button/key is pressed the hoist does not raise or lower	1)	Hoist not in correct slew position.	i)	Check hoist is slewed all the way to the endstop and the proximity switch is made.
	2)	End stop proximity switch not working.	ii)	Check adjustment.
	3)	Mains power switched off. Circuit breaker tripped.	iii)	Check position of main isolator.
	4)	Possible motor overload.	iv)	Check cause and reset.
	5)	Control fuse blown	v)	Check cause and replace.
Hoist carriage does not stop at lift limit switches.	1)	Hoist not in correct slew position.	i)	Check hoist is slewed to the correct end position and the switch is made.
	2)	Switch not working	ii)	Check operation of switch and replace if necessary.
Hoist carriage does not stop in correct place.	1)	Lift limit switch not in correct position.	i)	Check position and adjust.
Slew lock does not release.	1)	Compressed air not switched on	i)	Check compressed air is switched on.
	2)	Compressed air not at correct pressure.	ii)	Compressed air is set to correct pressure.
	3)	Fault with push button valve.	iii)	Check operation and replace if necessary.
	4)	Mechanism sticking	iv)	Check operation, lubricate if necessary.
Valve actuator fails to open/closeQ2	1)	Compressed air not switched on	i)	Check compressed air is switched on.
	2)	Compressed air not at correct pressure.	ii)	Compressed air is set to correct pressure.
	3)	Control fuse blown	iii)	Check cause and replace

3.4 Mill Assembly

3.4.1 General

The Mill Assembly comprises a Trolley fitted with Comill U5 Mill. A hopper is installed on the mill infeed and a 2500 mm Dia. Buck Type 'C' Active on the mill discharge.

3.4.2 Maintenance Schedules

Schedule A

The following operations should be done at least once a day for frequently used equipment, and once a day for each day the equipment is used otherwise. See *Schedules of Maintenance*.

Step	Action
1	Check all fittings in the pneumatic system for signs of air leakage.
2	Check trolley frame (including wheels) for signs of damage or excess wear; take corrective action as necessary

Schedule B

There are no weekly tasks for this station.

Schedule C

This schedule should be carried out every month for busy stations, and at least once a year in all cases. See *Schedules of Maintenance*.

Step	Action
1	Check all plastic hoses for signs of cracking or chaffing.
2	Flange Bolts securing the Buck Valve Assemblies to the Mill's discharge and discharge are to be inspected and tightened if necessary.
3	6" Flexible Joint M01-001/030: Check condition, replace if necessary
4	1.5" Crystaflex Hose M01-001/042: check condition, replace if necessary
4	Seals M01-001/033,046 Check condition – replace if necessary.
5	Compression seals (part of Buck Valves M01-001/026) check condition, replace if necessary.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Schedule D

This schedule should be carried out every three to six months for busy units, and at least once a year in all cases. See *Schedules of Maintenance*. If extremely abrasive product is being used, shorten the frequency between checks.

Step	Action
1	Calibrate all critical monitors and gauges
2	Rotary actuators (part of Buck 'C' Valve M01-001/026): Refer to supplier information in Section 4 and Check alignment.
3	SMC Vacuum Generators M01-001/039: Check serviceability as directed Supplier's information (Section 4)

Schedule E

This schedule should be carried out every six to twelve months for busy units, and at least once every two years in all cases. See *Schedules of Maintenance*.

Step	Action
1	Check condition of all the pneumatic pipes, replacing where necessary.
2	Check for loose electrical connections and re-tighten as required.
3	Replace seals not replaced at Schedule 'C' Item 4.
4	Compression seal (part M01-001/026): replace.
5	Buck 'C' Valve (M01-001/026): service as directed in Supplier's Information at Section 4.
6	U5 Mill M01-001/027: service as directed in Supplier's Information at Section 4.

Schedule F

There is no schedule F maintenance required on this equipment.

3.5 Recommended Spare Parts

A listing of recommended spare parts is given in the tables on the following pages.

Part numbers are given in the format: drawing number-item number. For example, item B01-002-021 refers to the item 021 on the general assembly drawing G1959-B01-002. The circled number 021 on the drawing points to item 021. The letter following the number indicates a part related to the item: 'A' being used for the complete item and subsequent letters for its component parts.

A *full* drawing number is unique in Buck's registry and consists of the contract number (G-number), equipment letter and sequence number, and the drawing number.

NOTE:

Spare Part --- item to be held in stock to minimize any machine repair time.

Wear Part --- item that would require replacing as part of a maintenance schedule.

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Buck Systems Contract No. / Equipment No. G1951-B01
 Equipment Description: SP2000 Single Pedestal Blender x 1
 Date: 31-October-2006
 Customer: Novartis - Singapore
 Customer Reference:

Buck Systems Part No.	Description	Qty on each M/c	Wear Part (w) Spare Part (s)	Recommended Stock Quantity
	Cage Ass'y with Swinging Arms G1951- B01- 002			
002-003	Air check pressure bung 81 dia. x 40 long	2	w	4
	2 Jack Drive Ass'y G1951- B01- 004			
004-025	Universal joint ref : 940F ME32	2	s	2
004-026	Universal joint gaiter ref : B01123	2	s	2
004-033	Polychain belt 12 mm widw x 180 teeth ref : 274J0144	1	w	1
004-034	Polychain belt 12 mm wide x 193 teeth ref : 274J0179	1	w	1
004-054	LZL 15 Air motor maintenance kit	1	w	1
	SP2000 Swinging Arm Ass'y G1951- B01 - 005			
005-037	Air check pressure bung 81 dia. x 40 long	3	w	6
	Heavy Duty Rotating Coupling B02012			
B02012-007	O' Ring 60 i/d x 5 mm section ref : 0600-50	8	w	8
	SP2000 Standard Direct Drive Ass'y B18038			
B18038-009	Proximity switch ref : XS4-P30PA340D	1	s	1
B18038-010	Proximity switch ref : XS3-P12PA340D	1	s	1
B18038-011	Cable for above switches ref : XZ-CP1241L5	2	s	1
B18038-037	Proximity switch ref : XS1-N08PA349	1	s	1
	Pneumatic Ass'y (with Swinging Arms) B18047			
B18047-002	1/4" Pressure switch ref : IS3000-02	2	s	1
B18047-003	5/3 Double solenoid valve 24 v. ref : VS7-8-FJG-D-3Z-Q	1	s	1
B18047-004	Exhaust cleaner ref : AMC810-14	1	w	1
B18047-005	1/8" BSP 3/2 Solenoid valve 24 v. ref : VZ512-5MNZ-01	1	s	1
B18047-008	3/8" BSP - 8 mm Speed controller ref : AS3001F-08	1	s	1
B18047-016	3/4" BSP 2/2 Pilot valve ref : VNA301A-20A-B	1	s	1
B18047-018	4 mm 3/2 n/c Poppet valve ref : VM1000-4N-00	2	s	1
B18047-019	Compact S.A. cylinder x 10 stk.ref : CQ2B12-10T	1	s	1
B18047-021	1/8" BSP 3/2 Pilot valve ref : VTA301-01	1	s	1
B18047-042	1/8" BSP 3/2 valve with roller plunger ref : VM130-01-06	1	s	1
B18047-044	M5 5/2 Pilot valve ref : VZA3120-M5	1	s	1
B18047-046	Quick exhaust valve ref : AQ340F-06-00	1	s	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Buck Systems Contract No. / Equipment No. G1951-D01
 Equipment Description: PH 600 Post Hoist x 1
 Date: 31-October-2006
 Customer: Novartis - Singapore
 Customer Reference:

Buck Systems Part No.	Description	Qty on each M/c	Wear Part (w) Spare Part (s)	Recommended Stock Quantity
	Size 1 Slewing Bottom Lift Ass'y D01170			
D01170-035	PVC coated cover - AGR21MB - 230 wide x 4568 long	1	w	1
	Std Lift Limit Switch Ass'y D99108			
D99108-002	Limit switch ref : XCK-J10511H29 (roller lever type)	1	s	1
	Std IBC Proximity Switch Ass'y D99109			
D99109-002	Proximity switch ref : XS1-N18PA340D	1	s	1
D99109-003	Cable for above switch x 10.0 m long ref : XZ-CP1241L10	1	s	1
	Size 1 & 2 Latch Endstop c/w Limit Switch D99116			
D99116-003	Proximity switch c/w 5.0 m cable ref : NJ2-F1-E2-MKA	2	s	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Buck Systems Contract No. / Equipment No. G1951-M01
 Equipment Description: U5 Mill & Support Frame x 1
 Date: 30-October-2006
 Customer: Novartis - Singapore
 Customer Reference:

Buck Systems Part No.	Description	Qty on each M/c	Wear Part (w) Spare Part (s)	Recommended Stock Quantity
	U5 Mill & Support Frame G1951- M01- 001			
001-026	DN250 Buck 'C' Valve - Active - spares listed below :			
	DN250 Bearing Shell	2	w	8
	DN250 Catch - Brass Bearing Guide	2	w	2
	DN250 Cover Pin	2	w	2
	DN250 Disc locking pin	2	w	2
	DN250 Main body seal EPDM white	1	w	1
	DN250 Passive C valve Bush	2	w	2
	DN250 locking pin spring	2	w	2
	DN250 Bush Bracket	2	s	4
	DN250 Passive Disc	1	s	1
001-027	Quadro U5 Comill spares as listed below :			
U5-19-10171D	Spares kit comprising : chute 'o' ring - viton	1	w	1
	impeller 'o' ring - viton	1	w	1
	impeller bolt	1	w	1
001-030	6" dia. Q-connect flexible joint translucent silicone/316 s.s.	1	w	1
001-033	6" Tri-clamp seal - EPDM	4	w	4
001-036	Limit switch ref : XCS-M3902L1 (roller plunger type)	2	s	1
001-038	Lead for above switch ref : XZ-CP1241L10	2	s	1
001-040	Pressure switch ref : ZSE-01-55L-Q	2	s	1
001-041	Silencer ref : AN200-02	1	w	1
001-042	1 1/2" Crystaflex hose x 1.0 m	1	w	1
001-043	1 1/2" Dipmould ends	3	w	3
001-046	1 1/2" Tri-clamp seal - EPDM	4	w	4

SECTION 4

Supplier's Information

See Volume 2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Blank Page

SECTION 5

Simplified Parts Lists & Drawings

Table of Contents

Parts Lists.....	Page
BLENDER (G1951-B01).....	3
G1951-B01-001 SP2000 Single Pedestal Blender Assembly	3
G1951-B01-002 Cage Assembly with Swinging Arms	4
G1951-B01-003 Lifting Frame Assembly.....	4
G1951-B01-004 2-Jack Drive Assembly.....	5
G1951-B01-005 SP2000 Swinging Arm Assembly	8
B18023 Earthing Assembly	11
B18037 Thro-Wall Pedestal Base & Covers.....	12
B18038 SP2000 Standard Direct Drive Assembly	13
B18046 Leg Delay Cam Assembly	16
B18047 Pneumatic Assembly (with Swinging Arms)	17
B02012 Rotary Coupling	20
G1951-B01-600 Control Panels	20
PH600 POST HOIST (G1951-DO1).....	21
G1951-D01-001 PH600 Post Hoist	21
G1951-D01-002 Fork Assembly	22
D01131 Size 1 Powered Slew Base Assembly.....	23
D01153 Size Local Terminal Box Assembly	24
D01169 Size 1 Slewing Column Assembly.....	24
D01170 Size 1 Slewing Bottom Lift Assembly	25
D02132 Size 2 Slew Base Bottom Cable Entry Assy.....	28
D99100 STD Carriage Cable Connection.....	28
D99108 STD Lift Limit Switch Assembly	29
D99109 STD IBC Proximity Switch.....	29
D99116 Size 1 & 2 Latch Endstop c/w Limit Switch.....	30
MILL (G1951-M01)	31
G1951-M01-001 U5 Mill & Support Frame	31

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

<u>Drawings</u>	<u>Drawing #</u>
Blender (G1951-B01)	
SP2000 Single Pedestal Blender	G1951-B01-001
Rotating Cage Assembly with Swing Arms	G1951-B01-002
Lifting Frame Assembly	G1951-B01-003
2-Jack Drive Assembly	G1951-B01-004
Swinging Arm Assembly	G1951-B01-005
SP2000 Blender Earthing Assembly	1016870
SP2000 Blender Thro-Wall Pedestal Base & Covers.....	1016879
SP2000 Standard Direct Drive Assembly.....	1016880
Blender Leg Cam Assembly	1016888
Blender Rotary Coupling.....	1016595
B01 Blender / D01 Post Hoist Electrical Schematics (59 Sheets)	G1951-B01-601
B01 Blender / D01 Post Hoist, Main Panel, GA	G1951-B01-610
Operator Station, Panel Layout.....	G1951-B01-620
Cable Layout (4 Sheets)	Spreadsheet Tables
Pneumatic Circuit	G1951-B01-801
P&I Diagram	G1951-B01-901
 PH600 Post Hoist (G1951-D01)	
PH600 Post Hoist	G1951-D01-001
Loading Fork Assembly	G1951-D01-002
PH600 Powered Slew Base Assy	1019581
PH600 Slewing Column Assy Bottom Lift	1019510
Slew Base Bottom Cable Entry Assembly.....	1019464
Carriage Cable Connection	1019858
STD Lift Limit Switch Assy	1017187
STD IBC 'In Position' Switch Assy	1019875
Slew End Stop Assy	1019907
P&I Diagram	G1951-D01-901
 Mill (G1951-M01)	
U5 Mill & Support Frame.....	G1951-M01-001
Electrical Schematics (16 Sheets)	G1951-M01-601
Control Panel, GA.....	G1951-M01-610
Pneumatic Circuit	G1951-M01-801
P&I Diagram	G1951-M01-901

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

BLENDER (G1951-B01)

G1951-B01-001 SP2000 Single Pedestal Blender Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	G1951-B01-002		ROTATING CAGE RHN ASSY WITH SWINGING ARMS	1
002	G1951-B01-004		2 JACK DRIVE ASSEMBLY	1
003	B18023		EARTHING ASSEMBLY (OLD IBC)	1
004	B18037		THRO WALL PEDESTAL BASE & COVERS	1
005	B18038		STANDARD DIRECT DRIVE ASSEMBLY (SAFE ZONE)	1
006	G1951-B01-003		LIFTING FRAME RHN ASSEMBLY (OLD IBC)	1
007	B02012		ROTARY COUPLING (SEE SEPARATE BOM)	1
008	B18047		PNEUMATIC CIRCUIT WITH SWINGING ARMS	1
009	B18050		TAGGING ASSEMBLY	1
010	G1951-B01-005		SWINGING ARM ASSEMBLY	1
011	B18046		LEG DELAY CAM ASSEMBLY	1
012			MAIN CONTROL CABINET LAYOUT	
013			OPERATOR PANEL LAYOUT	
014			MACHINE JUNCTION BOX LAYOUT	

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

G1951-B01-002 Cage Assembly with Swinging Arms

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	G1951-B01-021		ROTATING CAGE RHN	1
002	B18157		BUNG PLATE :- 70 DIA x 12 LG	2
003	B18158		BUNG - 81 DIA x 40LG new drg 1016539	2
004	B04111		BEARING PAD LONG :- 30 x 19 x 100 LONG BAR	12
005			M8 x 20 LONG SLOTTED PAN HD SETSCREW	24

G1951-B01-003 Lifting Frame Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	G1951-B01-023		LIFTING FRAME -	1
002	G1951-B01-024		ANTI TIP RAIL	1
003	B04151		BEARING PAD SHORT :- 30 x 19 x 90 LONG BAR	12
004			M6 x 20 LONG SLOTTED PAN HD SETCREW	24

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

G1951-B01-004 2-Jack Drive Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B01128		MULI-3 JACK MOUNTING PLATE : - 130 x 150 x 16 THK PLATE	1
002	B01129		MULI-3 JACK MOUNTING PLATE : - 110 x 170 x 16 THK PLATE	1
003			INKOMA PRECISION SCREW JACK HSG-3-R-1100 NUT FLANGED FMS-3, VERSION A, M/c TO ACCEPT GREASE NIPPLE TWO OFF INPUT SHAFTS (STANDARD)	2
004			NOT REQUIRED	
005	B01111		JACK NUT RETAINER : - 100 DIA BAR x 40 LONG	2
006			ANTI-ROTATION PIN : - 6 DIA BAR x 39 LONG	4
007			GREASE NIPPLE 1/4" x 28 UNF STRAIGHT – KINGFISHER LONG STRAIGHT REF. HUF4/Y	2
008			M10 x 60 LONG HEX. HD BOLT	8
009			M10 PLAIN WASHER	8
010			M10 x 30 LONG SOCKET HD CAP SCREW	8
011			(M8) 10 x 20 LONG SOCKET HD SHOULDER SCREW	8
012	B01130		JACK RESTRAINER : - 65 x 206 x 16 THK PLATE	2
013	B01132		BELLEVILLE MANDREL : - 25 DIA BAR x 63 LONG	2
014	B01133		STRIKER PLATE : - 70 DIA x 3 THK PLATE	2
015	B01134		SPRING HOUSING : - 35 DIA BAR x 40 LONG	2
016	B01135		LOCKNUT : - 55 DIA BAR x 12 LONG	2
017			BELLEVILLE DISC SPRING GROUP 1B TO DIN 2093 PART REF. D22511208	64

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
018			M5 x 12 LONG BUTTON HD CAP SCREW	48
019			M6 x 20 LONG HEX. HD SETSCREW	4
020	B01141		BEARING HOUSING	1
021			DEEP GROOVE BALL BEARING 20 x 32 x 7 - 2 SEALS	2
022	B01136		STUB SHAFT : - 22 DIA BAR x 135 LONG	1
023			CIRCLIP D1400 20 DIA SHAFT	2
024	G1951-B01-025		SHAFT : - 25 DIA BAR x 955 LONG	1
025			UNIVERSAL JOINT BORE 16.0 DIA H7 BOTH ENDS FENNER REF. 940F ME32 KEYWAY TO BS SQ 2.3 DEPTH x 5.0 WIDE & M4 THD HOLES 10 MM FROM END	2
026	B01123		U.J. GAITER TO DRAWING (P.M. PLASTIC MOULDINGS)	2
027			M8 x 20 LONG HEX. HD SETSCREW	4
028			M8 PLAIN WASHER	9
029			8 MM POLYCHAIN GT SPROCKET FOR 12 mm wide belt 25 GROOVES FENNER SPROCKET 8M-25S-12 CATALOGUE CODE 050J0025	2
030			TAPER LOCK BUSH NO. 1108 BORED 28 mm FENNER CATALOGUE CODE 029B0028	2
031			8 MM POLYCHAIN GT SPROCKET FOR 12 mm wide belt 40 GROOVES FENNER SPROCKET 8M-40S-12 CATALOGUE CODE 050J0040	2
032			TAPER LOCK BUSH NO. 1610 BORED 16 MM FENNER CATALOGUE CODE 029G0016	2
033			8 MM POLYCHAIN GT BELT 12 mm Wide 180 Teeth 1440 Pitch Length FENNER CATALOGUE CODE 274J0144	1
034			8 MM POLYCHAIN GT BELT 12 mm Wide 193 Teeth 1544 Pitch Length FENNER CATALOGUE CODE 274J0179	1
035	B01142		COVER PLATE : - 132 SQUARE x 1.6 THK SHEET	2
036	B01146		AIR MOTOR ADAPTER BLOCK : - 140 x 200 LONG x 40 THK BAR	1
037	B01147		AIR MOTOR STUB SHAFT : - 40 DIA BAR x 105 LONG	1
038			M8 x 50 LONG HEX. HD BOLT	4

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
039			M8 HEX. DOME NUT	4
040			M8 x 60 LONG HEX. HD BOLT	4
041	B01148		SPECIAL WASHER : - 20 DIA BAR x 3 THK	4
042			M8 x 75 LONG HEX. HD BOLT	1
043			6 x 6 x 40 LONG SQUARE PARALLEL KEY	1
044			8 x 5 x 55 LONG RECTANGULAR PARALLEL KEY	1
045			5 x 5 x 35 LONG SQUARE PARALLEL KEY	4
046			5 x 5 x 30 LONG SQUARE PARALLEL KEY	2
047	B01138		VALVE BRACKET : - 35 x 67 x 5 THK PLATE	2
048	B01139		VALVE TAPPING PLATE : - 16 x 30 x 3 THK PLATE	2
049			M3 x 20 LONG BUTTON HD CAP SCREW	4
050	B01131		LOCATING DOWEL PIN:- 8DIA BAR x 25 LONG	4
051	G1951-B01-026		AIR MOTOR COVER : - 707 x 870 x 1.6 THK SHEET (SHAPED TO SUIT)	2
052			SPARE NUMBER	
053	G1951-B01-027		PIPE COVER : - 220 x 300 x 1.6 THK SHEET	1
054			AIR MOTOR FLG MTD 3/4" BSP PORTS 2.5 KW - ATLAS COPCO - MODEL LZL 15	1
056			EARTH WIRE - 10mm x 100 LG	1
057			EYE CRIMP FOR M8	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

G1951-B01-005 SP2000 Swinging Arm Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B18170		DOUBLE SPROCKET SWINGING ARM SHAFT	1
002	B18171		INVERTED SINGLE SPROCKET SWINGING ARM SHAFT	1
003	B18172		SINGLE SPROCKET SWINGING ARM SHAFT	1
004	B18193		SWING ARM SHAFT SPACER TUBE – 1” NB SCH. 40 PIPE (33.40 O/DIA x 3.38 mm WALL) x 101 LONG	3
005	B18173-1		BUSH HOUSING - 60 DIA BRT BAR x 30 LONG	5
006	B18173-2		BUSH HOUSING - 60 DIA BRT BAR x 30 LONG	1
007			PINION - 3/8” PITCH , 19 TOOTH SIMPLEX (TO ISO STD 606) – BORE Ø30 H8 – CROSS & MORSE CAT. No. 06B1-19.	2
008	B18174		IDLER PINION SHAFT – 45 DIA x 36 LG	2
009	B18194		RETAINING WASHER – 40 O/D x 9 I/D x 3 THK PLATE	2
010	G1951-B01-028-1		TIE ROD - 6 O/DIA x 475 LG	2
011	B18175-2		TIE ROD - 6 O/DIA x 100 LG	1
012	B18175-3		TIE ROD - 6 O/DIA x 60 LG	1
013	G1951-B01-028-2		TIE ROD - 6 O/DIA x 835 LG	1
014	G1951-B01-028-3		TIE ROD - 6 O/DIA x 335 LG	1
015	B18175-6		TIE ROD - 6 O/DIA x 190 LG	1
016	B18189-2		CONNECTING ROD TERMINAL – 10 O/DIA x 40 LG R.H. THREAD	5
017	B18189-1		CONNECTING ROD TERMINAL – 10 O/DIA x 40 LG L.H. THREAD	7
018	B18176		ACTUATOR/ CHAIN TERMINAL – M10 ALLTHREAD x 45 LG	2
019	B18177-2		ROD GUIDE – 40 x 70 x 12 THK	1
020	B18178		ROD GUIDE – 50 x 32 x 12 THK	1
021	B18195		ARM SPROCKET SHAFT SPACER - 35 O/D x 26 I/D x 4 LG	3
022	B18196		PIVOT PIN – 25 DIA BRT BAR x 60 LG (1x45° chamfer both ends)	3

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
023	B18179		CYLINDER MOUNT BLOCK - 90 x 65 x 20 THK	2
024	B18180		AIR MOTOR STOP CAM – Ø85 x 12 LG BAR	1
025	B18181		DELAY VALVE BRACKET - 40 x 96 x 3 THK PLATE	1
026	B18197		SPROCKET SHAFT SPACER - 60 O/D x 26 I/D x 5 THK	2
027	B18182		STRAIGHT SWINGING ARM	2
028	B18183		SWINGING ARM SLEEVE	3
029	B18190		OFFSET SWINGING ARM RHN	1
030	B18185		ARM LOCATING CUP	3
031	B18198		DRIVE PIN :- 6 DIA x 33 LONG BRT BAR	6
032	B18186		ARM LOCATING PAD – Ø95 BAR x 60 LG	3
033			ROLLER CHAIN - 3/8" PITCH x 200 PITCHES (MAKES SIX)	1
034			CONNECTING LINK - 3/8" PITCH (No.26)	12
035			OILITE BUSH – 30 O/DIA x 25 I/DIA x 30 LG.	8
036			OILITE BUSH – 35 O/DIA x 30 I/DIA x 20 LG.	6
037	B18158		BUNG - 81 O/DIA x 40 LG – WHITE RUBBER 70-80 SHORE	3
038	B18199		STOP PIN :- 25 DIA BRT BAR x 50 LONG	3
039			M10 x 45 LG HEX HEAD SETSCREW	6
040			M6 x 30 LONG CAP HEAD SETSCREW	4
041			M8 x 30 LONG CAP HEAD SETSCREW	4
042			M6 PLAIN NUT	5
043			M6 PLAIN NUT L.H. THREAD	7
044			M8 x 20 LG HEX HEAD SETSCREW	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
045			M8 x 55 LG HEX HEAD SETSCREW	2
046			M8 FLAT WASHER	1
047			M8 HEX PLAIN NUT	2
048			M8 x 10 LG SOCKET SETSCREW - W POINT	6
049			M10 FLAT WASHER	12
050			M10 HEX PLAIN NUT	6
051			M4 x 25 LG SOCKET BUTTON HEAD SETSCREW	2
052			M4 FLAT WASHER	4
053			M4 HEX PLAIN NUT	2
054			M4 x 12 LONG HEX HD. SETSCREW	2
055			M6 x 40 LONG HEX HD. BOLTS	2
056			M6 x 50 LONG HEX HD. BOLTS	4
057			M6 FLAT WASHERS	6
058	B18177-1		ROD GUIDE – 40 x 95 x 12 THK	1
059	B18187-1		SWINGING ARM STOP PAD PLATE : 67 x 50 x 5 THK	3
060	B18187-2		SWINGING ARM STOP PAD : 30 x 50 x 10 THK	3
061			M5 x 15 LG SOCKET BUTTON HEAD SETSCREW	6
062			M5 LARGE FLAT WASHER	6
063	B18191-1		AIR MOTOR TOP COVER RHN: 1115 x 627 x 1.6THK SHEET	1
064	B18191-2		SWING ARM CHAIN COVER RHN	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B18023 Earthing Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B16112-1		ACCESS COVER PART No B16112-1:- 65 SQ x 1.6 THK SHEET	1
002	B16112-2		ACCESS COVER PART No B16112-2:- 170 SQ x 1.6 THK SHEET	1
003	B18112		ACCESS COVER :- 130 x 121 x 1.6 THK SHEET	1
004	B18110		SHAFT EARTH MOUNTING PLATE	1
005	B02125		PLUNGER DETAIL – 25 DIA x 125 LG	1
006			SPRING – LEE SPRING LTD - PART No LC 06 3HJ-12	2
007			6mm EARTH CABLE	1
008			RING TERMINAL EARTH TO FRAME M6 RS REF 373-279	4
009			RING TERMINAL EARTH TO PLUNGER M10 RS REF 224-9702	1
010			M10 LOCK NUT	1
011			M10 DOME NUT	1
012			M12 x 30 HEX HD SETSCREW	1
013			M12 FLAT WASHER	1
014	B04122		LEG EARTH PROD 18 DIA x 90 LG	1
015	B04123		HOUSING FABRICATION	1
016			M6 x 10 HEX HD SETSCREW	4
017			M5 x 10 HEX HD SETSCREW	2
018	B04134		CONTAINER EARTH PROD 18 DIA x 60 LG	1
019	B04135		HOUSING FABRICATION	1
020			COMPRESSION SPRING – LEE SPRINGS - PART No LC063HJ-9	1
021			M5 x 10 BUTTON HD SETSCREW	11

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B18037 Thro-Wall Pedestal Base & Covers

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B18134		BASEFRAME	1
002	B18137		TOP COVER	1
003	B18138-1		END COVER - 1892 x 1485 x 1.6 THK SHEET	1
004	B18138-2		SIDE COVER	1
005	B18138-3		SIDE COVER	1
006	B18138-4		END COVER BRACKET	2
007			M6 x 15 LONG BUTTON HD CAP SCREW	16
008	B16140		PEDESTAL GLAND PLATE - 230 x 70 x 2 THK SHEET	2
009			M5 x 15 LONG BUTTON HD CAP SCREW	8
010	B18192		BOTTOM WALL COVER	1
011	B18141		CIRCULAR WALL COVER BRACKET	2
012			M8 EXTRA LARGE DIA FLAT WASHER - FORM G	8
013			M8 x 25 LONG HEX HEAD SET SCREW	8
014	B18142		CIRCULAR WALL COVER WITHOUT SEAL	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B18038 SP2000 Standard Direct Drive Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001			DANFOSS BAUER BEVEL GEARED MOTOR C/W BRAKE & SSV SHRINK DISC REF NO. BK70-15U/D13LA4-TF-S/E075B9HN POWER - 9.5 KW @ 50HZ, 18.5 rpm @ 60HZ- 22.5 rpm,11.5KW, 5100 Nm SERVICE FACTOR - 1.05; TERMINAL BOX POSITION - STANDARD II OUTPUT SHAFT BORE- 90mm DIA; MOUNTING POSITION - H3 ENCLOSURE - IP 65, INSULATION - ZONE SAFE AREA LUBRICANT - FDA APPROVED; SUPPLY - 400v 3ph 50Hz	1
002			SPHERICAL ROLLER BEARING - S.K.F. - 125 DIA PART No. 22228 CCK/W33 C/W SEAL - TSN 528A	1
003			BEARING HOUSING - S.K.F. - PART No. SNH 528 T.A.	1
004			ADAPTOR SLEEVE - S.K.F. PART No H3128	1
005			FITTING RINGS - S.K.F. - PART No 2 FRB 15/250	1
006			ALL THREAD M30 x 3.5P x 350 LONG	4
007			M30 x 3.5P HEX NUT	12
008			M30 WASHER	12
009			PROXIMITY SWITCH - TELEMECANIQUE - PART No XS4-P30PA340D	2
010			PROXIMITY SWITCH - TELEMECANIQUE - PART No. XS3-P12PA340D	1
011			CONNECTOR LEAD - TELEMECANIQUE - PART No. XZ-CP1241L5	3
012	B02122		HAZARD LABEL :- 170 x 100 WHITE/RED/WHITE GRAVOPLY	1
013	B18144		PNEUMATIC BACKPLATE 1470 x 500 x 3 THK SHEET	1
014	B18116		ROTARY COUPLING PEG :- 10 DIA BAR x 40 LONG	1
015	B18145		STOP BRACKET & SWITCH MOUNT COMPRISING :-	1
016	B18150		SWITCH BRACKET :- 80 x 215 x 5 THK PLATE	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
017			M6 x 12 LONG SOCKET BUTTON HD SET SCREW	4
018			M3 x 30 LONG SOCKET HD CAP SCREW	4
019			M6 x 12 LONG HEX. HD SETSCREW	13
020	B16110-7		FRANK'S FLAG PART No B16110-7	2
021	B02012		ROTARY COUPLING ASSEMBLY (SEE SEPARATE BILL OF MATERIALS)	1
022	B18146		COUPLING PLATE:- 135 DIA x 60 LONG BAR	1
023	B16120		30 TOOTH INDEXING WHEEL (LASER CUT PROFILE)	1
024	B08103		PROXIMITY SWITCH TARGET DISC :- 12 DIA x 2 LONG BAR	1
025			M3 x 6 LONG HEX SOCKET COUNTERSUNK HEAD SCREW	1
026	B18147		GEARBOX TORQUE BRACKET COMPRISING :-	1
027	B18148		TORQUE BRACKET COMPRISING :-	1
028	B02109		TORQUE BAR COMPRISING :-	1
029	B02110		SPRING MANDREL 50 DIA x 220L BAR , CASE HARDENED	1
030	B02111		CAP 60 DIA x 50 LONG BAR	1
031	B02112		LINCH PIN 25 DIA x 100L BRT BAR	1
032			BELLEVILLE SPRING WASHER PART No. D80415	30
033			M24 x 3 P HEX FULL NUT	4
034			SPLIT PIN 3 DIA x 35 LONG	2
035			M24 PLAIN WASHER - FORM A	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING No.	MTL No.	DESCRIPTION	QTY
036	B18149		SPEED SWITCH BRACKET	1
037			PROXIMITY SWITCH - TELEMECANIQUE - PART No. XS1-N08PA349	1
038	B18151		BEARING MOUNTING PLATE COMPRISING;-	1
039			SPHERICAL ROLLER BEARING - S.K.F. - 180 DIA PART No. 23040 CCK/W33	1
040			PLUMMER BLOCK BEARING HOUSING - S.K.F. - PART No. SN 3040	1
041			ADAPTER SLEEVE - S.K.F. - PART No. H 3040	1
042			LOCATING RING - S.K.F. - PART No. FRB 10/310	1
043			V-RING SEAL - S.K.F. - PART No. V-180 A	2
044			M20 x 70 LONG HEX HD BOLT	4
045			M20 PLAIN WASHER	8
046			M20 NYLOC NUT	4
047			M12 x 40 LONG STUD (TOTAL LENGTH = 57) FABROY REF 120.040	4
048			M12 PLAIN WASHER	4
049			M12 NYLOC NUT	4
050			M6 x 15 LONG SOCKET HEAD CAP SCREW	4
051			M12 x 50 LONG HEX HD SET SCREW	4
052			M8 HEX NUT	4

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B18046 Leg Delay Cam Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B18166		DELAY CAM :- 25 x 15 x 565 LONG	1
002	B18167		MOUNTING PLATE :- 45 x 45 x 5 THK PLATE	1
003	B18168		SPRING :- 127 x 25 x 22swg	1
004			M5 x 15 LONG SOCKET HEAD CAP SCREW	2
005			M4 x 20 LONG SOCKET HEAD CAP SCREW	2
006			M4 FLAT WASHER	2
007			M5 x 10 LONG BUTTON HD. SOCKET SCREW	2
008	B03151		COVER	1
009			M5 x 6 LONG BUTTON HD. SOCKET SCREW	4
010			M5 FLAT WASHER	6
011	B18169		30 DIA x 19 LONG BAR	2
012			M8 x 20 LONG SLOTTED PAN HEAD SETSCREW	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B18047 Pneumatic Assembly (with Swinging Arms)

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	B18047		FRL + SHUT OFF VALVE ASSEMBLY : SMC PART REF AC5000 (U K000198)	1
002			¼" PRESSURE SWITCH : SMC PART REF IS3000-02	2
003			DOUBLE SOLENOID VALVE 5/3 OPEN CENTRE 24V DC : SMC PART REF VS7-8-FJG-D-3Z-Q	1
004			1½" BSP EXHAUST CLEANER : SMC PART REF AMC810-14	1
005			1/8" BSP 3/2 SOLENOID VALVE 24V DC : SMC PART REF VZ512-5MNZ-01	1
006			PLUG WITH 3 m LEAD : SMC PART REF DXT170-123-A-30	1
007			8 mm EQUAL TEE : SMC PART REF KQT08-00	2
008			3/8" BSP – 8 mm SPEED CONTROLLER : SMC PART REF AS3001F-08	1
009			¼" BSP REGULATOR : SMC PART REF AR20-F02	1
010			REGULATOR BRACKET : SMC PART REF AR20P-270AS	1
011			1/8" BSP PRESSURE GAUGE : SMC PART REF 4K8-10	1
012			1/8" BSP – 8 mm SOCKET HEAD MALE CONNECTOR : SMC PART REF KQS08-U01	4
013			1/8" BSP – 8 mm MALE CONNECTOR : SMC PART REF KQH08-U01	2
014			¼" BSP – 8 mm SOCKET HEAD MALE CONNECTOR : SMC PART REF KQS08-U02	2
015			¼" BSP – 8 mm MALE CONNECTOR : SMC PART REF KQH08-U02	6
016			¾" BSP 2/2 PILOT VALVE : SMC PART REF VNA301A-20A-B	1
017			1/8" BSP SHUTTLE VALVE : SMC PART REF VR1210-01	1
018			4 mm 3/2 NORMALLY CLOSED POPPET VALVE : SMC PART REF VM1000-4N-00	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
019			Ø12 COMPACT CYLINDER SINGLE ACTING SPRING EXTEND 10 mm STROKE : SMC PART REF CQ2B12-10T	1
020			1/8" BSP TIME DELAY VALVE : SMC PART REF VR2110-01	1
021			1/8" BSP 3/2 PILOT VALVE : SMC PART REF VTA301-01	1
022			M5 – 6 mm SOCKET HEAD MALE CONNECTOR : SMC PART REF KQS06-M5	5
023			M5 – 4 mm MALE CONNECTOR : SMC PART REF KQH04-M5	3
024			8 mm O/D TUBE : SMC PART REF TU0805B-20 – 20 m COIL	1
025			6mm O/D TUBE : SMC PART REF TU0604B-20 – 20 m COIL	1
026			4 mm O/D TUBE : SMC PART REF TU0425B-20 – 20 m COIL	1
027			4 mm EQUAL TEE : SMC PART REF KQT04-00	2
028			8 mm – 6 mm PLUG-IN REDUCER : SMC PART REF KQR06-08	2
029			1/8" BSP – 6 mm MALE CONNECTOR : SMC PART REF KQH06-U01	12
030			1/8" BSP – 4 mm MALE CONNECTOR : SMC PART REF KQH04-U01	3
031			6 mm EQUAL TEE : SMC PART REF KQT06-00	3
032			6 mm – 4 mm PLUG-IN REDUCER : SMC PART REF KQR04-06	2
033			ISO SINGLE SUB BASE 3/4" PORTS : SMC PART REF VS7-2-A06	1
034			3/4" BSP - 3/4" O/D TUBE ST MALE ADAPTOR : NORGREN PART REF 34 0346 55	16
035			3/4" O/D TUBE SLEEVE : NORGREN PART REF 34 0278 09	16
036			3/4" O/D TUBE TUBING NUT : NORGREN PART REF 34 0279 09	16
037			3/4" O/D NATURAL NYLON TUBE – 20 m	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by **Buck Systems**

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
038			NOT REQUIRED	
039	B08102		EXHAUST CLEANER MOUNTING BRACKET	1
040	B08101		¾" BSP ADAPTER : - 38 DIA x 65 LONG BAR	2
041			50 DIAx125 STROKE. D'BLE ROD COMP'T CYL SMC REF CQ2WA50-125D-X439	1
042			1/8" BSP 3/2 VALVE WITH ROLLER PLUNGER : SMC PART REF VM130-01-06	1
043			EXHAUST RESTRICTOR WITH SILENCER : SMC PART REF ASN2-M5	2
044			M5 5/2 PILOT VALVE : SMC PART REF VZA3120-M5	1
045			1/8" BSP 3/2 VALVE WITH CROSS ROLLER PLUNGER : SMC PART REF VM130-01-07	1
046			QUICK EXHAUST VALVE : SMC PART REF AQ340F-06-00	1
047			¼" BSP – 6 mm MALE STUD ELBOW : SMC PART REF KQL06-02S	2
048			1/8" BSP – 6 mm MALE ELBOW : PART REF KQL06-U01	2
049	B18027		LAYOUT OF PNEUMATIC BACKPLATE	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

B02012 Rotary Coupling

ITEM	TAG/DRAWING No.	MTL No.	DESCRIPTION	QTY
001	B02136		BODY :- 110 DIA x 162 LONG BAR	1
002	B02137		SPOOL :- 135 DIA x 190 LONG BAR	1
003			DEEP GROOVE BALL BRG :- 85 O/D x 65 I/D x 10 THK PT No 61813-2RS1	1
004			DEEP GROOVE BALL BRG :- 90 O/D x 70 I/D x 10 THK PT No 61814-2RS1	1
005	B02139		THRUST WASHER	1
006			STD EXTERNAL CIRCLIP FOR 65mm DIA SHAFT TO DIN 471	1
007			'O' RING 60mm I/D 5mmDIA TO DIN 3771 PIMSEAL PART No 0600-50	8

G1951-B01-600 Control Panels

ITEM	TAG/DRAWING No.	MTL No.	DESCRIPTION	QTY
001			MAIN CONTROL PANEL G1951-B01/D01/M01 800x2000x500 +2000x500 (SIDE PANEL)	1
002			600x500x250	1
003			PEDESTAL MOUNTED JUNCTION BOX G1951-B01-640 (200x300x155)	1
004			HOIST MOUNTED JUNCTION BOX G1951-D01-640 (1000x600x210)	1
005			QUADRO MILL CONTROL PANEL G1951-M01 (600x600x210)	1
006			FANUC PANELPC 17" STANDARD UNITWITH SINDOWS XP PART No. IC5007TAX0030	1
007			iFIX PLUS SCADA PAK UNLIMITED RUNTIME VER 4.0 - M4 KEY PART No. 27003540001M	1
008			S17 SIEMENS SIMATIC PART No. 95113133400C	1
009			CP5613 PCI CARD WIN2K XP PRO PART No. 6GK15613AA01	1
010			SIMATIC NET PB DP5613 2005 SOFTWARE PART No. 6GK17135DB633AA0	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

PH600 POST HOIST (G1951-DO1)

G1951-D01-001 PH600 Post Hoist

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D01169		BOTTOM LIFT COLUMN ASSEMBLY	1
002	D01170		BOTTOM LIFT ASSEMBLY	1
003	G1951-D01-002		FORK ASSEMBLY	1
004	D01131		POWERED SLEW BASE ASSEMBLY	1
005	D02132		SLEW BASE BOTTOM CABLE CHAIN ASSEMBLY	1
006	D99100		STD CARRIAGE CABLE CONNECTION	1
007	D99108		STD LIFT LIMIT SWITCH ASSEMBLY	2
008	D99116		LATCH END STOP C/W LIMIT SWITCH	1
009	D01153		SIZE 1 LOCAL TERMINAL BOX ASSEMBLY - SLEWING	1
010	D99109		STD IBC PROXIMITY SWITCH ASSEMBLY	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

G1951-D01-002 Fork Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	G1951-D01-021		FORK FABRICATION :-	1
002	D01244		STD FORK MOUNTING COVER:-	1
003			BUTTON HD CAPSCREW - M5 x 10	8
004			HEX HD SET SCREW - M16 x 50 GRADE 8.8	6
005			HEX 'NYLOC' NUT - M16 GRADE 8	6
006			FLAT WASHER - M16	12
007			NOT REQUIRED	
008	D99109		IBC IN POSITION SWITCH ASSEMBLY	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D01131 Size 1 Powered Slew Base Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D02230		SIZE 1&2 POWERED SLEW BASE PLATE	1
002	D02212		SIZE 1&2 SLEWING BASE SHROUD	1
003	D02213		SIZE 1&2 SLEWING BASE GLAND PLATE	1
004	D02233		SIZE 1 & 2 ENDSTOP STRIKER PLATE	1
005			INTERNALLY GEARED SLEWING RING - REF No. 32-0411-01-ZZ00	1
006			SOCKET HEAD SET SCREW (LOW HEAD) - M12 x 60	24
007			HEX HD BOLT - M12 x 90	2
008			FLAT WASHER - M12	24
009			FULL NUT - M12	24
010			HEX HD SET SCREW - M4 x 15 LONG	1
011			FULL NUT - M4	1
012			BUTTON HD CAPSCREW - M5 x 10	12
013			FLAT WASHER - M5	4
014			FULL NUT - M5	4
015			HEX HD BOLT - M12 x 80	22
016	D02231		SIZE 2 POWERED SLEW PINION : SPUR GEAR - MODULE 5, 12TEETH - CROSS & MORSE REF:- S5012B BORE AND KEYWAY	1
017			BRAKE MOTOR & GEARBOX (HELICAL) : 0.18 KW, 255:1, 5.4 rpm, 307Nm; SERVICE FACTOR - 1.1, FLANGE DIAMETER - 160mm BRAKE HAND RELEASE POSITION - 5, OIL FILLER/BREATHER POSITION - C; TERMINAL BOX POSITION - 4 ZONE - SAFE , PROTECTION IP54 TYPE - GST06-3M VCK 063C32; SUPPLY - 380/415V 50Hz	1
018			FLAT WASHER - M8	4
019			HEX HD SET SCREW BOLT - M8 x 30	4
020	D03216		SIZE 3 POWERED SLEW PINION RETAINER:- 50 DIA. x 6 THK	1
021			PARALLEL KEY - 8W x 7H x 45 LONG, RADIUS ENDS	1
022			M10 x 35 LONG HEX. HD SETSCREW	1
023			TAG - SEE CONTRACT TAG LIST	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D01153 Size Local Terminal Box Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D01213		SIZE 2 SLEWING BASE COVER	2
002	D01237		SIZE 2 SLEWING COLUMN REAR COVER DETAIL	1
003	D01239		SIZE 2 COVER LOWER BRACKET	1
004	D01238		SIZE 2 COVER UPPER BRACKET	1
005			SEALING STRIP HEAD CUSHION RS No. 823-572	1.4 M
006			BUTTON HD. CAP SCREW - M6 x 10	6
007			HEX HD SCREW - M8 x 15	4
008			WASHER - M8	2
009			BUTTON HD. SCREW - M5 x 10	4
010			SIDE CUSHION GASKET SPONGE RUBBER 'EMKA' 1011-20	2.0M

D01169 Size 1 Slewing Column Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D01252 SHT 1&2		SIZE 1 SLEWING COLUMN FABRICATION:-	1
002	D01253		SLEWING COLUMN SHROUD - 970 x 16SWG SHEET x 5007	1
003	D01220		SIZE 1 COLUMN INSPECTION COVER	1
004			BUTTON HD SCREW- M6 x 10 LONG	4

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D01170 Size 1 Slewing Bottom Lift Assembly

ITEM	TAG/DRAWING No.	MTL No.	DESCRIPTION	QTY
001	D01201		SIZE 1 LIFT CARRIAGE FABRICATION	1
002	D01205		SIZE 1 LIFT CHAIN ANCHOR	2
003	D01209		SIZE 1 COVER BELT CLAMP PLATE	2
004	D01210		SIZE 1 COVER BELT CLAMP BAR:-	2
005	D99200		STD LIFT CARRIAGE LIMIT SWITCH STRIKER PLATE:-	1
006			ISO SIMPLEX ROLLER CHAIN - 3/4" PITCH ISO 606 No 12b-1 INNER LINKS AT CHAIN ENDS, 485 PITCHES	2
007			ISO SIMPLEX ROLLER CHAIN CONNECT LINK - CROSS & MORSE - PART REF 76 TO SUIT 3/4" PITCH 12B-1 CHAIN (spring clip type)	4
008	D 01251		DRIVE SPROCKET - DOUBLE SIMPLEX - 0.75" PITCH -18T BORE & KEYWAY; CROSS & MORSE REF:- DS12B1-18	1
009			LOCKNUT - M55X2: FAG REF KM11	1
010			LOCK WASHER - M55: FAG REF KM11	1
011	D01258		CHAIN IDLER SHAFT	1
012	D01248		GEARBOX DRIVE SHAFT	1
013			PARALLEL KEY - 16W X 10H X 35 LONG , RADIUS ENDS	1
014			PARALLEL KEY - 14W X 9 H X 64 LONG, RADIUS ENDS	2
015			BEARING UNIT - 50 DIA: INA REF:- PME50	1
017	D01263		CHAIN IDLER BRACKET	1
018			SOCKET HD CAPSCREW - M6 X 10	2
019			SPLIT (COTTER) PIN - 4 DIA X 36	2
020			HEX LOCKNUT - M20	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING G	MTL No.	DESCRIPTION	QTY
	No.			
021			HEX NUT - M20	2
022			BUTTON HD CAPSCREW - M5 X 10	16
023			HEX NUT - M6	4
024			SOCKET HD CSK SCREW - M8 X 20	4
025			FLAT WASHER - M6	4
026			HEX HD SCREW - M10X35	6
027			HEX HD SCREW - M16X30	4
028			FLAT WASHER - M10	6
029			HEX NUT - M12	4
030			FLAT WASHER - M 12	4
031	D01221		SIZE 1 COVER BELT ROLLER BRACKET:-	2
032			CONVEYOR ROLLER - INTERROLL SERIES 1100, 30 DIA ROLLER LENGTH = 230; M6 THREADED FEMALE ENDS	2
033			COMPRESSION SPRING - 11.25 OD x 1.25 WIRE x 64 LG 1.99N/mm ASSOCIATED SPRING REF D12230	4
034			HEX HD SET SCREW - M6 x 10	4
035			CONVEYOR BELTING - CHIORINO 50 FDA BELTING-AGR21MB 230mm WIDE 4568 LONG	1
036			HEX HD BOLT - M8 x 70	4
037			LOCKNUT - M8	4
038	D01211		SIZE 1 CARRIAGE END COVER	2
039	D99222		BELT ROLLER EARTHING SPRING - 15 x 65 x 0.3 THICK	2
040			RING TERMINAL EARTH M8 - RS REF 224-9689	2
041			RING TERMINAL EARTH M4 - RS REF 437-3807	2
042			6 mm EARTH CABLE - LENGTH CUT TO SUIT ON ASSEMBLY	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
043			HEX HD SET SCREW - M4 x 8 LONG	4
044			HEX NUT - M4	4
045			PLAIN WASHER - M4	4
046			EXTERNAL CIRCLIP - 50 DIA - D1400-0500	1
047	D01257		SIZE 1 & 2 IDLER SHAFT KEY PLATE	1
048	D01259		IDLER SPROCKET - SIMPLEX - 0.75" PITCH - 18T CROSS & MORSE REF:- 12B1-18	2
049	D01260		IDLER SHAFT SPACER -INNER	1
050	D01261		IDLER SHAFT SPACER-OUTER	2
051			BALL BEARING WITH 2 SEALS - 55x72x9 - SKF - 61811-2RS	4
052			COLLAR EYE BOLT - M20	2
053			HEX HD SCREW - M12x25	2
054	D99262		SIZE 1&2&3 CARRIAGE GLAND PLATE	2
055			LENZE HELICAL WORM GEARED MOTOR c/w BRAKE . POWER - 1.5 KW, RATIO 113.67:1, SPEED 12 rpm, TORQUE 936 Nm, SERVICE FACTOR - 1.5; FLANGE DIA - 250mm, POSITION - 5; SHAFT DIA - 50mm, POSITION - NIL, MOUNTING POSITION - C TERMINAL BOX POSITION - 4 BRAKE HAND RELEASE POSITION - 4 SUPPLY - 380-415v 3ph 50Hz; ENCLOSURE - IP 54, INSULATION - CLASS F; SPECIAL FEATURE - BRAKE BFK458.10 180V DC FITTED WITH HALF WAVE RECTIFIER PART B5-77681 TYPE - B1.5 13 GSS07-2M HAK 090-C32	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D02132 Size 2 Slew Base Bottom Cable Entry Assy

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D02215		SIZE 1&2 SLEW BASE ENERGY CHAIN OUTER GUIDE-	1
002	D02216		SIZE 1&2 SLEW BASE ENERGY CHAIN INNER GUIDE:-	1
003			ENERGY CHAIN: Black - MURRPLASTIK TYPE MP 18050	1.3m
004			ENERGY CHAIN MOUNTING BRACKET SET - MURRPLASTIK TYPE KA 18050	1
005			FLAT WASHER - M6 (No OFF AS REQ'D)	
006			FULL NUT - M6	7
007			BUTTON HD CAPSCREW - M6 x 15	3
008			SOCKET HD CAPSCREW - M6 x 15	3

D99100 STD Carriage Cable Connection

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001			ENERGY CHAIN - IGUS SERIES 14 No 14.4.028.0 (BLACK) x 3225 LG	1
002			ENERGY CHAIN MOUNTING BRACKETS WITH TIEWRAP PLATE SET IGUS No.114.4.12PZ	1
003			SOCKET HD CAPSCREW - M6 x 15	4
004			FLAT WASHER - M6	4

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D99108 STD Lift Limit Switch Assembly

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D99201		STD LIFT LIMIT SWITCH BRACKET:-	1
002			LIMIT SWITCH - TELEMECHANIQUE XCK-J10511H29 (ROLLER LEVER TYPE)	1
003			SOCKET HD CAPSCREW - M6 x 20	2
004			PRESSED CHANNEL SPRING NUT - M6 SCN6 (SPECIFIED PRODUCTS)	2
005			SOCKET HD CAPSCREW - M5 x 40	2
006			TAG - SEE CONTRACT TAG LIST	1

D99109 STD IBC Proximity Switch

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D99208		STD IBC IN POS'N SWITCH ACCESS COVER:-	1
002			INDUCTIVE PROXIMITY SWITCH - FLUSH MOUNTABLE, 5mm SENSING RANGE; TELEMECHANIQUE XS1-N18PA340D	1
003			PROXIMTY SWITCH CABLE - 90 DEG PLUG, 10m CABLE TELEMECHANIQUE XZ-CP1241L10	1
004			BUTTON HD SOCKET SCREW - M5 x 10 LONG	4
005			CABLE GLAND - (M10) ELKAY No 240-B	1
006			TAG - SEE CONTRACT TAG LIST	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

D99116 Size 1 & 2 Latch Endstop c/w Limit Switch

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	D99219		STD BASIC ENDSTOP: ANTI - CLOCKWISE HANDED	1
			CLOCKWISE HANDED	1
002	D99220		LATCH LIMIT SWITCH BRACKET	2
003			INDUCTIVE PROXIMITY SWITCH : 2 mm SENSING RANGE EMBEDDABLE DC 3 WIRE; PEPERRL- FUCHS COMFORT SERIES NJ2-F1-E2-5MKA (PNP) - 5m LONG CABLE	2
004			HEX HD SET SCREW - M10 x 35 LG	4
005			WASHER - M10	4
006			HEX HD SET SCREW - M3 x10 LG	4
007			WASHER - M3	8
008			HEX HD SET SCREW - M3 x 20 LG	4
009			NUT - M3	4

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

MILL (G1951-M01)

G1951-M01-001 U5 Mill & Support Frame

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
001	G1951-M01-021		MILL SUPPORT FRAME	1
002	G1951-M01-022		MILL HOPPER	1
003	G1951-M01-023		MILL HOPPER LID	1
004	G1951-M01-042		MODIFICATIONS TO MILL	1
005	G1951-M01-025		PIVOT BUSH - SHEET 15 THK x 120 DIA	1
006	G1951-M01-026		PIVOT WASHER - SHEET 6 THK x 120 DIA	1
007	G1951-M01-027		PIVOT MOUNTING - PLATE 8 THK x 130 x 310	1
008	G1951-M01-028		PIVOT RETAINING PLATE - PLATE 6 THK x 120 DIA	
009	G1951-M01-029		VALVE SUPPORT PLATE	1
010	G1951-M01-024		TERMINAL BOX DRILLING DETAILS (SEE ITEM 076)	1
011	G1944-M06-048		SPOOL PIECE - BAR 167 DIA x 30 LONG	2
012	G1951-M01-030		DOCKING SWITCH ACTUATOR	1
013	G1951-M01-031		SHROUD MOUNTING PLATE - 6 THK x 400 x 300	1
014	G1951-M01-032		VACUUM OUTLET PIPE	1
015	G1951-M01-033		VACUUM OUTLET PIPE	1
016	G1951-M01-034		DETAIL OF SHROUD TOP COVER	1
017	G1951-M01-035		DETAIL OF SHROUD BOTTOM COVER	1
018	G1951-M01-036		SAFETY SWITCH BRACKET - PLATE 3 THK x 30 x 135	2

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
019	G1951-M01-037		VACUUM OUTLET PIPE	1
020	G1951-M01-038		PIAB EJECTOR MODIFICATIONS	1
021	G1951-M01-039		U BOLT - BAR 8 DIA x 202 LONG	2
022	G1944-C01-024		DOCKING SWITCH BRACKET - 3 THK x 30 x 120 LONG	1
023	G1951-M01-040		EXTRACT PIPE COMPRISING :-	2
024	G1951-M01-041		GUIDE PIN - BAR 48 DIA x 130 LONG	2
025			SPARE	
026			250 DIA BUCK 'C' VALVE (ACTIVE HALF); CONTACT PARTS - 316L, NON CONTACT PARTS – 304; WHITE EPDM SEAL AND COMPENSATOR VIBRAFLOW VIBRATOR	1
027			QUADRO U5 COMIL TO DRG U5-00-00159	1
028			125mm DIA FIXED CASTOR - ALWAYS (LAG) REF No 17157 WHEEL MAT'L- POLYAMIDE 6, INOX, TOP PLATE-304 SS	2
029			125mm DIA SWIVEL CASTOR C/W BRAKE - ALWAYS (LAG) REF No 17107FR WHEEL MAT'L- POLYAMIDE 6, INOX, TOP PLATE-304 SS	2
030			YTRON QUADRO 6" DIA Q-CONNECT FLEXIBLE JOINT c/w internal flanges	1
031			SPARE	
032			150 DIA TRI-CLAMP	4
033			150 DIA TRI-CLAMP SEAL	4
034			SPARE	
035			SPARE	

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
036			TELEMECANIQUE LIMIT SWITCH -ROLLER PLUNGER (2N/C) XCS-M3902L1	2
037			TELEMECANIQUE PHOTO-ELECTRIC SENSOR - DIFFUSE XU5-P18PP340D	1
038			TELEMECANIQUE CONNECTOR LEAD XZ-CP1241L10	1
039			SMC VACUUM GENERATOR	1
040			SMC PRESSURE SWITCH REF ZSE1-01-55L-Q	2
041			SMC SILENCER REF AN200-02	1
042			1.5" CRYSTAFLEX HOSE	1m
043			1.5" DIPMOULDED ENDS -	3
044			HOSE CLAMP - HEYCO REF - 700.2360	6
045			1.5" TRI-CLAMP	4
046			1.5" TRI-CLAMP SEAL	4
049			KOPEX FLEXIBLE CONDUIT SIZE 32, REF EF171026 (CUT TO SUIT)	5M
050			KOPEX RHINO CONNECTOR SZE 32x1.5, REF EF942026	4
051			HEX HEAD SET SCREW M8 x 45 LONG	4
052			HEX HEAD SET SCREW M8 x 25 LONG	8
053			HEX HEAD SET SCREW M8 x 15 LONG	30
054			HEX HEAD SET SCREW M5 x 10 LONG	6
055			HEX HEAD SET SCREW M4 x 25 LONG	4
056			HEX HEAD SET SCREW M4 x 15 LONG	2
057			HEX HEAD SET SCREW M3 x 20 LONG	2
058			SOCKET HEAD CAP SCREW M6 x 50 LONG	8

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems


ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
059			HEX NUT M8	11
060			HEX NUT M4	4
061			HEX LOCKNUT M8	3
062			SMC TUBING 6mm BLACK REF TU0604B	20M
063			SMC TUBING 12mm BLACK REF TU1208B	2M
064			SMC ELBOW 1/4-6mm REF AS2201F-02-06S-X35	2
065			SMC STRAIGHT M5-6mm REF KQH06-M5-X2	1
066			SMC 6/8 STRAIGHT REDUCER REF KQR06-08	1
067			SMC 6/10 STRAIGHT REDUCER REF KQR06-10	1
068			SMC 6 mm EQUAL TEE REF KQT06-00	1
069			SMC ELBOW 3/8-12mm REF KQL12-03S-X2	1
070			SMC BULKHEAD 12mm REF KQE12-00-X2	1
071			SMC EQAL ELBOW 12mm REF KQL12-00	1
072			SMC BULKHEAD CONNECTOR 3/8-12 REF KQE12-03	1
073			ELKAY CABLE GLAND M20 REF 251	2
074			ELKAY LOCKNUT M20 REF 93	2
075			BRAIDED EARTH STRAP 12 WIDE X 150 LONG	1
076			ELECTRIX TERMINAL BOX 220 x 100 x 85 REF TEC6-S316 (SATIN FINISH)	1
077			HARTING HAN SOCKET - COMPRISING HOUSING - SIZE 24B - 09 30 024 0318 CRIMP TERMINAL - MALE- 12 CONTACTS - 09 14 012 3001 CRIMP CONTACT - MALE - 09 15 000 6104 (0.14-0.37) PNEUMATIC MODULE - MALE 09 14 003 4501 CONTACT - MALE - 09 14 000 6153 HINGED FRAME - 09 14 024 0313 DUMMY MODULE - 09 14 000 9950	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems



ITEM	TAG/DRAWING	MTL No.	DESCRIPTION	QTY
	No.			
078			HARTING HAN PLUG - COMPRISING HOOD - SIZE 24B - 09 30 024 0541 CRIMP TERMINAL - FEMALE - 12 CONTACTS - 09 14 012 3101 CRIMP CONTACT - FEMALE - 09 15 000 6204 PNEUMATIC MODULE - FEMALE 09 14 003 4501 CONTACT WITH SHUT OFF - FEMALE - 09 14 000 6258 HINGED FRAME - 09 14 024 0303 DUMMY MODULE - 09 14 000 9950	1
079			ELECTROFLEX CONNECTOR PG29 - REF EF944026	1
080			SOCKET HEAD BUTTON SCREW M5 x 10 LONG	4
081			HEX DOMENUT M5	4
082			ELKAY CABLE GLAND M10 REF 240	1
083			ELKAY LOCKNUT M10 REF 78	1

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems



Blank Page




ENLARGED SECTION THRO' BUNG HOUSING





ENLARGED SECTION THRO' BEARING PAD



Revision/Original	---	---	Drawing not complete
Details/Description/Change No.	Chk	Appd	or approved for manufacture
<small>This drawing or document is COPYRIGHTED by and in the property of GEA Process Engineering Ltd. or its wholly owned subsidiary. It is not to be copied, reproduced, or transmitted in any form or by any means, without prior written consent of GEA Process Engineering Ltd.</small>			
		ROTATING CAGE ASSY WITH SWING ARMS	
<small>THIRD ANGLE PROJECTION</small>	<small>Scale 1:5</small>	<small>Drawn: ADS 23/May/04</small>	<small>Checked: RE 23/May/04</small>
<small>Plot: Datum</small>	<small>ISO 9120</small>	<small>ISO 2768</small>	<small>RE G1951-B01-002 of 1.01</small>




ENLARGED SECTION THRO' BEARING PAD




FOR EARTHING ASSEMBLY DETAILS
SEE DRAWING No. B18023


Revision/Original	---	---	Drawing not complete	
Details/Description/Change No.	Chk	Appd	or approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and in the property of GEA Process Engineering Ltd. or its wholly owned subsidiary. It is not to be copied, reproduced, published or distributed in any form or by any means without prior written consent of GEA Process Engineering Ltd.</small>			GEA Buck Systems LIFTING FRAME ASSY	
THIRD ANGLE PROJECTION	Scale 1:5	ISO 9120	Drawn ADS	Checked ADS
Plot/Datum	20	21	22	A0



ASSEMBLE DRIVE AS DRAWN FOR RHN BLENDER




32 OFF BELLEVILLE DISC SPRINGS STACKED IN SERIES & PARALLEL AS SHOWN. SPRING STACK FREE HEIGHT = 36 MM. SPRING HOUSING TO BE SCREWED INTO JACK RETAINING PLATE 4.15 TURNS WHICH ON A 1" BSP THREAD EQUATES TO A LINEAR MOVEMENT OF 9.6 MM WHICH GIVES THE SPRING STACK A PRE-LOADED HEIGHT OF 26.4 MM.




ENLARGED SECTION THRO' BELLEVILLE DISC SPRING STACK
SCALE 1:1

NOTE:
ASSEMBLE DRIVE AS DRAWN OR OPPOSITE HAND
REFER TO GENERAL ARRANGEMENT DRAWING FOR HANDING

Revision	Original	Chk	Appd	Drawing not complete
Details	Description/Change No.	---	---	or approved for manufacture
<small>This drawing or document is COPYRIGHTED by and in the property of GEA Process Engineering Ltd. or its wholly owned subsidiary or agent. It is not to be copied, reproduced, altered or used in any way without the written consent of GEA Process Engineering Ltd.</small>				GEA Systems Buck 2 JACK DRIVE ASSY
THIRD ANGLE PROJECTION	Scale 1:2.5	ISO 9226	ISO 2768	Date: 23/May/04 Drawn: ADS Checked: ADS Approved: RE Drawing No: G1951-B01-004 Rev: 1 of 1 CD-85-000-01-01



01	IFS UPDATE	RXH	30/May/06
Rev No.	Description of Revision	Revised By	Date
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering (MPS) Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering (MPS) Ltd.</small>			
<small>TOLERANCES UNLESS OTHERWISE STATED: DIMENSIONS IN MILLIMETRES FRACTIONS DECIMALS 1/16 0.0625 1.588 1/8 0.125 3.175 3/16 0.1875 4.763 1/4 0.25 6.35 3/8 0.375 9.525 1/2 0.5 12.7 3/4 0.75 19.05 1 1.0 25.4 1 1/4 1.25 31.75 1 1/2 1.5 38.1 2 2.0 50.8 2 1/2 2.5 63.5 3 3.0 76.2 4 4.0 101.6 5 5.0 127.0 6 6.0 152.4 8 8.0 203.2 10 10.0 254.0 12 12.0 304.8 15 15.0 381.0 20 20.0 508.0 25 25.0 635.0 30 30.0 762.0 40 40.0 1016.0 50 50.0 1270.0 60 60.0 1524.0 80 80.0 2032.0 100 100.0 2540.0 125 125.0 3175.0 150 150.0 3810.0 200 200.0 5080.0 250 250.0 6350.0 300 300.0 7620.0 400 400.0 10160.0 500 500.0 12700.0 600 600.0 15240.0 800 800.0 20320.0 1000 1000.0 25400.0</small>		SP2000 BLENDER EARTHING ASSEMBLY OLD IBC	
THIRD ANGLE PROJECTION	Scale 1:2.5	Drawn RXH	Date 30/05/06
		Drawing No. 1016870	SM 1 of 1
<small>CAD-DWG-198079-01DWG</small>			




Rev No	IFS UPDATE	Description of Revision	Rev No	8/Jan/06
02	001	001	001	001

This drawing is deemed to be the property of GEA Process Engineering (Pty) Ltd. and is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without the prior written consent of GEA Process Engineering (Pty) Ltd.

GEA Buck
 THRO WALL PEDESTAL
 BASE & COVERS WITHOUT SEAL

Scale: 1:2.5
 Date: 08/01/06
 Drawing No: 1016879




SECTION 'C-C'
SCALE 1:5

NOTE A : ASSEMBLE 'BELLEVILLE' SPRING WASHERS
'BACK-TO-BACK' AS SHOWN, 15 PER SIDE

NOTE B : GREASE ON ASSEMBLY


NOTE C : ADJUST DIMENSION 'A' TO ACHIEVE REQUIRED
LOAD RESISTANCE BETWEEN :
193mm = 1700 Kg &
173mm = 3400 Kg



VIEW ON ARROW 'B'


COUPLING OPTIONS (021)
OPTION 1 - STANDARD
COUPLING
OPTION 2 - NIR COUPLING

SCALE 1:2.5




NOTE!
CIRCULAR WALL COVER
DRG No. 1016910 OR 1016911
TO BE ASSEMBLED ONTO
THE SHAFT BEFORE BEARINGS
WHEN THRO WALL COVERS USED.


NOTE!
BORE OF GEARBOX & SHAFT
SURFACE TO BE COMPLETELY
FREE OF GREASE BEFORE
ASSEMBLY




SECTION 'A-A'



03	IFS UPDATE	ROOM	17/Jan/07
Rev No.	Description of Revision	Revised By	Date
<small>This drawing is deemed to be COPYRIGHTED by and in the property of GEA Process Engineering (SPL) Ltd. All rights reserved. It is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without the prior written consent of GEA Process Engineering (SPL) Ltd.</small>			
SP2000 BLENDER STANDARD DIRECT DRIVE ASSY		Drawn Date 23/05/06	Drawing No. 1016880
THIRD ANGLE PROJECTION		Scale 1:7.5	Drawn Date 23/05/06



02	ITEM 013 ADDED	RXH	21/Aug/07
Rev No.	Description of Revision	Revised By	Date
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering (NPS) Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering (NPS) Ltd.		GEA Buck Systems BLENDER LEG DELAY CAM ASSEMBLY	
TOLERANCES UNLESS OTHERWISE STATED MACHINING: 0 = ±0.30, 0.0 = ±0.10, ANG'DPTS = ±0.50° FABRICATION: 0 TO 500 = ±1.0, 500 TO 254 = ±2.0, 254 TO 254 = ±3.0 ALL OTHER GEOMETRY TO COMPLY TO THE TOLERANCE STANDARDS SPECIFIED BELOW ISO 13920 -BF ISO 2768 -mK		Drawn: RXH Date: 24/05/06 Drawing No.: 1016888	Sht 1 of 1
THIRD ANGLE PROJECTION		Scale: 1:2	






ASSEMBLY INSTRUCTIONS
 CHECK INSIDE BORES OF BODY TO ENSURE ALL BURRS HAVE BEEN REMOVED
 FIT BEARINGS TO BODY ITEM 001, USE LOCTITE 601 BEARING FIT IF REQ'D
 ENSURE BEARINGS ARE FULLY SEATED, GREASE INSIDE BORE USING SOFT
 GENERAL PURPOSE GREASE, ENSURE GOOD EVEN COVERAGE.
 CHECK SPOOL ITEM 002 TO ENSURE ALL BURRS AND SHARP EDGES ARE REMOVED.
 LIGHTLY GREASE EACH 'O' RING AND FIT IN GROOVES AS SHOWN ABOVE.
 SLIDE BODY OVER SPOOL, TAKE CARE TO AVOID DAMAGE TO 'O' RINGS FROM EDGES
 OF AIRWAY HOLES IN BORE. PRESS BEARINGS INTO PLACE, FIT THRUST
 WASHER AND CIRCLIP, CHECK THAT ASSEMBLY ROTATES SMOOTHLY
PROCEDURE TO TEST FOR LEAKS
 EACH AIRWAY MUST BE TESTED SEPARATELY, FIT A BLANKING PLUG TO SHAFT SIDE
 OF COUPLING, CONNECT AN AIR LINE WITH AN ON/OFF VALVE AND A PRESSURE
 GAUGE TO THE MATCHING BODY PORT, PRESSURISE TO 5.5 BAR, CHECK FOR LEAKS
 AROUND FITTINGS WITH SOAPY WATER, RECTIFY IF LEAKING, SWITCH OFF AIR SUPPLY
 SPOOL SHOULD NOW BE ROTATED INSIDE THE BODY AT APPROXIMATELY 20 R.P.M.
 ENSURE PRESSURE WITHIN COUPLING IS MAINTAINED FOR 1 HOUR, BEFORE PROCEEDING
 TO NEXT AIRWAY, WHEN ALL CHECKS ARE COMPLETED ASSEMBLY CAN BE FITTED TO MACHINE

02	IFS UPDATE	RXH	24/May/06
Rev No.	Description of Revision	Revised By	Date
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering (MPS) Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering (MPS) Ltd.</small>			
<small>TOLERANCES UNLESS OTHERWISE STATED MACHINING: F = ±0.05, 6 TO 250 = ±0.05, 0.0 = ±0.05 FABRICATION: 50 TO 250 = ±0.05, 25 TO 50 = ±0.05 ANGLE DIMS = ±0.5° ALL OTHER GEOMETRY TO COMPLY TO THE TOLERANCE STANDARDS SPECIFIED BELOW</small>		BLENDER ROTARY COUPLING ASSY	
THIRD ANGLE PROJECTION	Scale 1:1	Drawn RXH	Date 24/05/06
		Drawing No. 1016595	Shr 1 of 1
<small>CAD-BSL-W16595-02.DWG</small>			




	1	2	3	4	5	6	7	8	
A									A
B	<p><u>TITLE:—</u></p> <p>B01 BLENDER/D01 POST HOIST</p> <p><u>DRAWING No.</u></p> <p>G1951—B01—601</p>								B
C									C
D									D
E									E
F									F

PCP DRG. No. C4341

Revision	AS TESTED		Drawing not complete or											
Details	Description / Change No		Chk	Appd	approved for manufacture									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST TITLE SHEET									
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	1	Rev	
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	16/10/2006	18/10/2006		G1951—B01—601	Next Sht	2	2
Plot—Datum														




PLA1 Date 03/01/2007 Report of drawings C4341-B01 Page 1
 B01 BLENDER/D01 POST HOIST
 Without filter

Drawing	Description	Creation	Modification
1	TITLE SHEET	04/10/2006	18/10/2006
2	INDEX SHEET 1	04/10/2006	08/11/2006
3	INDEX SHEET 2	04/10/2006	08/11/2006
20	COMPONENT KEY AND IDENTIFICATION	04/10/2006	16/10/2006
21	CABLE SPECIFICATION FOR SCHEMATIC DIAGRAMS	23/03/2006	16/10/2006
22	COMPONENT SYMBOLS FOR SCHEMATIC DIAGRAMS	04/10/2006	16/10/2006
25	PANEL REFERENCES FOR SCHEMATIC DIAGRAMS	04/10/2006	16/10/2006
30	POWER CIRCUIT - 400V DISTRIBUTION MAIN PANEL	04/10/2006	03/01/2007
31	POWER CIRCUIT - 400V DISTRIBUTION MAIN PANEL	04/10/2006	03/01/2007
33	POWER CIRCUIT - 230V DISTRIBUTION MAIN PANEL	04/10/2006	03/01/2007
34	POWER CIRCUIT - 230V DISTRIBUTION MAIN PANEL	04/10/2006	03/01/2007
35	SPARE SHEET	04/10/2006	16/10/2006
38	POWER CIRCUIT-SLEW MOTOR STARTER MAIN PANEL	04/10/2006	07/11/2006
39	POWER CIRCUIT-SLEW MOTOR MAIN PANEL	04/10/2006	07/11/2006
48	POWER CIRCUIT-LIFT VARIABLE SPEED DRIVE M. PANEL	04/10/2006	03/01/2007
49	POWER CIRCUIT-HOIST MOTOR MAIN PANEL	04/10/2006	07/11/2006
50	POWER CIRCUIT-MILL MOTOR MAIN PANEL	04/10/2006	03/01/2007
51	POWER CIRCUIT-HOIST BLENDER SPEED DRIVE M. PANEL	04/10/2006	07/11/2006
52	POWER CIRCUIT-ROTATE MOTOR MAIN PANEL	04/10/2006	03/01/2007
53	POWER CIRCUIT-MILL VARIABLE SPEED DRIVE	04/10/2006	03/01/2007
54	POWER CIRCUIT-MILL MOTOR MAIN PANEL	04/10/2006	03/01/2007
80	SPARE SHEET	04/10/2006	07/11/2006
90	EMERGENCY STOP RELAY	04/10/2006	03/01/2007
91	EMERGENCY STOP-MOTOR AVAILABLE	04/10/2006	03/01/2007
92	EMERGENCY STOPS	04/10/2006	07/11/2006
95	CONTROL CIRCUIT - PLC RACK LAYOUT	04/10/2006	07/11/2006
98	CONTROL CIRCUIT - DIG I/P 0-7 RACK 1 SLOT 3	04/10/2006	23/11/2006
99	CONTROL CIRCUIT - DIG I/P 0-7 RACK 1 SLOT 3	04/10/2006	03/01/2007
100	CONTROL CIRCUIT - DIG I/P 8-15 RACK 1 SLOT 3	04/10/2006	08/11/2006
101	CONTROL CIRCUIT - DIG O/P 0-7 RACK 1 SLOT 3	04/10/2006	08/11/2006
102	CONTROL CIRCUIT - DIG O/P 8-15 RACK 1 SLOT 3	04/10/2006	03/01/2007
103	CONTROL CIRCUIT - DIG I/P 0-7 RACK 1 SLOT 4	04/10/2006	08/11/2006
104	CONTROL CIRCUIT - DIG I/P 8-15 RACK 1 SLOT 4	04/10/2006	03/01/2007
105	CONTROL CIRCUIT - DIG I/P 16-23 RACK 1 SLOT 4	04/10/2006	03/01/2007
106	CONTROL CIRCUIT - DIG I/P 24-32 RACK 1 SLOT 4	04/10/2006	16/10/2006
107	CONTROL CIRCUIT - DIG O/P 0-7 RACK 1 SLOT 5	04/10/2006	16/10/2006
108	CONTROL CIRCUIT - DIG O/P 8-15 RACK 1 SLOT 5	04/10/2006	03/01/2007
109	CONTROL CIRCUIT - DIG O/P 16-23 RACK 1 SLOT 5	04/10/2006	03/01/2007

Revision	MODIFIED TO COMMENTS				Drawing not complete or										
Details	Description / Change No		Chk	Appd	approved for manufacture										
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST INDEX SHEET 1										
THIRD ANGLE		Scale			Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	2	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	08/11/2006		08/11/2006		G1951-B01-601	Next Sht	3	4
Plot-Datum															

PLA1		Date 03/01/2007 Report of drawingsC4341-B01 Page			2	
Without filter						
Drawing	Description	Creation	Modification			
110	CONTROL CIRCUIT - DIG O/P 24-32 RACK 1 SLOT 5	04/10/2006	16/10/2006			
111	SPARE SHEET	04/10/2006	08/11/2006			
120	CONTROL CIRCUIT - ENCODER RACK 1 SLOT 6	04/10/2006	16/10/2006			
121	Terminal strip drawing Number 1	03/01/2007	03/01/2007			
122	Terminal strip drawing X3.1 Number 1	03/01/2007	03/01/2007			
123	Terminal strip drawing X3.2 Number 1	03/01/2007	03/01/2007			
124	Terminal strip drawing D3.1 Number 1	03/01/2007	03/01/2007			
125	Terminal strip drawing X3.1 Number 1	03/01/2007	03/01/2007			
126	Terminal strip drawing Number 1	03/01/2007	03/01/2007			
127	Terminal strip drawing MJB Number 1	03/01/2007	03/01/2007			
128	Terminal strip drawing X1.1 Number 1	03/01/2007	03/01/2007			
129	Terminal strip drawing X3.1 Number 1	03/01/2007	03/01/2007			
130	Terminal strip drawing X3.1 Number 2	03/01/2007	03/01/2007			
131	Terminal strip drawing X3.1 Number 3	03/01/2007	03/01/2007			
132	Terminal strip drawing X3.1 Number 4	03/01/2007	03/01/2007			
133	Terminal strip drawing X3.2 Number 1	03/01/2007	03/01/2007			
134	Terminal strip drawing X3.3 Number 1	03/01/2007	03/01/2007			
135	Terminal strip drawing X3.4 Number 1	03/01/2007	03/01/2007			
136	Terminal strip drawing X3.5 Number 1	03/01/2007	03/01/2007			
137	Terminal strip drawing X3.6 Number 1	03/01/2007	03/01/2007			
138	Terminal strip drawing X5.1 Number 1	03/01/2007	03/01/2007			


PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS				Drawing not complete or								
Details	Description / Change No		Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST INDEX SHEET 2								
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	3	Rev
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	PM	08/11/2006		08/11/2006		G1951-B01-601	Next Sht	20	3
Plot-Datum													


COMPONENT KEY

- A - VARIABLE SPEED DRIVE/ASSEMBLY/PC. BOARD
- B - RESOLVER/ENCODER
- C - CAPACITOR
- D - DIODE
- E - CABINET ILLUMINATION
- F - FUSE/FUSE SWITCH/OVERLOAD
- G - POWER SUPPLY UNIT/GENERATOR
- H - PILOT LAMP
- K - CONTACTOR/RELAY/TIMER
- L - CHOKE/REACTOR
- M - MOTOR/FAN VENTILATOR
- P - METER/HMI
- Q - CIRCUIT BREAKER/ISOLATOR
- R - RESISTOR/POTENTIOMETER
- S - SWITCH/PUSHBUTTON/SENSOR
- T - TRANSFORMER
- X - TERMINAL/Socket
- Y - SOLENOID VALVE
- Z - RFI FILTER

COMPONENT IDENT. KEY



CABLE No. KEY



Revision	AS TESTED				Drawing not complete or										
Details	Description / Change No		Chk	Appd	approved for manufacture										
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST COMPONENT KEY AND IDENTIFICATION										
THIRD ANGLE		Scale			Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	20	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	16/10/2006		16/10/2006		G1951-B01-601	Next Sht	21	2
Plot-Datum															

CABLE SPECIFICATION

WIRE COLOUR ABBREVIATIONS IN CIRCUIT DIAGRAMS

WIRING SPECIFICATION

WIRE COLOURS

PHASE R OF 3 PHASE CIRCUIT.....RED
 PHASE Y OF 3 PHASE CIRCUIT.....YELLOW
 PHASE B OF 3 PHASE CIRCUIT.....BLUE
 PROTECTIVE EARTH.....MARKED GREEN/YELLOW
 PHASE OF A.C. SINGLE PHASE CIRCUIT.....RED
 NEUTRAL OF A.C. SINGLE PHASE OR 3 PHASE CIRCUIT.....BLACK
 POSITIVE OF A DC CIRCUIT (+24V).....BROWN
 NEGATIVE OF A DC CIRCUIT (0V).....GREY
 NON IS SIGNALS.....ORANGE

BUSBAR COLOURS

POWER.....MARKED WITH PHASE COLOURS RD/YE/BU
 PROTECTIVE EARTH.....MARKED GREEN/YELLOW
 NEUTRAL.....ALL NEUTRAL'S SHOULD BE MARKED BLACK




MINIMUM WIRE SIZE

CONTROL WIRING.....1.5mm²
 SIGNAL WIRING.....0.75mm²

IEC 757	ENGLISH	DEUTSCH	FRANCAIS	ITALIANO	ESPANOL
GN	GREEN	GRUN	VERT	VERDE	VERDE
RD	RED	ROT	ROUGE	ROSSO	ROJO
YE	YELLOW	GELB	JAUNE	GIALLO	AMARILLO
BK	BLACK	SCHWARZ	NOIR	NERO	NEGRO
BU	BLUE	BLAU	BLEU	BLU	AZUL
BN	BROWN	BRAUN	BRUN	MARRONE	MARRON
OG	ORANGE	ORANGE	ORANGE	ARANCIONE	NARANJA
VT	VIOLET	VIOLETT	VIOLET	VIOLA	VIOLETA
GY	GREY	GRAU	GRIS	GRIGIO	GRIS
WH	WHITE	WEISS	BLANC	BLANCO	BLANCO
GN/YE	GREEN/ YELLOW	GRUN/ GELB	VERT/ JAUNE	VERDE/ GIALLO	VERDE/ AMARILLO
PK	PINK	ROSA			
CL	CLEAR	KLAR			

SPECIAL MANUFACTURING INSTRUCTIONS

ALL CABLE TO BE LOW SMOKE ZERO HALOGEN TYPE

Revision	AS TESTED		Drawing not complete or			
Details	Description / Change No		Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST CABLE SPECIFICATION FOR SCHEMATIC DIAGRAMS	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified
PROJECTION			ISO 13920 - BF ISO 2768 - mK	PM	16/10/2006	16/10/2006
Plot-Datum			Status	Drawing No	Sht No	21
				G1951-B01-601	Next Sht	22
					Rev	2

	1	2	3	4	5	6	7	8				
A		FIELD TERMINAL		3 POLE ISOLATOR		3 WIRE PROXIMITY SWITCH		FUSE		CLOSED SOLENOID VALVE		AMMETER
B		FUSED TERMINAL		CLOSED PUSHBUTTON		CLOSED PROXIMITY SWITCH		THERMAL OVERLOAD		OPEN SOLENOID VALVE		VOLTMETER
C		RELAY		OPEN PUSHBUTTON		OPEN PROXIMITY SWITCH		3 POLE THERMAL OVERLOAD		ELECTROMAGNETIC BRAKE		TRANSFORMER
D		DELAY ON OPERATION RELAY		E-STOP DETENT PUSHBUTTON		CLOSED PRESSURE SWITCH		3 POLE THERMAL/MAGNETIC CIRCUIT BREAKER		ELECTROMAGNETIC CLUTCH		RESISTOR
E		DELAY ON RELEASE RELAY		E-STOP DETENT PUSHBUTTON KEY RELEASE		OPEN PRESSURE SWITCH		CLOSED CONTACT		SINGLE PHASE VENTILATOR FAN		CAPACITOR
F		LAMP		CLOSED LIMIT SWITCH		CLOSED TEMPERATURE SWITCH		OPEN CONTACT		3 PHASE MOTOR		POWER SUPPLY
		TRANSFORMER LAMP		OPEN LIMIT SWITCH		OPEN TEMPERATURE SWITCH		CHANGE OVER CONTACT		SINGLE PHASE MOTOR		REVERSING CONTACTOR

PCP DRG. No. C4341

Revision	AS TESTED	Drawing not complete or	
Details	Description / Change No	Chk	Appd
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>		B01 BLENDER/D01 POST HOIST COMPONENT SYMBOLS FOR SCHEMATIC DIAGRAMS	
THIRD ANGLE		Scale	Tolerances unless otherwise stated
PROJECTION		ISO 13920 -BF	ISO 2768 -mK
Plot-Datum		Drawn	Date
		PM	16/10/2006
		Modified	Date
			16/10/2006
		Status	Drawing No
			G1951-B01-601
		Sht No	22
		Next Sht	25
		Rev	2

1 2 3 4 5 6 7 8

A

A

B

B

C

C

D

D

E




E

F


F

PANEL	REF	LOCATION	POWER TML	CONTROL TML	INTER CON SKT	DEVICE SKT
MAIN PANEL	B01	+610	X1.1	X3.1	N/A	N/A
OPERATOR PANEL	B01	+640	N/A	X3.2	N/A	N/A
PEDESTAL MOUNTED J/BOX	B01	+641	N/A	X3.4	N/A	N/A
HOIST MOUNTED J/BOX	D01	+640	N/A	X3.3	N/A	N/A
MILLING PLC PANEL	M01	+610	X1.2	X3.5	N/A	N/A
MACHINE MOUNTED E-STOP	B01		N/A	X3.6	N/A	N/A
AUDIO/VISUAL ALARM	B01	+610	N/A	X3.7	N/A	N/A

PCP DRG. No. C4341

Revision	AS TESTED		Drawing not complete or									
Details	Description / Change No		Chk	Appd	approved for manufacture							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST PANEL REFERENCES FOR SCHEMATIC DIAGRAMS							
THIRD ANGLE		Scale			Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	16/10/2006		16/10/2006		G1951-B01-601	Next Sht	30	2
Plot-Datum												


1 2 3 4 5 6 7 8



INCOMING SUPPLY
400V
3PH + EARTH
50HZ


PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS		Drawing not complete or approved for manufacture			
Details	Description / Change No		Chk	Appd		
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST POWER CIRCUIT 400V DISTRIBUTION	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	03/01/2007	03/01/2007
Plot-Datum			Status	Drawing No	Sht No	Rev
				G1951-B01-601	30	4
					Next Sht	31




PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS		Drawing not complete or approved for manufacture			
Details	Description / Change No		Chk	Appd		
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST POWER CIRCUIT 400V DISTRIBUTION	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006	07/11/2006
Plot-Datum			Status	Drawing No	Sht No	Rev
				G1951-B01-601	31	3
					Next Sht	33



PCP DRG. No. C4341

Revision	AS TESTED	Drawing not complete or			
Details	Description / Change No	Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT 230V DISTRIBUTION	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	16/10/2006
Plot-Datum				Modified	Date
					16/10/2006
				Status	Drawing No
					G1951-B01-601
				Sht No	33
				Rev	2
				Next Sht	34






PCP DRG. No. C4341

Revision	AS TESTED	Drawing not complete or			
Details	Description / Change No	Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT 230V DISTRIBUTION	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	16/10/2006
Plot-Datum				Modified	Date
					16/10/2006
				Status	Drawing No
					G1951-B01-601
				Sht No	34
				Rev	2
				Next Sht	35

THIS PAGE INTENTIONALLY LEFT BLANK


PCP DRG. No. C4341

Revision	REVISED TO COMMENTS				Drawing not complete or								
Details	Description / Change No		Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST CONTROL CIRCUIT SPARE SHEET								
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	35	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	07/11/2006	16/10/2006	G1951-B01-601	Next Sht	38	3
Plot-Datum													




PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS			Drawing not complete or											
Details	Description / Change No			Chk	Appd	approved for manufacture									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						B01 BLENDER/D01 POST HOIST POWER CIRCUIT SLEW MOTOR STARTER									
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	38	Rev	
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	07/11/2006		07/11/2006		G1951-B01-601	Next Sht	39	3
Plot-Datum															




PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS				Drawing not complete or									
Details	Description / Change No		Chk	Appd	approved for manufacture									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST POWER CIRCUIT SLEW MOTOR									
THIRD ANGLE		Scale			Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	39
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	07/11/2006	07/11/2006		G1951-B01-601	Next Sht	48	3
Plot-Datum														



PCP DRG. No. C4341


Revision	MODIFIED TO COMMENTS			Drawing not complete or								
Details	Description / Change No	Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT HOIST MOTOR								
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	49	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006		07/11/2006		G1951-B01-601	Next Sht	50	3
Plot-Datum												



ARRANGEMENT DRAWING
SHOWING PLUG & SOCKETS


PCP DRG. No. C4341

Revision	REVISED TO COMMENTS			Drawing not complete or								
Details	Description / Change No	Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST PLUG AND SOCKET ARRANGEMENT								
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	50	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	03/01/2007		03/01/2007		G1951-B01-601	Next Sht	51	4
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS	Drawing not complete or approved for manufacture			
Details	Description / Change No	Chk	Appd		
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT ROTATE VARIABLE SPEED DRIVE	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006
Plot-Datum				Modified	Date
					07/11/2006
				Status	Drawing No
					G1951-B01-601
				Sht No	51
				Next Sht	52
				Rev	3




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS	Drawing not complete or			
Details	Description / Change No	Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT ROTATE MOTOR	
THIRD ANGLE				Scale	Tolerances unless otherwise stated
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006
Plot-Datum				Modified	Date
				Status	Drawing No
					Sht No 52
					Rev 3
					Next Sht 53
					G1951-B01-601




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS	Chk	Appd	Drawing not complete or approved for manufacture								
Details	Description / Change No											
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST POWER CIRCUIT MILL MOTOR VARIABLE SPEED DRIVE								
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	53	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006		07/11/2006		G1951-B01-601	Next Sht	54	3
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or										
Details	Description / Change No		Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST POWER CIRCUIT MILL MOTOR								
THIRD ANGLE		Scale			Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	54
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006		07/11/2006			G1951-B01-601	Next Sht	80	4
Plot-Datum													




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS			Drawing not complete or									
Details	Description / Change No			Chk	Appd	approved for manufacture							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						B01 BLENDER/D01 POST HOIST SPARE SHEET							
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	07/11/2006		07/11/2006	G1951-B01-601	Next Sht 90	3
Plot-Datum													




PCP DRG. No. C4341

Revision	MODIFIED TO COMMENTS	PM	Drawing not complete or									
Details	Description / Change No	Chk	Appd	approved for manufacture								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST SCHEMATIC WIRING DIAGRAM FOR EMERGENCY STOP RELAY								
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	90	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	03/01/2007	PM	03/01/2007		G1951-B01-601	Next Sht	91	5
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or			
Details	Description / Change No		Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST EMERGENCY STOP MOTOR AVAILABLE CONTACTORS	
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	PM	07/11/2006
Plot-Datum					Modified	Date
						07/11/2006
					Status	Drawing No
						G1951-B01-601
					Sht No	91
					Rev	3
					Next Sht	92



PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or			
Details	Description / Change No		Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST EMERGENCY STOP MOTOR AVAILABLE CONTACTORS	
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	PM	07/11/2006
Plot-Datum					Modified	Date
					Status	Drawing No
						Sht No 91
						Rev 3
						Next Sht 92
						G1951-B01-601





PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or approved for manufacture			
Details	Description / Change No		Chk	Appd		
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST EMERGENCY STOPS	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006	07/11/2006
Plot-Datum			Status	Drawing No	Sht No	Rev
				G1951-B01-601	92	3
					Next Sht	95

Revision		REVISD TO COMMENTS	
Details	Description / Change No	Appd	Chk
Drawing not complete or approved for manufacture			
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or GEA Process Engineering Ltd.			
THIRD ANGLE PROJECTION		Scale	Tolerances unless otherwise stated
Plot-Datum PROJECTION THIRD ANGLE Scale Tolerances unless otherwise stated		ISO 13920 - BF	ISO 2768 - mk
Drawn	Date	Modified	Date
PM	07/11/2006		07/11/2006
G1951-B01-601		Status	Drawing No
Rev	95	Sht No	98
Next Sht	98		3


GEA BUCK SYSTEMS
B01 BLENDER/D01 POST HOIST CONTROL CIRCUIT HMI & PLC RACK LAYOUT






PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or									
Details	Description / Change No		Chk	Appd	approved for manufacture							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST CPU DIG INPUT TERM X11 DIG I/P 0-7 RACK 1 SLOT 3							
THIRD ANGLE		Scale			Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006		07/11/2006		G1951-B01-601	Next Sht	99	3
Plot-Datum												



PCP DRG. No. C4341



Revision	REVISED TO COMMENTS		Drawing not complete or approved for manufacture									
Details	Description / Change No		Chk	Appd								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST CPU DIG INPUT TERM X12 DIG I/P 0-7 RACK 1 SLOT 3							
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	99	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	07/11/2006		07/11/2006		G1951-B01-601	Next Sht	100	3
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or			
Details	Description / Change No		Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST CPU DIG INPUT TERM X12 DIG I/P 8-15 RACK 1 SLOT 3	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	08/11/2006	08/11/2006
Plot-Datum						
				Status	Drawing No	Sht No
					G1951-B01-601	100
						Rev
						3
					Next Sht	101


Revision		REVISD TO COMMENTS	
Details	Description / Change No	Appd	Appd
Drawing not complete or approved for manufacture			
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd			
THIRD ANGLE PROJECTION		Scale	
Tolerances unless otherwise stated			
Drawn	Date	Modified	Date
PM	08/11/2006		08/11/2006
G1951-B01-601		G1951-B01-601	
Next Shd	103	Rev	102
Plot-Datum			






PCP DRG. No. C4341

Revision	REVISED TO COMMENTS			Drawing not complete or								
Details	Description / Change No			Chk	Appd	approved for manufacture						
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						B01 BLENDER/D01 POST HOIST DIGITAL INPUTS DIG I/P 8-15 RACK 1 SLOT 4						
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	104	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	08/11/2006		08/11/2006		G1951-B01-601	Next Sht	105	3
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO COMMENTS		Drawing not complete or				
Details	Description / Change No		Chk	Appd	approved for manufacture		
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST DIGITAL INPUTS DIG I/P 16-23 RACK 1 SLOT 4		
THIRD ANGLE		Scale			Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	08/11/2006	08/11/2006	Status
Plot-Datum					Drawing No	Sht No	Rev
					G1951-B01-601	105	3
					Next Sht	106	

Revision		AS TESTED	
Details		Description / Change No	
Appd		Appd	
Drawing not complete or approved for manufacture			
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or GEA Process Engineering Ltd			
THIRD ANGLE PROJECTION		Scale	
		Tolerances unless otherwise stated ISO 13920 - BF ISO 2768 - mK	
Plot-Datum		Drawn	
		PM 16/10/2006	
		Date 16/10/2006	
		Modified 16/10/2006	
		Date 16/10/2006	
		Status	
		Drawing No G1951-B01-601	
		Next Shd 107	
Rev		Sht No	
106		106	

GEA BUCK SYSTEMS
 B01 BLENDER/D01 POST HOIST
 DIGITAL INPUTS
 DIG I/P 24-32 RACK 1 SLOT 4



1 2 3 4 5 6 7 8


1 2 3 4 5 6 7 8


A B C D E F


A B C D E F

SHT 105.8 3313 -/-

SHT 105.8 3304


Revision		AS TESTED	
Details		Description / Change No	
Appd		Appd	
Drawing not complete or approved for manufacture			
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd			
THIRD ANGLE PROJECTION		Scale	
		Tolerances unless otherwise stated	
ISO 13920 - BF ISO 2768 - mk PM		Drawn Date Modified Date	
GEA BUCK SYSTEMS		Drawing No Status Date Modified Date	
B01 BLENDER/D01 POST HOIST CPU DIG OUTPUT DIG O/P 0-7 RACK 1 SLOT 5		G1951-B01-601 Next Shd 108 Rev 107	
Plot-Datum			







PCP DRG. No. C4341

Revision	AS TESTED	Drawing not complete or			
Details	Description / Change No	Chk	Appd	approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST CPU DIG OUTPUT DIG O/P 8-15 RACK 1 SLOT 5	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	PM	16/10/2006
Plot-Datum				Modified	Date
					18/10/2006
				Status	Drawing No
					G1951-B01-601
				Sht No	108
				Rev	2
				Next Sht	109


Revision		AS TESTED	
Details		Description / Change No	
Appd		Appd	
Drawing not complete or approved for manufacture			
<p>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</p>			
THIRD ANGLE PROJECTION		Scale	
			
Tolerances unless otherwise stated			
ISO 13920 - BF		ISO 2768 - mk	
Drawn	16/10/2006	Date	16/10/2006
Modified	16/10/2006	Date	16/10/2006
Status	G1951-B01-601		
Drawing No	G1951-B01-601		
Sht No	110	Next Sht	110
Rev	109		



Revision		AS TESTED	
Details		Description / Change No	
Appd		Appd	
chk		chk	
Appd		Appd	
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd			
THIRD ANGLE PROJECTION		Scale	
		Tolerances unless otherwise stated	
ISO 13920 - BF ISO 2768 - mk		Drawn PM Date 16/10/2006 Modified Date 16/10/2006	
Plot-Datum		Drawing No G1951-B01-601 Status Date 16/10/2006	
Sht No 110 Rev 2		Next Sht 111	



B01 BLENDER/D01 POST HOIST
 CPU DIG OUTPUT
 DIG O/P 24-32 RACK 1 SLOT 5

Drawing not complete or
 approved for manufacture





THIS PAGE INTENTIONALLY LEFT BLANK

PCP DRG. No. C4341




Revision	MODIFIED TO COMMENTS				Drawing not complete or									
Details	Description / Change No		Chk	Appd	approved for manufacture									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					B01 BLENDER/D01 POST HOIST SPARE SHEET									
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	111	Rev	
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	PM	08/11/2006	08/11/2006		G1951-B01-601	Next Sht	120	3
Plot-Datum														

	1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION							
B	SHEET		90/2	90/2	90/2	90/2	90/5	90/5
C	Cablemarking	Cabletype	Pin Number.					
D	Terminal strip	Destination symbol	Connection no.	2				
			Designation	X321	X322	X327	X328	
	Link							
	Terminal number		11	12	13	14	203	204
	Terminal type		O	O	O	O	O	O
	Terminal strip	Destination symbol	Connection no.	2				
			Designation	-S90.2.	-S90.2.	-U90.4.	-U90.4.	-U90.4.
	Cablemarking	Cabletype	Pin Number.	9013	9014	9004	9002	9007
				9008				
E	TERMINAL FUNCTION							
	ELEMENT FUNCTION		HSS-001-8002	HSS-001-8002				
F								

PCP DRG. No. C4341



Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 122
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht 123

	1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION							
B	SHEET		90/5	90/5				
C	Cablemarking	Cabletype	Pin Number.					
D	X32	Destination symbol	Connection no.					
D			Designation					
E		Link	Terminal number	Terminal type				
F	Terminal strip	Destination symbol	Connection no.	4	3			
F	Designation		-S90.6.	-S90.6.				
	Cablemarking	Cabletype	Pin Number.					
	TERMINAL FUNCTION							
	ELEMENT FUNCTION		HS-001-9200	HS-001-9200				

Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 123
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht 124

PCP DRG. No. C4341



	1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION							
B	SHEET		120/2	120/2				
C	Cablemarking	Cabletype	Pin Number.					
D	X31	Destination symbol	Connection no.					
D			Designation					
E		Link	Terminal number	Terminal type	201	202		
F	Terminal strip	Destination symbol	Connection no.					
F	Designation		-S30.1. 1					
	Cablemarking	Cabletype	Pin Number.	PE	3304			
	TERMINAL FUNCTION							
	ELEMENT FUNCTION		ISOL					

Revision				Drawing not complete or									
Details	Description / Change No			Chk	Appd	approved for manufacture							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						B01 BLENDER/D01 POST HOIST							
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	125	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK			03/01/2007	G1951-B01-601	Next Sht	126	
Plot-Datum													




PCP DRG. No. C4341

1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION		M4 P/S F1				
B	SHEET		99/2	ZS-001-4000			
C	Cablemarking	Cabletype	Pin Number.				
D	MJB	Destination symbol	Connection no.	2			
			Designation	-S99.2. BK			
		Link	Terminal number	3			
		Terminal type		O	O	O	O
	Terminal strip	Destination symbol	Connection no.	BN			
			Designation	-S99.2. 1			
	Cablemarking	Cabletype	Pin Number.	3313	9901		
E	TERMINAL FUNCTION		ZS-001-4000				
F	ELEMENT FUNCTION						

PCP DRG. No. C4341




Revision				Drawing not complete or			
Details	Description / Change No	Chk	Appd	approved for manufacture			
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST			
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK				03/01/2007
Plot-Datum				Status	Drawing No	Sht No	Rev
					G1951-B01-601	127	127
						Next Sht	128

ELEMENT FUNCTION	SHEET	Cablemarking	Cabletype	Pin Number.	Destination symbol	Link	Terminal number	Terminal type	Terminal strip	Destination symbol	Connection no.	Designation	Cablemarking	Cabletype	Pin Number.	TERMINAL FUNCTION	ELEMENT FUNCTION
M4 P/S E12	50/1				2			O	13				4808			ZS-4001/1	
	50/4				1			O	2				4806			M4 P/S F7	
	48/7						1	O	X33.1				4807				
	48/7				2		3	O	X33.3				4807				
	48/7				2		4	O	X33.4				4807				
M3500	49/4				V1		5	O	X31.29				3313				
M3500	49/4				V2		6	O	-M4.9.1				4802			LIFT INVERTER	
M-001-2000	52/4				V1		7	O	-A4.8.2				5101			SC-001-2000	
M-001-2000	52/4				V2		8	O	-A5.1.2				5102			SC-001-2000	
M4.000	54/5				3		9	O	-A5.1.2				5401			MILL INVERTER	
M4.000	54/5				2		10	O	-A53.2				5402			MILL INVERTER	
	92/3						15	O	-A53.2				9201				
	92/3						16	O	X3.117				9202				
	92/3						17	O	X3.118				9202				
	92/3						18	O	X3.115				9201				
	92/4						19	O	X3.116				9202				
	92/4						20	O	X3.121				9203				
	92/4						21	O	X3.122				9204				
	92/4						22	O	X3.119				9203				
	92/4						23	O	X3.120				9204				
	92/6						24	O	X3.125				9205				
	92/6						25	O	X3.126				9206				
	92/6						26	O	X3.123				9205				
	92/6						27	O	X3.124				9206				
PS-001-9010	98/3				3		27	O	X3.129				3313				
	98/4						28	O	X3.127				3313				
	98/6						29	O	X3.15				3313				
	98/7						30	O	X3.131				3313				
	98/7						31	O	X3.130				3313				
	99/1						32	O	X3.164				3304				
PS-001-9010	98/3				4		33	O	-S98.3				9802				
	98/4						34	O	-CPU95.5.23				9804				
	98/6						35	O	-CPU95.5.25				9806				
	98/7						36	O	-CPU95.5.27				9807				
MILL INVERTER	98/7				L2		37	O	-CPU95.5.28				9808				
	99/2						38	O	-CPU95.5.29				3313				
	99/4						39	O	X3.139				3313				
	99/5						40	O	X3.138				3313				
HSS-001-3502	99/5				13		41	O	X3.141				3313				
	99/6						42	O	X3.140				3313				
HSS-001-4000	99/7				13		43	O	X3.148				3313				
	99/2				2		44	O	-CPU95.5.2				9901				
	99/4						45	O	-CPU95.5.5				9904				
HSS-001-3502	99/5				14		46	O	-CPU95.5.6				9905				
	99/6						47	O	-CPU95.5.8				9907				
	99/7						48	O	-CPU95.5.9				9908				
HSS-001-4000	100/2				14		49	O	-CPU95.5.12				3313				
	100/4						50	O	X3.142				3313				
	100/6						51	O	X3.150				3313				
	100/7						52	O	X3.149				3313				
	100/7						53	O	X3.152				3313				
	100/7						54	O	X3.151				3313				
HSS-001-2000	100/2						55	O	-CPU95.5.1				10001				
	100/4						56	O	-CPU95.5.15				10004				
	100/6						57	O	-CPU95.5.17				10006				
	100/7						58	O	-CPU95.5.18				10007				
	101/2						59	O	-CPU95.5.19				10008				
	101/2						60	O	-CPU95.5.22				10101				
	101/3						61	O	-CPU95.5.23				10102				
	101/4						62	O	-CPU95.5.24				10103				
	101/6						63	O	-CPU95.5.25				10104				
	101/7							O	-CPU95.5.28				10107				
								O	-CPU95.5.29				10108				

Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				
THIRD ANGLE  Scale		Tolerances unless otherwise stated		
PROJECTION 		Drawn	Date	Modified
Plot-Datum		Date	Date	Status
		Drawing No G1951-B01-601		Sht No 129
		Next Sht 130		Rev




PCP DRG. No. C4341

1		2		3		4		5		6		7		8	
A	ELEMENT FUNCTION													A	
	SHEET														
B														B	
C	Cablemarking		Cabletype		Pin Number.										C
	X31	Destination symbol		Connection no.		Designation									
Link		Terminal number		Terminal type										D	
Terminal strip		Destination symbol		Connection no.		Designation									
Cablemarking		Cabletype		Pin Number.										E	
TERMINAL FUNCTION													E		
ELEMENT FUNCTION															
3313		X3.1123		1										F	
3313		X3.1126		1											
3313		X3.1125		1											
3313		X3.1128		1											
3313		X3.1127		1											
3313		X3.1130		1											
3313		X3.1129		1											
10601		-CPU95.5		32											
10602		-CPU95.5		33											
10603		-CPU95.5		34											
10604		-CPU95.5		35											
10605		-CPU95.5		36											
10606		-CPU95.5		37											
10607		-CPU95.5		38											
10608		-CPU95.5		39											
10702															
10703															
10704															
10705															
10706															
10707															
10708															
3304		X3.1147		1											
3304		X3.1146		1											
3304		X3.1149		1											
3304		X3.1148		1											
3304		X3.1151		1											
3304		X3.1150		1											
3304		X3.1161		1											
10801															
10802										X3.4		2			
10803										X3.4		2			
10804															
10805															
10806															
10807															
10808															
3304		X3.1152		1											
3304		X3.1163		1						X3.4		2			
3304		X3.1162		1											
3304		X3.1165		1											
3304		X3.1164		1											
3304		X3.1167		1											
3304		X3.1166		1											
3304		X3.1177		1						X3.4		2			
10901															
10902															
10903															
10904															
10905															
10906															
10907															
10908															
3304		X3.1168		1						X3.4		2			
3304		X3.1179		1											
3304		X3.1178		1											
3304		X3.1181		1											
3304		X3.1180		1											
3304		X3.1183		1											
3304		X3.1182		1											

Revision				Drawing not complete or	
Details		Description / Change No		approved for manufacture	
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST	
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Modified	Date
Plot-Datum				Status	Drawing No
				03/01/2007	G1951-B01-601
				Sht No	131
				Next Sht	132



PCP DRG. No. C4341

	1	2	3	4	5	6	7	8	
A	ELEMENT FUNCTION		SHEET		104/2	104/2	48/7	48/7	
B	Cablemarking		Cabletype	Pin Number.					
C	X3.3	Destination symbol	Connection no.		X3.1213 2	X3.1214 2	X3.11 1	X3.13 1	
			Designation			X3.14 1	X3.17 2	X3.18 2	X3.122 2
		Link							
		Terminal number							
Terminal strip	Destination symbol	Connection no.							
		Designation							
D	Cablemarking		Cabletype	Pin Number.	3313	10401	4806	4807	
E	TERMINAL FUNCTION		ELEMENT FUNCTION		HSS-001-3510	HSS-001-3510	ZS-3512/1	ZS-3510/1	
F	PCP DRG. No. C4341								



Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 134
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht 135

1	2		3			4		5			6			7			8							
A	ELEMENT FUNCTION																							
	SHEET		104/6	104/5	105/5	105/6	105/5	105/6																
B																								
C	Cablemarking		Cabletype		Pin Number.																			
	X35	Destination symbol	Connection no.																					
			Designation																					
	Link																							
Terminal number		4			5			7			8			9			10							
Terminal type		O			O			O			O			O			O							
D	Terminal strip	Destination symbol	Connection no.		2																			
			Designation		X3.197			X3.4 9			X3.111			X3.112			X3.119							
Cablemarking		Cabletype		Pin Number.			3313			3304			3313			3313			10505			10506		
E	TERMINAL FUNCTION																							
	ELEMENT FUNCTION																							
F																								

PCP DRG. No. C4341



Revision			Drawing not complete or	
Details	Description / Change No		Chk	Appd
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 136
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht 137


	1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION							
B	SHEET		103/6	103/6	92/6	92/6	92/6	92/6
C	Cablemarking	Cabletype	Pin Number.					
D	Terminal strip	Destination symbol	Connection no.	X3.1209 2	X3.1212 2	X3.120 2	X3.119 2	X3.123 2
			Designation	X3.1209 2	X3.1212 2	X3.120 2	X3.119 2	X3.123 2
	Link		Terminal number	1	2	3	4	
			Terminal type	○	○	○	○	○
	Terminal strip	Destination symbol	Connection no.	X3.2 1	-S92.6. 4	-S92.6. 1	-S92.6. 1	-S92.6. 2
			Designation	X3.2 1	-S92.6. 4	-S92.6. 1	-S92.6. 1	-S92.6. 2
E	Cablemarking	Cabletype	Pin Number.	3313	10307	9204	9203	9205
F	TERMINAL FUNCTION							
	ELEMENT FUNCTION		HSS-001-8001	HSS-001-8001	HSS-001-8001	HSS-001-8001	HSS-001-8001	

Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 137
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht 138


PCP DRG. No. C4341

	1	2	3	4	5	6	7	8
A	ELEMENT FUNCTION		M4 P/S F1					
B	SHEET		99/1 99/2					
C	Cablemarking	Cabletype	Pin Number.					
C	Destination symbol	Connection no.		2	1			
		Designation						
	Link	Terminal number		1				
	Terminal type							
D	Terminal strip	Destination symbol	Connection no.		1	2		
		Designation						
	Cablemarking	Cabletype	Pin Number.	9901	3313			
E	TERMINAL FUNCTION							
	ELEMENT FUNCTION		M2 P/S D5					
F	PCP DRG. No. C4341							



Revision			Drawing not complete or	
Details	Description / Change No	Chk	Appd	approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				B01 BLENDER/D01 POST HOIST
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn
PROJECTION			ISO 13920 -BF ISO 2768 -mK	Date
Plot-Datum				Modified
				Date
				Status
				Drawing No
				Sht No 138
				Rev
				03/01/2007
				G1951-B01-601
				Next Sht



ENCLOSURE DEPTH 500MM



Revision	AS TESTED	---	---	Drawing not complete or approved for manufacture								
Details	Description/Change No:	Chk	Appd									
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.				G1951-B01 BLENDER/D01 POST HOIST MAIN PANEL GENERAL ARRANGEMENT								
THIRD ANGLE PROJECTION				Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Sht
Plot-Datum :		---	ISO 13920 -BF	ISO 2768 -MK	PM	20/09/06	PM	21/12/06		G1951-B01-610	of 1	1



DOOR TO BE FITTED WITH EARTH BRAID

ENCLOSURE 250MM DEEP
STAINLESS STEEL CONSTRUCTION

P.C.P. DRG. No C4341

Revision	AS TESTED			Drawing not complete or approved for manufacture									
Details	Description/Change No:	Chk	Appd										
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.		GEA Buck Systems		OPERATOR STATION PANEL LAYOUT									
THIRD ANGLE PROJECTION		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Sht	1	Rev	1
			ISO 13920 ISO 2768	PM	26/09/06	PM	21/12/06		G1951-B01-620	of	1		1
Plot-Datum :													

A3

G1951-Cable Layout

SIZE mm2	CABLE TYPE	CIRCUIT CLASS	SOURCE	DESTINATION	HARTING CONNECTOR REFERENCE	TERMINAL BLOCK	TERMINAL No	P&ID REF.	CORE NUMBER	DESCRIPTION
			B01 MAIN		N/A					
			B01 MAIN		N/A					
			B01 MAIN		N/A					
			B01 MAIN		N/A					
			SLEW MOT.ISOL.	BRIDGE RECTIFIER	N/A	L1	L1		L1	SLEW MOTOR BRIDGE RECTIFIER
			SLEW MOT.ISOL.	BRIDGE RECTIFIER	N/A	L2	L2		L2	SLEW MOTOR BRIDGE RECTIFIER
			SLEW MOT.ISOL.	SLEW MOTOR	N/A	39L04	39L04	M-XXX-3502	1	SLEW MOTOR
			SLEW MOT.ISOL.	SLEW MOTOR	N/A	39L05	39L05	M-XXX-3502	2	SLEW MOTOR
			SLEW MOT.ISOL.	SLEW MOTOR	N/A	39L06	39L06	M-XXX-3502	3	SLEW MOTOR
			SLEW MOT.ISOL.	SLEW MOTOR	N/A	E	E	M-XXX-3502	E	SLEW MOTOR
			SLEW MOT.ISOL.	SLEW MOTOR	N/A	E	E	M-XXX-3502	SCN	SLEW MOTOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	L1	L1			LIFT MOT. BRIDGE RECT.
			B01 MAIN	D01 HOIST MOUNT JB	N/A	L2	L2			LIFT MOT. BRIDGE RECT.
			B01 MAIN	D01 HOIST MOUNT JB	N/A	1	1			LIFT MOT. BRIDGE RECT.
			B01 MAIN	D01 HOIST MOUNT JB	N/A	2	2			LIFT MOT. BRIDGE RECT.
			B01 MAIN	D01 HOIST MOUNT JB	N/A	U	U	M-XXX-3500		LIFT MOTOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	V	V	M-XXX-3500		LIFT MOTOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	W	W	M-XXX-3500		LIFT MOTOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	E	E	M-XXX-3500	SCN	LIFT MOTOR
			B01 MAIN	B01 PED. BLE. JB	N/A	L1	L1		L1	ROT. ISOL. BRIDGE RECT.
			B01 MAIN	B01 PED. BLE. JB	N/A	L2	L2		L2	ROT. ISOL. BRIDGE RECT.
			B01 MAIN	B01 PED. BLE. JB	N/A	1	1		1	ROT. ISOL. BRIDGE RECT.
			B01 MAIN	B01 PED. BLE. JB	N/A	2	2		2	ROT. ISOL. BRIDGE RECT.
			B01 MAIN	B01 ROTATE MOTOR	N/A	U	U	M-XXX-2000	U	ROTATE MOTOR
			B01 MAIN	B01 ROTATE MOTOR	N/A	V	V	M-XXX-2000	V	ROTATE MOTOR
			B01 MAIN	B01 ROTATE MOTOR	N/A	W	W	M-XXX-2000	W	ROTATE MOTOR
			B01 MAIN	B01 ROTATE MOTOR	N/A	E	E	M-XXX-2000	SCN	ROTATE MOTOR
			B01 MAIN	M01 QUADRO MILL MOT.	N/A	L1	L1	M-XXX-4000	1	MILL MOTOR
			B01 MAIN	M01 QUADRO MILL MOT.	N/A	L2	L2	M-XXX-4000	2	MILL MOTOR
			B01 MAIN	M01 QUADRO MILL MOT.	N/A	L3	L3	M-XXX-4000	3	MILL MOTOR
			B01 MAIN	M01 QUADRO MILL MOT.	N/A	E	E	M-XXX-4000	E	MILL MOTOR
			B01 MAIN	M01 QUADRO MILL MOT.	N/A	SCN	SCN	M-XXX-4000	SCN	MILL MOTOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	X1.1	1	HSS-XXX-3502		SLEW MOTOR ISOLATOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	X1.1	2	HSS-XXX-3502		SLEW MOTOR ISOLATOR
			B01 MAIN	D01 HOIST MOUNT JB	N/A	X1.1	3	HSS-XXX-3502		SLEW MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	1	ZS-3512/2	1	OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	2	ZS-3510/B	2	LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	3	ZS-3510/B	3	LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	4	ZS-3512/2	4	OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	5	TS-3500	5	LIFT MOTOR THERMISTOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	6	TS-3500	6	LIFT MOTOR THERMISTOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	17	HSS-XXX-3510	7	HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	18	HSS-XXX-3510	8	HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	21	HSS-XXX-3510	9	HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	22	HSS-XXX-3510	10	HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	29	HSS-XXX-3500	11	LIFT MOTOR ISOLATOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	35	HSS-XXX-3500	12	LIFT MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	40	HSS-XXX-3502	11	SLEW MOTOR ISOLATOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	45	HSS-XXX-3502	13	SLEW MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	72	YI-XXX-3001	14	POWER SUPPLY HEALTHY
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	93	ZS-XXX-3512/2	11	OVERTRAVEL SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	94	ZS-XXX-3510A	11	LOAD/UNLOAD OVERTRAVEL SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	97	XS-XXX-4701	11	MILL IN POSITION +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	98	XS-XXX-3521	11	PROCESS POSITION SLEW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	99	XS-XXX-3520	11	LOAD/UNLOAD POSITION SLEW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	100	ZS-XXX-3512/2	15	OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	101	ZS-XXX-3510A	16	LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	104	XS-XXX-4701	17	MILL IN POSITION
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	105	XS-XXX-3521	18	PROCESS POSITION SLEW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	106	XS-XXX-3520	19	LOAD/UNLOAD POSITION SLEW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	78	YI-XXX-3001	20	POWER SUPPLY HEALTHY 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	139		21	ENCODER SET SIGNAL
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	213	HSS-XXX-3510	22	HOIST JB E-STOP
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.1	E	EARTH	E	EARTH
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	7	TS-3501	1	ROTATE MOTOR THERMISTOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	8	TS-3501	2	ROTATE MOTOR THERMISTOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	19	HSS-XXX-8001	3	M/C EMERGENCY STOP P/B

G1951-Cable Layout


SIZE mm2	CABLE TYPE	CIRCUIT CLASS	SOURCE	DESTINATION	HARTING CONNECTOR REFERENCE	TERMINAL BLOCK	TERMINAL No	P&ID REF.	CORE NUMBER	DESCRIPTION
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	20	HSS-XXX-8001	4	M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	23	HSS-XXX-8001	5	M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	24	HSS-XXX-8001	6	M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	39	ST-XXX-2102	7	BLENDER ROTATIONAL SPEED SENSOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	44	ST-XXX-2102	8	BLENDER ROTATIONAL SPEED SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	49	HSS-XXX-2000	7	ROTATE MOTOR ISOLATOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	54	HSS-XXX-2000	9	ROTATE MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	73	YI-XXX-9201	10	SAFE AREA VISUAL ALARM
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	74	HS-XXX-9201	11	SAFE AREA AUDIBLE ALARM
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	79	YI-XXX-9201	12	SAFE AREA VISUAL ALARM 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	80	HS-XXX-9201	12	SAFE AREA AUDIBLE ALARM 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	107	PS-XXX-9000	7	PEDESTAL JB MAIN AIR PRE SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	108	PS-XXX-3300	7	CAGE CLAMPED PRESS SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	109	ZS-XXX-3410	7	IBC IN POSITION SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	110	XS-XXX-3400	7	CAGE DOWN POSITION SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	161	XV-XXX-3000C	12	AIR CHECK ENABLE SOLENOID 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	162	XV-XXX-3000A	12	CLAMP SOLENOID 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	163	XV-XXX-3000B	12	UNCLAMP SOLENOID 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	115	PS-XXX-9000	13	PEDESTAL JB MAIN AIR PRE SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	116	PS-XXX-3300	14	CAGE CLAMPED PRESS SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	117	ZS-XXX-3410	15	IBC IN POSITION SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	118	XS-XXX-3400	16	CAGE DOWN POSITION SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	153	XV-XXX-3000C	17	AIR CHECK ENABLE SOLENOID
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	154	XV-XXX-3000A	18	CLAMP SOLENOID
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	155	XV-XXX-3000B	19	UNCLAMP SOLENOID
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.1	E		E	EARTH
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	9	M-XXX-4000	1	MILL MOTOR THERMISTOR INPUT
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	10	M-XXX-4000	2	MILL MOTOR THERMISTOR INPUT
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	30	ZS-XXX-4000	3	MILL MOT. ROT. SPD. SENSOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	36	ZS-XXX-4000	4	MILL MOT. ROT. SPD. SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	38	ZS-XXX-4000	5	MILL MOTOR ROTATIONAL SPEED SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	42	HSS-XXX-4000	3	MILL MOTOR ISOLATOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	43	ZS-XXX-4000	6	MILL MOTOR ROTATIONAL SPEED SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	47	HSS-XXX-4000	7	MILL MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	111	YS-XXX-4001/2	3	MILL SAFETY SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	112	YS-XXX-4001/1	3	MILL DOCKING SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	119	YS-XXX-4001/2	8	MILL SAFETY SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	120	YS-XXX-4001/1	9	MILL DOCKING SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.1	E		E	EARTH
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	11	HSS-XXX-8002	1	B01 PED. BLENDER OP E-STOP N/C
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	12	HSS-XXX-8002	2	B01 PED. BLENDER OP E-STOP N/C
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	13	HSS-XXX-8260	3	OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	14	HSS-XXX-8260	4	OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	27	PS-XXX-9010	5	AIR PRESSURE SWITCH MAIN PANEL +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	0V		6	0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	33	PS-XXX-9010	7	AIR PRESSURE SWITCH MAIN PANEL
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	205	HSS-XXX-8002	8	MAIN PANEL E-STOP N/O
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	206	HSS-XXX-8002	9	MAIN PANEL E-STOP N/O
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 MAIN CNT. PNL.	N/A	X3.1	E		E	EARTH
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	15	HSS-XXX-8000	1	OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	16	HSS-XXX-8000	2	OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	25	HSS-XXX-8260	3	OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	26	HSS-XXX-8260	4	OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	31	ST-XXX-2102	5	BLENDER ROT SPD SENSOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	37	ST-XXX-2102	6	BLENDER ROT SPD SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	75	YI-XXX-9200	7	OP CONTROLS ON
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	81	YI-XXX-9200	8	OP CONTROLS ON 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	83	XS-XXX-2200	5	BLENDER IBC UPRIGHT +24VDC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	84	XS-XXX-2201	5	BLENDER IBC INVERTED +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	85	HS-XXX-9200	5	OPERATOR PANEL E-STOP RESET +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	87	X3.2 17, X3.2 19	8	0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	89	XS-XXX-2200	9	BLENDER IBC UPRIGHT
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	90	XS-XXX-2201	10	BLENDER IBC INVERTED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	91	HS-XXX-9200	11	OPERATOR PANEL E-STOP RESET
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	203	HS-XXX-9200	12	E-STOP RESET
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	204	HS-XXX-9200	13	E-STOP RESET
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	207	HSS-XXX-8260	14	FORTRESS KEY OPERATED

G1951-Cable Layout

SIZE mm2	CABLE TYPE	CIRCUIT CLASS	SOURCE	DESTINATION	HARTING CONNECTOR REFERENCE	TERMINAL BLOCK	TERMINAL No	P&ID REF.	CORE NUMBER	DESCRIPTION
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	208	HSS-XXX-8000	5	OPERATOR PANEL E-STOP OPERATED +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	209	HSS-XXX-8001	5	MACHINE MOUNTED E-STOP OPERATED +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	210	HSS-XXX-8260	15	FORTRESS KEY OPERATED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	211	HSS-XXX-8000	16	OPERATOR PANEL E-STOP OPERATED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	212	HSS-XXX-8001	17	MACHINE MOUNTED E-STOP OPERATED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.1	E		E	EARTH
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	1	HSS-XXX-8000		OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	2	HSS-XXX-8000		OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	3	HSS-XXX-8000		OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	4	HSS-XXX-8000		OP. PNL. E-STOP PED. BLE.
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	5	HSS-XXX-8260		OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	6	HSS-XXX-8260		OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	7	HSS-XXX-8260		OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	8	HSS-XXX-8260		OP. PNL. FORTRESS KEY
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	9	ST-XXX-2102		BLENDER ROTATIONAL SPEED SENSOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	10	ST-XXX-2102		BLENDER ROTATIONAL SPEED SENSOR 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	11	ST-XXX-2102		BLENDER ROTATIONAL SPEED SENSOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	12	YI-XXX-9200		OP CONTROLS ON
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	13	YI-XXX-9200		OP CONTROLS ON 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	14	XS-XXX-2200		BLENDER IBC UPRIGHT +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	15	XS-XXX-2201		BLENDER IBC INVERTED +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	16	HS-XXX-9200		OPERATOR PANEL E-STOP RESET +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	17	XS-XXX-2200		BLENDER IBC UPRIGHT 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	18	XS-XXX-2200		BLENDER IBC UPRIGHT
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	19	XS-XXX-2201		BLENDER IBC INVERTED 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	20	XS-XXX-2201		BLENDER IBC INVERTED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLENDER OP	N/A	X3.2	21	HS-XXX-9200		OPERATOR PANEL E-STOP RESET
1	MULTICORE									
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	1	ZS-3512/2		OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	2	ZS-3510/B		LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	3	ZS-3510/B		LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	4	ZS-3512/2		OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	5	HSS-XXX-3510		HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	6	HSS-XXX-3510		HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	7	HSS-XXX-3510		HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	8	HSS-XXX-3510		HOIST JB E-STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	9	HSS-XXX-3500		LIFT MOTOR ISOLATOR
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	10	HSS-XXX-3500		LIFT MOTOR ISOLATOR 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	11	YI-XXX-3001		POWER SUPPLY HEALTHY
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	12	YI-XXX-3001		POWER SUPPLY HEALTHY 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	13	ZS-XXX-3512/2		OVERTRAVEL SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	14	ZS-XXX-3510A		LOAD/UNLOAD OVERTRAVEL SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	15	XS-XXX-3521		PROCESS POSITION SLEW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	16	XS-XXX-3520		LOAD/UNLOAD POSITION SLEW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	17	ZS-XXX-3512/2		OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	18	ZS-XXX-3510A		LOAD/UNLOAD OVERTRAVEL SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	19	ZS-XXX-3521		PROCESS POSITION SLEW 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	20	XS-XXX-3521		PROCESS POSITION SLEW
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	21	XS-XXX-3520		LOAD/UNLOAD POSITION SLEW 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.3	22	XS-XXX-3520		LOAD/UNLOAD POSITION SLEW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	1	PS-XXX-9000		PEDESTAL JB MAIN AIR PRE SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	2	PS-XXX-3300		CAGE CLAMPED PRESS SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	3	ZS-XXX-3410		IBC IN POSITION SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	4	XS-XXX-3400		CAGE DOWN POSITION SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	5	PS-XXX-9000		PEDESTAL JB MAIN AIR PRE SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	6	PS-XXX-3300		CAGE CLAMPED PRESS SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	7	ZS-XXX-3410		IBC IN POSITION SW 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	8	ZS-XXX-3410		IBC IN POSITION SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	9	XS-XXX-3400		CAGE DOWN POSITION SW 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.4	10	XS-XXX-3400		CAGE DOWN POSITION SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	1	ZS-XXX-4000		MILL MOTOR ROTATIONAL SPEED SENSOR +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	2	ZS-XXX-4000		MILL MOTOR ROTATIONAL SPEED SENSOR 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	3	ZS-XXX-4000		MILL MOTOR ROTATIONAL SPEED SENSOR

G1951-Cable Layout

SIZE mm2	CABLE TYPE	CIRCUIT CLASS	SOURCE	DESTINATION	HARTING CONNECTOR REFERENCE	TERMINAL BLOCK	TERMINAL No	P&ID REF.	CORE NUMBER	DESCRIPTION
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.5	4	XS-XXX-4701		MILL IN POSITION SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.5	5	XS-XXX-4701		MILL IN POSITION SW 0V
1	MULTICORE	CONTROLS<65V	B01 MAIN	D01 HOIST MOUNT JB	N/A	X3.5	6	XS-XXX-4701		MILL IN POSITION SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	7	YS-XXX-4001/2		MILL SAFETY SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	8	YS-XXX-4001/1		MILL DOCKING SW +24V DC
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	9	YS-XXX-4001/2		MILL SAFETY SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	M01 QUADRO MILL	N/A	X3.5	10	YS-XXX-4001/1		MILL DOCKING SW
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	1	HSS-XXX-8001		M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	2	HSS-XXX-8001		M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	3	HSS-XXX-8001		M/C EMERGENCY STOP P/B
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	4	HSS-XXX-8001		M/C EMERGENCY STOP P/B
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	5	XV-XXX-3000C		AIR CHECK ENABLE SOLENOID +24V DC
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	6	XV-XXX-3000A		CLAMP SOLENOID +24V DC
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	7	XV-XXX-3000B		UNCLAMP SOLENOID +24V DC
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	8	XV-XXX-3000C		AIR CHECK ENABLE SOLENOID
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	9	XV-XXX-3000A		CLAMP SOLENOID
	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	10	XV-XXX-3000B		UNCLAMP SOLENOID
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	11	HSS-XXX-8260		FORTRESS KEY OPERATED +24V DC
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	12	HSS-XXX-8000		OPERATOR PANEL E-STOP OPERATED +24V DC
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	13	HSS-XXX-8001		MACHINE MOUNTED E-STOP OPERATED +24V DC
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	14	HSS-XXX-8260		FORTRESS KEY OPERATED
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	15	HSS-XXX-8000		OPERATOR PANEL E-STOP OPERATED
		CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.6	16	HSS-XXX-8001		MACHINE MOUNTED E-STOP OPERATED
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.7	1	YI-XXX-9201		SAFE AREA VISUAL ALARM
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.7	3	YI-XXX-9201		SAFE AREA VISUAL ALARM
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.7	2	HS-XXX-9201		SAFE AREA AUDIBLE ALARM
1	MULTICORE	CONTROLS<65V	B01 MAIN	B01 PED. BLE. JB	N/A	X3.7	4	HS-XXX-9201		SAFE AREA AUDIBLE ALARM



BLENDER AT REST (LIFTING FRAME ON FLOOR)

ROTATING CAGE

ARMS PARKED

Revision	Original	Description/Change No.	Checked	Approved
1	Original			


This drawing or document is copyrighted by and in the property of GEA Process Engineering Ltd. or its wholly owned subsidiary. It is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, without prior written consent of GEA Process Engineering Ltd.

GEA PNEUMATIC ASSEMBLY
 SP200 - SINGLE PEDESTAL BLENDER

Scale: 1:1
 Date: 07/06/03
 Drawn: [Name]
 Checked: [Name]
 Approved: [Name]

Plot: Datum

R0 1st ISSUE
 R1 TAG NUMBERS ADDED
 R0 07/06/03
 R1 24/04/06



- ### NOTES
- REFER TO PNEUMATIC CIRCUIT DIAGRAM G1951-B01-801.
 - MAIN AIR PRESSURE SWITCH SET TO CHANGE OVER AT 3.75BarG FALLING
 - CAGE CLAMPED PRESSURE SWITCH SET TO CHANGE OVER AT 1.4BarG RISING
 - NOT USED
 - HARD WIRED INTERLOCK
 - REFER TO CONNECTION DIAGRAM G1951-M01-630 FOR SERVICES AND TERMINATION DETAILS.
- NB: CONTROL SYSTEMS SUPPLIER TO PROVIDE TERMINATION DIAGRAM, MACHINE AND SITE CABLE SCHEDULE, ELECTRICAL TERMINATION AND HOOK UP DIAGRAMS
- MMM = MACHINE (ID) NUMBER
 - ** (PS) = INSTRUMENT PREFIX
 - XXX = NOVARTIS TAG NUMBERS
 - ZZZ(5100) = SEQUENTIAL LOOP TAG NUMBER
- FOR ALL P&IDs WITHIN A SYSTEM.
- CONTROL OPERATIONS ARE INITIATED VIA THE MAIN CONTROL SYSTEM (SUPPLIED BY GEA BUCK SYSTEMS).
 - SOLENOID VALVES, REMOTE I/O, TERMINALS AND CONNECTORS ARE CONTAINED WITHIN THE CONTROL PANEL.
- ROTATION MOTOR WILL NOT START OR CONTINUE TO RUN AT ANY SPEED OR IN EITHER DIRECTION UNLESS IBC IS CONFIRMED AS CLAMPED.
 - CLAMP/UNCLAMP AIR MOTOR WILL NOT RUN IN EITHER DIRECTION UNLESS IBC IS CONFIRMED AS UPRIGHT.





MOTOR DETAILS					
TAG	kW	AMPS	RPM	GEARBOX O/P RPM	COMMENTS
M2000	9.5	20.5A	1410	18.5	TBC
-	-	-	-	-	-

INSTRUMENT LINE SYMBOLS	
INSTRUMENT TAG	DESCRIPTION
⊕ ????	INSTRUMENTS WHICH ARE FIELD MOUNTED
⊖ ????	INSTRUMENTS WHICH ARE MOUNTED ON A PANEL
⊗ ????	INSTRUMENTS WHICH ARE MOUNTED WITHIN A PANEL

INSTRUMENT LINE SYMBOLS	
INSTRUMENT LINE	DESCRIPTION
---	PNEUMATIC SIGNAL
---	ELECTRICAL SIGNAL
---	ELECTRICAL BINARY SIGNAL


MACHINE MATRIX (NOTE 7)					
MACHINE NUMBER	SYSTEM TAG No.	AREA	NOVARTIS TAG No.	ROOM No	COMMENTS
G1951-B01	001	BLENDING	202.M.0311	306B	

Revision	UPDATED TO CUSTOMER COMMENTS	---	---	Approval Withdrawn, Old revision of document								
Details	Description/Change No:	Chk	Appd									
<p>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.</p>						SP2000 SINGLE PEDESTAL BLENDER P&ID						
THIRD ANGLE PROJECTION		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Shr	1	Rev
Plot-Datum :		---	ISO 13920 -BF ISO 2768 -mK	MAPA	4/Dec/06	MAPA	4/Dec/06	BK	G1951-B01-901	of	1	05
CAD-BSL-G1951-B01-901-05.DWG												



SWL 300 kg

NOTE:-
THE 'SAFE WORKING LOAD' ETCHED LABEL MUST BE SHOWN ON A VISIBLE PART OF THE LIFT ATTACHMENT WHICH IS NOT REMOVABLE ie. COVER OR GUARD.




ETCHED LABEL DETAILS

MAT'L:- BSEN 10088-2-1.4301
EXTERNAL SURFACE FINISH
1.0um RA MAX

8kN PULL OUT
PER BOLT





PULL OUT FORCE GIVEN IS FOR PH600 HOIST AT MAX LOAD CONDITION AT ANY SLEW POSITION. 920kg INC STEELWORK. THE FIGURE DOES NOT CONTAIN ANY FACTORS OF SAFETY. FLOOR ANCHOR BOLTS (BY OTHERS) MUST BE SPECIFIED WHICH EXCEED THIS FIGURE WITH AN APPROPRIATE FACTOR OF SAFETY.

Revision	AMENDED TO AS BUILT NOTES	---	---	Drawing not complete
Def'n	Description/Change No.	---	---	or approved for manufacture
Drawn	---	---	---	---
Checked	---	---	---	---
Approved	---	---	---	---
		PH600 POST HOIST		
THIRD ANGLE PROJECTION	Scale	1:12.5	Drawn	Date
Proj.-Dwg Unit	ISO 1928	-B	ISO 2768	-M
			REBNA	4/JAN/07
			RE	G1951-D01-001
				4/06



02	SENSOR REPOSITIONED, GUIDES ADDED	RMB	18/Dec/06
Rev. No.	Description of Revision	Revised By	Date
<small>This drawing or document is COPYRIGHTED by and in the property of GEA Process Engineering (PTE) Ltd. All rights reserved. It is not to be copied, stored, or used for manufacture or otherwise without prior written consent of GEA Process Engineering (PTE) Ltd.</small>			
		LOADING FORK ASSEMBLY	
THIRD ANGLE PROJECTION	Scale: 1:5	Drawn: MXD	Date: 18/07/04
		Drawing No: G1951-D01-002	Sheet: 1 of 1

COLUMN HEIGHT = 1350 + TOTAL LIFT HEIGHT





ISOMETRIC VIEW

MINIMUM COLUMN TOTAL LIFT = 1000mm
DRAWING SHOWS 3m TOTAL LIFT AS EXAMPLE ONLY!

REFER TO CONTRACT SPECIFIC
GA FOR LIFT & COLUMN HEIGHTS

GSA Buck Systems		1019510	
SLEWING COLUMN ASST BOTTOM LEFT		1019510	
GSA Buck Systems		1019510	



Rev No.	Description of Revision	Revised By	Date
02	CABLE CHAIN SLEW LIMIT LABEL ADDED	RNE	20/Dec/07


This drawing is deemed to be the property of GEA Process Engineering (P) Ltd. and is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without the prior written consent of GEA Process Engineering (P) Ltd.

GEA Buck Systems
PH600 & PH1000 & PH1500
SLEW BASE BOTTOM CABLE ENTRY ASSY


Scale: 1:2
 Date: 26/05/06
 Drawing No: 1019464
 Part of 1 of 1
 No. APP-0044-02/06

SEE ALSO RELEVANT LIFT ASSEMBLY & CONTRACT SPECIFIC GA


ENERGY CHAIN O/A LENGTH
= TOTAL LIFT HEIGHT-425mm




01	Original	SWI	6/Jun/06
Rev No.	Description of Revision	Revised By	Date
<p>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering (NPS) Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering (NPS) Ltd.</p>		<p>GEA Buck Systems PH600 & PH1000 PH1500 & PH2000 CARRIAGE CABLE CONNECTION</p>	
<p>THIRD ANGLE PROJECTION</p>		<p>Scale 1:7.5</p>	<p>Drawn SWI</p> <p>Date 06/06/06</p> <p>Drawing No. 1019858</p> <p>Sht 1 of 1</p>
<p>TOLERANCES UNLESS OTHERWISE STATED</p> <p>MACHINING 0 = ±0.30 0.0 = ±0.10 ANG'DPTS = ±0.50°</p>		<p>FABRICATION 0 TO 500 = ±1.0 500 TO 1M = ±2.0 1M TO 2M = ±3.0</p> <p>ALL OTHER GEOMETRY TO COMPLY TO THE TOLERANCE STANDARDS SPECIFIED BELOW</p> <p>ISO 13920 -BF ISO 2768 -mK</p>	



LOCATION OF LIFT LIMIT SWITCH ASSEMBLY
 ASSEMBLY COMMON TO ALL COLUMN SIZES
 SIZE 2 HOIST COLUMN SHOWN (PLAN)



DETAIL A



DETAIL ON ARROW B

SWITCH POSITION MAY BE ADJUSTED
 UP AND DOWN LENGTH OF PRESSED CHANNEL
 SEE CONTRACT SPECIFIC GA FOR No OFF & POS'N

THIS DRAWING SUPER SEEDS D99108

Revision	Original	STDS	STDS	Document Complete and											
Details	Description/Change No:	Chk	Appd	Approved for use											
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.</small>				POST HOIST STD LIFT SWITCH ASSY											
THIRD ANGLE PROJECTION		Scale	1:1	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No.	Sht	1	Rev	
Plot-Datum :				ISO 13920	-BF	ISO 2768	-mK	CKP	20/Oct/05	CKP	20/Oct/05	DC	1017187	of	100
												CAD-BSL-1017187-00.DWG			


CONTAINER (NARROW WAY LOADED SHOWN)

PASS PNEUMATIC CABLE THROUGH GLAND & CUTOUT IN CENTRAL CARRIAGE PLATE TO CABLE CHAIN

CARRIAGE CABLE CONNECTION MUST BE USED IN CONJUNCTION WITH THIS ASSEMBLY

002 003 SET FACE OF PROXIMITY SWITCH TO DIMENSION SHOWN DO NOT MOUNT FACE OF SWITCH ABOVE TOP FACE OF FORK


**SEE FORK FAB'N FOR SWITCH MOUNTING DETAIL



SECTION A-A

CONTROL PANEL (IP65)

REAR COVER



CARRIAGE DRILLING DETAIL


**FOR CUTOUT ON U/SIDE OF FORK, SEE FORK FAB'N

**SEE FORK FABRICATION





**SEE FORK FAB'N DRG

**SEE EITHER STD OR CONTRACT SPECIFIC FORK ASSEMBLY

01	Original	SWI	7/Jun/06
Rev No.	Description of Revision	Revised By	Date
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering MP&SI Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied in whole or in part, used for manufacture or disclosed to others without prior written consent of GEA Process Engineering MP&SI Ltd.</small>			
GEA Buck Systems <small>TOLERANCES UNLESS OTHERWISE STATED: DIMENSIONS IN MILLIMETRES FRACTIONS DECIMALS ASSEMBLY 1/16 0.0625 1/32 0.03125 FINISHES UNLESS OTHERWISE STATED: ALL SURFACES UNLESS SPECIFIED TO THE CONTRARY TO BE TO THE FOLLOWING STANDARDS: ISO 13000 -01 ISO 1708 -01</small>		PH600 & PH1000 PH1500 & PH2000 STD IBC IN POSITION SWITCH ASSY	
THIRD ANGLE PROJECTION	Scale 1:5	Drawn SWI	Date 07/06/06
		Drawing No. 1019875	Sheet 1 of 1



02	ITEMS 010 AND 011 ADDED	RXH	5/Jan/07
Rev No.	Description of Revision	Revised By	Date
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering (NPS) Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering (NPS) Ltd.		GEA Buck Systems PH600 & PH1000 & PH1500 SLEW ENDSTOP ASSY ANTICLOCKWISE HANDING ZONE SAFE	
TOLERANCES UNLESS OTHERWISE STATED MACHINING: 0 = ±0.50, 0.0 = ±0.10, ANG'DPTS = ±0.50° FABRICATION: 0 TO 500 = ±1.0, 500 TO 2M = ±2.0, 2M TO 2H = ±3.0 ALL OTHER GEOMETRY TO COMPLY TO THE TOLERANCE STANDARDS SPECIFIED BELOW ISO 13920 -BF, ISO 2768 -mK		Drawn: SWI Date: 07/06/06 Drawing No.: 1019907	Sht 1 of 1



NOTES

- REFER TO PNEUMATIC CIRCUIT DIAGRAM G1951-D01-801.
- NOT USED
- NOT USED
- NOT USED
- HARD WIRED INTERLOCK
- REFER TO CONNECTION DIAGRAM G1951-D01-630 FOR SERVICES AND TERMINATION DETAILS.

NB: CONTROL SYSTEMS SUPPLIER TO PROVIDE TERMINATION DIAGRAM, MACHINE AND SITE CABLE SCHEDULE, ELECTRICAL TERMINATION AND HOOK UP DIAGRAMS

7. MMM = MACHINE (ID) NUMBER
 **(PS) = INSTRUMENT PREFIX
 XXX = SYSTEM TAG NUMBERS
 ZZZ(5100) = SEQUENTIAL LOOP TAG NUMBER

FOR ALL P&IDS WITHIN A SYSTEM.

8. CONTROL OPERATIONS ARE INITIATED VIA THE HOIST CONTROL SYSTEM.

9. VALVE JUNCTION BOXES CONTAIN SOLENOIDS, REMOTE I/O, TERMINALS AND CONNECTORS.








MOTOR DETAILS					
TAG	kW	AMPS	RPM	GEARBOX O/P RPM	COMMENTS
M3500	1.5KW	5.3	1440	12	TBC
M3502	0.1B	0.58	1365	5.4	TBC

INSTRUMENT LINE SYMBOLS	
INSTRUMENT TAG	DESCRIPTION
⊕ ????	INSTRUMENTS WHICH ARE FIELD MOUNTED
⊖ ????	INSTRUMENTS WHICH ARE MOUNTED ON A PANEL
⊗ ????	INSTRUMENTS WHICH ARE MOUNTED WITHIN A PANEL

INSTRUMENT LINE SYMBOLS	
INSTRUMENT LINE	DESCRIPTION
—//—	PNEUMATIC SIGNAL
—///—	ELECTRICAL SIGNAL
—X—	ELECTRICAL BINARY SIGNAL

MACHINE MATRIX (NOTE 7)					
MACHINE NUMBER	SYSTEM TAG No.	AREA	NOVARTIS TAG No.	ROOM No	COMMENTS
G1951-D01	001	BLENDING	202.M.0311/C001	306B	

Revision	UPDATED TO COMMENTS	---	---	Drawing not complete						
Details	Description/Change No:	Chk	Appd	or approved for manufacture						
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.						PH600 BLENDING ROOM POST HOIST P&ID				
THIRD ANGLE PROJECTION	Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Shr	Rev
	---	ISO 1920 -BF ISO 2768 -mK	MAPA	13/Sep/06	MAPA	13/Sep/06	RE	G1951-D01-901	of	1 03
Plot-Datum :								CAD-BSL-G1951-D01-901-03.DWG		



OUTLINE OF INVERTED IBC'S IN DOCKED POSITION WHEN IN BLENDER FRAME

Revision	DEVELOPMENT UPDATES	---	---	Drawing not complete
Def all	Description/Change No.	---	---	or approved for manufacture
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Operations Ltd. All rights are reserved. It is not to be copied, reproduced, or used for manufacturing or otherwise without the prior written consent of GEA Process Operations Ltd.</small>				GEA Buck Systems TYPE US QUADRO MILL AND SUPPORT FRAME
THIRD ANGLE PROJECTION	Scale 1:5	Drawn	Date	Checked
Plot - Day/Un	ISO 15926 - RP 1 ISO 2718	AJP	5/Jan/07	AJP
			5/Jan/07	RE
				G1951-M01-001
				005


Revision		REVISD TO CUSTOMER COMMENTS	
Details		Description / Change No	
Appd	Chk	Appd	
DRAWING COMPLETE AND APPROVED FOR USE		M01 MILL PLC PANEL	
TITL SHEET		G1951-M01-601	
G1951-M01-601		Drawing No	
1		Sht No	
2		Next Sht	
3		Rev	
07/02/2008		Date	
RS		Drawn	
ISO 2768 - mk		Tolerances unless otherwise stated	
ISO 13920 - BF		PROJECTION	
Scale		THIRD ANGLE	
G1951-M01-601		Plot-Datum	

DRAWING No.

G1951-M01-601




TITLE:-

M01 MILL PLC PANEL



PLA1		Date 06/02/2008 Report of drawings C4341-M01 Page			1	
Without filter						
Drawing	Description	Creation	Modification			
1	TITLE SHEET	12/09/2006	07/02/2008			
2	INDEX SHEET	12/09/2006	07/02/2008			
20	COMPONENT KEY AND IDENTIFICATION	12/09/2006	07/02/2008			
21	CABLE SPECIFICATION FOR SCHEMATIC DIAGRAMS	12/09/2006	07/02/2008			
22	COMPONENT SYMBOLS FOR SCHEMATIC DIAGRAMS	12/09/2006	07/02/2008			
25	PANEL REFERENCES FOR SCHEMATIC DIAGRAMS	12/09/2006	07/02/2008			
30	MILL PANEL I/O RACK	12/09/2006	07/02/2008			
31	MILL MOTOR SUPPLY	12/09/2006	07/02/2008			
32	MILL PANEL SLOT 4	12/09/2006	07/02/2008			
33	MILL PANEL SLOT 4	12/09/2006	07/02/2008			
34	MILL PANEL SLOT 5	12/09/2006	07/02/2008			
35	SAFETY SWITCH	12/09/2006	07/02/2008			
36	MILL PANEL SLOT 6	12/09/2006	07/02/2008			
37	MILL PANEL SLOT 6	12/09/2006	07/02/2008			
38	Terminal strip drawing X1.1	20/11/2006	07/02/2008			
			Number 1			
39	Terminal strip drawing X3.5	20/11/2006	07/02/2008			
			Number 1			


PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND									
Details	Description / Change No			Chk	Appd	APPROVED FOR USE							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL INDEX SHEET							
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	2	Rev
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	20	3
Plot-Datum													


COMPONENT KEY

- A - VARIABLE SPEED DRIVE/ASSEMBLY/PC. BOARD
- B - RESOLVER/ENCODER
- C - CAPACITOR
- D - DIODE
- E - CABINET ILLUMINATION
- F - FUSE/FUSE SWITCH/OVERLOAD
- G - POWER SUPPLY UNIT/GENERATOR
- H - PILOT LAMP
- K - CONTACTOR/RELAY/TIMER
- L - CHOKE/REACTOR
- M - MOTOR/FAN VENTILATOR
- P - METER/HMI
- Q - CIRCUIT BREAKER/ISOLATOR
- R - RESISTOR/POTENTIOMETER
- S - SWITCH/PUSHBUTTON/SENSOR
- T - TRANSFORMER
- X - TERMINAL/SOCKET
- Y - SOLENOID VALVE
- Z - RFI FILTER

COMPONENT IDENT. KEY



CABLE No. KEY



PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND										
Details	Description / Change No			Chk	Appd	APPROVED FOR USE								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL COMPONENT KEY AND IDENTIFICATION								
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	20	Rev
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	RS	07/02/2008					G1951-M01-601	Next Sht	21	3
Plot-Datum														

CABLE SPECIFICATION

WIRE COLOUR ABBREVIATIONS IN CIRCUIT DIAGRAMS

WIRING SPECIFICATION

WIRE COLOURS

PHASE R OF 3 PHASE CIRCUIT.....RED
 PHASE Y OF 3 PHASE CIRCUIT.....YELLOW
 PHASE B OF 3 PHASE CIRCUIT.....BLUE
 PROTECTIVE EARTH.....MARKED GREEN/YELLOW
 PHASE OF A.C. SINGLE PHASE CIRCUIT.....RED
 NEUTRAL OF A.C. SINGLE PHASE OR 3 PHASE CIRCUIT.....BLACK
 POSITIVE OF A DC CIRCUIT (+24V).....BROWN
 NEGATIVE OF A DC CIRCUIT (0V).....GREY
 NON IS SIGNALS.....ORANGE

BUSBAR COLOURS

POWER.....MARKED WITH PHASE COLOURS RD/YE/BU
 PROTECTIVE EARTH.....MARKED GREEN/YELLOW
 NEUTRAL.....ALL NEUTRAL'S SHOULD BE MARKED BLACK




MINIMUM WIRE SIZE


CONTROL WIRING.....1.5mm²
 SIGNAL WIRING.....0.75mm²

IEC 757	ENGLISH	DEUTSCH	FRANCAIS	ITALIANO	ESPANOL
GN	GREEN	GRUN	VERT	VERDE	VERDE
RD	RED	ROT	ROUGE	ROSSO	ROJO
YE	YELLOW	GELB	JAUNE	GIALLO	AMARILLO
BK	BLACK	SCHWARZ	NOIR	NERO	NEGRO
BU	BLUE	BLAU	BLEU	BLU	AZUL
BN	BROWN	BRAUN	BRUN	MARRONE	MARRON
OG	ORANGE	ORANGE	ORANGE	ARANCIONE	NARANJA
VT	VIOLET	VIOLETT	VIOLET	VIOLA	VIOLETA
GY	GREY	GRAU	GRIS	GRIGIO	GRIS
WH	WHITE	WEISS	BLANC	BLANCO	BLANCO
GN/YE	GREEN/ YELLOW	GRUN/ GELB	VERT/ JAUNE	VERDE/ GIALLO	VERDE/ AMARILLO
PK	PINK	ROSA			
CL	CLEAR	KLAR			

SPECIAL MANUFACTURING INSTRUCTIONS

ALL CABLE TO BE LOW SMOKE ZERO HALOGEN TYPE

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND								
Details	Description / Change No			Chk	Appd	APPROVED FOR USE						
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL CABLE SPECIFICATION FOR SCHEMATIC DIAGRAMS						
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	21	Rev
PROJECTION			ISO 13920 - BF ISO 2768 - mK	RS	07/02/2008		16/10/2006		G1951-M01-601	Next Sht	22	3
Plot-Datum												




PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND										
Details	Description / Change No			Chk	Appd	APPROVED FOR USE								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL COMPONENT SYMBOLS FOR SCHEMATIC DIAGRAMS								
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	22	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008			G1951-M01-601	Next Sht	25	3
Plot-Datum														



PCP DRG. No. C4341




Revision	REVISED TO CUSTOMER COMMENTS				DRAWING COMPLETE AND								
Details	Description / Change No		Chk	Appd	APPROVED FOR USE								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					M01 MILL PLC PANEL PANEL REFERENCES FOR SCHEMATIC DIAGRAMS								
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	25	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008	20/11/2006	G1951-M01-601	Next Sht	30	3
Plot-Datum													



PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND									
Details	Description / Change No			Chk	Appd	APPROVED FOR USE							
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL MILL PANEL I/O RACK CONFIGURATION							
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	30	Rev
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008	06/02/2008	G1951-M01-601	Next Sht	31	3
Plot-Datum													

FROM
G1951-B01-601
SHT 54




TO
G1951-B01-601
SHT 54

PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND								
Details	Description / Change No			Chk	Appd	APPROVED FOR USE						
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL SCHEMATIC WIRING DIAGRAM FOR MILL MOTOR SUPPLY						
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No
PROJECTION			ISO 13920 -BF ISO 2768 -mK	RS	07/02/2008		20/11/2006		G1951-M01-601	Next Sht	32	3
Plot-Datum												

DROP 1

SLOT 4



BUCK VALVE
VACUUM GENERATOR
PRESSURE SWITCH
PS-XXX-5203


BUCK VALVE
OPEN
LIMIT SWITCH
ZSD-XXX-5100

BUCK VALVE
CLOSED
LIMIT SWITCH
ZSC-XXX-5100

SPARE


PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND											
Details	Description / Change No			Chk	Appd	APPROVED FOR USE									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL									
						DIGITAL INPUT SIGNALS									
				SLOT 4											
THIRD ANGLE		Scale	Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	32	Rev		
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	33	3
Plot-Datum															



PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND								
Details	Description / Change No			Chk	Appd	APPROVED FOR USE						
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL DIGITAL INPUT SIGNALS SLOT 4						
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No
PROJECTION			ISO 13920 -BF ISO 2768 -mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	34	3
Plot-Datum												



DROP 1

SLOT 5

Q10.0

Q10.1

Q11.0

Q11.1

13

14

15

16

19 3401
X3.50

21 3403
X3.50

23 3405
X3.50

25 3407
X3.50

20
X3.50

22
X3.50

24
X3.50

26
X3.50

SHT 33.8 3002

3002 SHT 35.1

SHT 36.1

SPARE


SPARE

SPARE

SPARE


PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND								
Details	Description / Change No	Chk	Appd	APPROVED FOR USE								
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>				M01 MILL PLC PANEL DIGITAL OUTPUT SIGNALS SLOT 5								
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	34	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	35	3
Plot-Datum												



PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS				DRAWING COMPLETE AND									
Details	Description / Change No		Chk	Appd	APPROVED FOR USE									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>					M01 MILL PLC PANEL SCHEMATIC WIRING DIAGRAM FOR SAFETY SWITCH									
THIRD ANGLE		Scale			Tolerances unless otherwise stated		Drawn	Date	Modified	Date	Status	Drawing No	Sht No	35
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008	06/02/2008		G1951-M01-601	Next Sht	36	3
Plot-Datum														



PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND											
Details	Description / Change No			Chk	Appd	APPROVED FOR USE									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL DIGITAL INPUT SIGNALS SLOT 6									
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	36	Rev	
PROJECTION			ISO 13920	-BF	ISO 2768	-mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	37	3
Plot-Datum															

DROP 1

SLOT 6

CONT. FROM
SHT. 36

19.4

19.5

19.6

19.7

3

7

4

8


37 3701
X3.5

38 3702
X3.5

39 3703
X3.5

40 3704
X3.5

BK -S37.2.



SHT 36.8 → 3001

SHT 35.8 → 3002

X3.5
24

SHT 36.8 → 3001

X3.5
41

X3.5
42

X3.5
43

X3.5
44

3001




AIR PRESSURE
SWITCH
PS-XXX-9010


PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND								
Details	Description / Change No			Chk	Appd	APPROVED FOR USE						
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL DIGITAL INPUT SIGNALS SLOT 6						
THIRD ANGLE		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No	Sht No	37	Rev
PROJECTION			ISO 13920 -BF ISO 2768 -mK	RS	07/02/2008		06/02/2008		G1951-M01-601	Next Sht	38	3
Plot-Datum												

1	2		3			4		5			6			7			8						
A	ELEMENT FUNCTION																A						
B	SHEET																B						
C	Cablemarking	Cabletype		Pin Number.																			C
D	X11	Destination symbol	Connection no.																			D	
Designation																			D				
Link		Terminal number																			D		
E	Terminal strip	Destination symbol	Connection no.																			E	
Designation																			E				
F	Cablemarking	Cabletype		Pin Number.																			F
E	TERMINAL FUNCTION																E						
F	ELEMENT FUNCTION																F						

PCP DRG. No. C4341

Revision	REVISED TO CUSTOMER COMMENTS			DRAWING COMPLETE AND											
Details	Description / Change No			Chk	Appd	APPROVED FOR USE									
<small>This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd</small>						M01 MILL PLC PANEL									
THIRD ANGLE		Scale	Tolerances unless otherwise stated			Drawn	Date	Modified	Date	Status	Drawing No	Sht No	38	Rev	
PROJECTION			ISO 13920 -BF	ISO 2768 -mK	RS	07/02/2008			20/11/2006		G1951-M01-601	Next Sht	39	3	
Plot-Datum															




FRONT VIEW

SIDE VIEW

P.C.P. DRG. No. C4341

Revision	DOCUMENTATION CORRECTIONS	BJO	BJO	Drawing not complete or approved for manufacture								
Details	Description/Change No:	Chk	Appd									
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.		GEA Buck Systems		U5 QUADRO MILL CONTROL PANEL ARRANGEMENT DRAWING								
THIRD ANGLE PROJECTION		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Sht	1	Rev
		NTS	ISO 13920 -BF ISO 2768 -mK	PM	20/09/06	BJO	06/03/08		G1951-M01-610	of	1	3
Plot-Datum :				A3								




CUSTOMER'S LINE.
CLEAN, DRY,
QUALITY AIR.
6.0 BarG MIN

INSIDE CABINET

Revision	UPDATED TO SAT	PM	---	Drawing complete and approved for use											
Details	Description/Change No:	Chk	Appd												
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.				PNEUMATIC CIRCUIT FOR MILL MOTOR PANEL											
THIRD ANGLE PROJECTION		Scale	NTS	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Sht	1	Rev	1	2
Plot-Datum :		ISO 13920	ISO 2768	PM	30/10/06	PM	06/02/08			G1951-M01-801	of	1			

P.C.P. DRG No. C4341


A3



NOTES

- REFER TO PNEUMATIC CIRCUIT DIAGRAM G1951-M01-801.
- VACUUM SWITCH SET POINT -650mBAR UNDERPRESSURE RISING
- NOT USED
- VACUUM SWITCH SET POINT -650mBAR UNDERPRESSURE RISING
- HARD WIRED INTERLOCK
- N/A
- MMM = MACHINE (ID) NUMBER
 **(PS) = INSTRUMENT PREFIX
 XXX = SYSTEM TAG NUMBERS
 ZZZ(5100) = SEQUENTIAL LOOP TAG NUMBER
- FOR ALL P&IDS WITHIN A SYSTEM.
- CONTROL OPERATIONS ARE INITATED VIA THE HOIST CONTROL SYSTEM.
- VALVE JUNCTION BOXES CONTAIN SOLENOIDS, REMOTE I/O, TERMINALS AND CONNECTORS.

MOTOR DETAILS					
TAG	kW	AMPS	RPM	GEARBOX O/P RPM	COMMENTS
M4000	0.375	0.95	1365	5.4	TBC
-	-	-	-	-	-



INSTRUMENT LINE SYMBOLS	
INSTRUMENT TAG	DESCRIPTION
⊙ ? / ????	INSTRUMENTS WHICH ARE FIELD MOUNTED
⊙ ? / ????	INSTRUMENTS WHICH ARE MOUNTED ON A PANEL
⊙ ? / ????	INSTRUMENTS WHICH ARE MOUNTED WITHIN A PANEL

INSTRUMENT LINE SYMBOLS	
INSTRUMENT LINE	DESCRIPTION
—//—	PNEUMATIC SIGNAL
—///—	ELECTRICAL SIGNAL
—//—	ELECTRICAL BINARY SIGNAL

MACHINE MATRIX (NOTE 7)					
MACHINE NUMBER	SYSTEM TAG No.	AREA	NOVARTIS TAG No.	ROOM No.	COMMENTS
G1951-M01	001	BLENDING ROOM	202.M.0311/C001	306B	

Revision Details	DUST EXTRACT VAC GEN DELETED. Description/Change No:	---	---	Document Complete and Approved for use							
This drawing or document is COPYRIGHTED by and is the property of GEA Process Engineering Ltd, all rights to copyright, patented or patentable design or invention being reserved. It must not be copied (in whole or in part), used for manufacture or disclosed to others without prior written consent of GEA Process Engineering Ltd.				U5 QUADRO MILL & SUPPORT FRAME P&ID							
THIRD ANGLE PROJECTION		Scale	Tolerances unless otherwise stated	Drawn	Date	Modified	Date	Status	Drawing No.	Shr	Rev
Plot-Datum :		---	ISO 13920 -BF ISO 2768 -mK	MAPA	24/Oct/06	MAPA	2/Nov/06	CO	G1951-M01-901	of	1/06
CAD-BSL-G1951-M01-901-05.DWG											

SECTION 6 INSTALLATION GUIDELINES

CONTENTS

6.0 SAFETY	3
6.1 PH600 POST HOIST - INSTALLATION.....	3
6.1.1 Preparation.....	3
6.1.2 Mounting and alignment	4
6.1.3 Electrical/Pneumatic Installation	5
6.1.4 Adjustments - Slew & Carriage Position Switches	5
6.2 BLENDER (B01) – INSTALLATION	7
6.2.1 General	7
6.2.2 Blender Main Frame and Cage.....	7
6.2.3 Control System.....	7
6.2.4 Adjust Clamping Pressure	8
6.2.5 Set "Container Clamped" Sensor.....	9
6.2.6 Set "Lifting Frame" Proximity Switch.....	10
6.3 U5 MILL (M01).....	11

Operation & Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Blank Page

Section 6

INSTALLATION GUIDELINES

6.0 Safety

All installation actions must be carried out by, alert qualified personnel capable of recognising risks and dangers associated with installation.



HEAVY WEIGHTS - EQUIPMENT WEIGHING MORE THAN 20KG MUST BE LIFTED USING SUITABLE MECHANICAL LIFTING APPARATUS.

LIFTING APPARATUS – LIFTING APPARATUS MUST ONLY BE USED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS AND LOCAL HEALTH AND SAFETY REGULATIONS. ALL LIFTING APPARATUS AND SLINGS MUST BE APPROVED.

BLENDER: DANGER TO LIFE & LIMB – ROTATING MACHINERY; THE BLENDER MUST BE INSTALLED IN AN ENCLOSED AREA WITH RESTRICTED ACCESS. INTERLOCK SYSTEMS AND LOCAL OPERATING PROCEDURES MUST ENSURE THAT NO PERSONNEL ARE WITHIN THE DANGER AREA WHEN THE MACHINE IS OPERATING

Do not climb on the machine, use approved climbing/access equipment.

NOTE...

All electrical connections are to be made with reference to drawings in Section 5.

6.1 PH600 Post Hoist - Installation

PH600 Post Hoist is to be installed in the Blending Room. The procedure detailed below is to be applied to the hoist supplied.

6.1.1 Preparation

Before proceeding, please check the following:

1. All the components of the hoist are present and undamaged.
2. Down stream equipment is in position (or its proposed position and orientation is clearly marked), if it has a direct bearing on the installation of the hoist.
3. Proposed location has enough room for the hoist to perform its intended range of motion.
3. Hoist will have adequate maintenance access.

The hoist is provided with mounting holes in the base for fixing the unit to the floor. Some hoists are supplied with an additional ceiling unit to support the hoist at the ceiling (depending on model supplied); mounting holes are provided to fix this unit to the (structural) ceiling. (See section 5 for drawings showing installation dimensions).

Fixing bolts are not supplied as part of the equipment. The fixing of the unit is dependent on site conditions such as the type of structure being fixed to, the material and grade and the intended use. It is recommended that for fixing into concrete, chemical resin anchors of the correct specification for the loading conditions are used. Specification of the fixing fasteners should always be defined by a qualified structural engineer, based on the calculations for floor and ceiling loadings.

6.1.2 Mounting and alignment

General installation procedures are as follows:

1. Refer to the mechanical general assembly (GA) drawing (see Section 5). In particular, refer to the plan view and note the orientation of the 'Load' and 'Unload' positions, and the 'Reach' radius of slew.
2. Mark the position for the hoist on the floor. Use the centre line of the down stream equipment, in conjunction with the 'Reach' radius of the hoist, to locate, accurately, the hoist base plate and anchor points.
Important: Where a ceiling mount is to be fitted, (depending on model) the location of the ceiling mount must be exactly vertically above the centre of the base plate.
3. Mark the location of the base plate's fixing holes on the plant floor, and ceiling support mounting bolts where applicable.
4. Drill the floor (and ceiling) at the appropriate points. Follow the instructions of supervising structural engineer. Follow the instructions for the use of the chemical resin anchors (if used) and observe the required curing period.
5. Using appropriate lifting gear, raise the Column to the vertical position and position the base plate over the fixing bolts. The ceiling support (if fitted) can be fitted to the top of the column at this stage.
6. Secure the base plate to the floor. Where a ceiling support is to be fitted, the lifting gear should continue to support the Column until the ceiling support has been fixed to the ceiling.
7. Check/ensure hoist is vertical. Remove the lifting gear.
8. The hoist will have been shipped with the forks or attachment separate from the column. This should now be fitted and the mounting bolts are to be tightened to the torque values listed in Section 3.
9. Final alignments should be checked at this stage. The mounting bolts should then be tightened to appropriate torque for the type of fasteners used.

IMPORTANT...

DO NOT TIGHTEN THE FIXING BOLTS BEFORE LEVELLING & VERTICAL ALIGNMENT HAS BEEN CARRIED OUT.

6.1.3 Electrical/Pneumatic Installation

Refer to electrical and pneumatic drawings (See Section 5) and make the connections between the Hoist and any remote panels (where applicable).

HIGH VOLTAGE – ENSURE MAINS SUPPLY IS ISOLATED BEFORE CONNECTING TO THE MAIN CONTROL PANEL

1. Connect the mains supply to the main control panel in accordance with electrical diagrams. (Section 5) In particular, ensure that the hoist is grounded.
2. Connect compressed air supply (where applicable). (See Section 1 for capacity).

6.1.4 Adjustments - Slew & Carriage Position Switches

End stops with limit switches are installed to set the permitted angle of slew between Load and Process positions. Similarly, limit switches are fitted to the hoist column to set the Hoist 'Load/lower overtravel' position and the Upper Stop/Slew Position. The position of each limit switch is set, when the machine is commissioned, to enable the machine achieve the design parameters. If it is necessary to adjust (fine tune) the positions set at commissioning proceed as directed in the following paragraphs.

Slew Position

To adjust a Slew position (load or process):

1. Determine the direction of movement, and estimate the amount of adjustment require. It will help if the desired position of the forks (centre line) is marked on the floor.
2. Slew the hoist until it is mid-way between Process and Load positions.
3. Ensure the machine is made safe.
4. Remove the covers from the powered slew base assembly, and identify the Process Slew and Load Slew stops.
5. Using a scribe or paint & brush, clearly mark the existing positions of both slew switches (default positions).
6. If the 'Process' Slew position is to be adjusted:
 - 6.1 Using M10 socket spanner, slacken both set screws on the stop plate. Do NOT loosen the set screws – they should be just slack enough to enable them to be moved by gentle tapping with hammer.
 - 6.2 Using hammer gently move the stop plate until the limit switch is the desired position (estimated).
 - 6.3 Connect mains power and slew the hoist to the 'Process' position.
 - 6.4 Check the accuracy of slew against the external marker.
 - 6.5 With the machine made safe - repeat actions at Step 6.2 – 6.4 above until centre line of forks is in desired position.

CAUTION: When adjusting the stop plate, take care and ensure that any movement does not cause the 'Flag' on the slewing base to collide with the face plate of the limit switch.

 - 6.6 When desired position is achieved, tighten set screws on stop plate.
7. If the 'Load' Position is to be adjusted, carry out the sets detailed at 6.1 - 6.6 above.

Carriage Height Position

There are two limit switches installed on the Hoist Column to set the Load/Lower Overtravel position and the Upper Stop/Slew position. The position of the 'Load/Unload Overtravel switch is the 'O' datum for the encoder & counter.

The encoder uses this datum, to determine the heights (above datum) of the following positions (See G1951-D01-901 P&I Drawing in Section 5):

- Unload Pre-Stop
- Slew Pre-Stop
- Forks Empty Interlock
- Slew Height

The distance (in millimetres) of each position in relation to the 'O' datum is represented by encoder pulses, on the basis of 1 pulse = 1 millimetre.

Therefore, if the 'O' datum is moved UP or DOWN, the relative stop positions of the hoist carriage will change accordingly, unless the encoder values for the respective positions are changed by the same value as the Datum.

The Upper Limit switch on the hoist column is set at commissioning to protect the hoist and should NOT be adjusted.

To adjust the Load/Lower Overtravel Limit switch, proceed as follows:

1. Determine the distance and direction of change for the datum.
2. Lower the hoist to fully down position.
3. Ensure the hoist is made safe.
4. Remove the left side of the Hoist Front cover.
5. Locate the lower limit switch and remove the cable ties to reveal Qty 2 Allen Head bolts.
6. Using scribe, or paint & brush, mark the Mark the existing position of the limit switch (default).
7. Slacken the Allen head bolts sufficient to allow the switch assembly to be raised or lowered, as required.
8. Connect power to the hoist and raise/lower to test accuracy of new position.
9. With the machine made safe, repeat the actions at Steps 7 & 8 until the desired accuracy is achieved.
10. Tighten the Allen Head bolts and re-fit the front cover.
11. The height of the 'O' datum has now changed (Up or Down) by a specific amount. This amount is to be recorded, because it is the basis for any changes to the interim positions of the hoist. If the interim carriage height positions are to be adjusted, this must be done through software in conjunction with the encoder and counter using the formulae $1\text{pulse} = 1\text{mm}$

6.2 Blender (B01) – Installation

6.2.1 General

All standard motors incorporate breather holes in the frame between the mounting feet, to allow an exchange of air within the motor under varying temperature conditions. The breather holes are fitted with plastic plugs before the motor is dispatched to maintain environmental protection. The plugs may be permanently removed after installation in clean, dry-air operating conditions.

To prevent movement and to allow efficient operation, the user should ensure that the equipment is properly fixed. There are bolt-holes in the frame base for this purpose.

Holding-down bolts are not supplied with this equipment. The correct type of fixing is dependent on the type and individual characteristics of the plant flooring and cannot be specified by Buck Systems without full information and instructions from the customer. *EACH* fixing bolt must be able to withstand a pullout load of 1750 Kg.

6.2.2 Blender Main Frame and Cage.

The blender must be installed on a horizontal flat surface and fixed to prevent movement due to dynamic loads when operating. Refer to drawing G1903-B01-001 (Sheet 1) for details of the loading/space requirements.

Position the blender, making sure that enough free space is left to allow for the cage rotation. Clearance for maintenance is required to the rear of the frame.

Mark the site floor with the position of the base frame boltholes.

Ensure that the frame will not be twisted, when the holding down bolts are tightened, by fitting packing pieces beneath the frame. Secure the frame to floor (following procedures outlined by supplier of the chosen fixing device).

6.2.3 Control System

There are two control cabinets/panels to be installed, see Drawing G1951-B01-001:

Main Control Panel - Floor-mounted against the wall in the Technical Area.

Operator Control Panel – Mounted flush with wall in safe area, outside Blending Room.

Electrical Connections

For details of electrical connections refer to the drawings G1951-B01-601 in Section 5.I.

The terminal blocks inside the electrical panels and junction box are clearly numbered to aid installation. Make electrical connections as follows:

Control Circuits:

Main Control Panel to machine junction box on the blender frame.

Main Control Panel Operator Interface Control Panel.

Power:

Motor power and motor brake connections between Main Control panel and the Machine Junction Box.

Mains three-phase supply to control panel.

Note: Ensure control circuit wiring is routed separately from power supply and three-phase wiring to the motor. Where this is not possible a separation of at least 300 mm is to be maintained between control and power wiring.

Earth Connections

Make earth connections in accordance with drawing Nos. G1959-B01-601 and B18023.

Pneumatic Connections

Make the pneumatic connections; refer to drawings G1903-B01-801 & G1903-B01-901 in Section 5:

Main air supply to filter/regulator/ lubricator unit in the pneumatic panel.

Set Up Switches and Sensors

See circuit diagram G1951-B01-601, pneumatic circuit diagram G1951-B01-801 and process diagram G1951-B01-901 in Section 5 of this manual..

The blender requires an air supply of 5.5 BarG (80 psi) at a flow rate of 60 Litres/Second. This pressure is set by the main regulator. Minimum pressure to ensure adequate clamping is 3.75 BarG (49 psi). Pressure Switch PSI-9000 is set to activate as the supply falls below this value.

6.2.4 Adjust Clamping Pressure

Refer to the pneumatic circuit diagram G1951-B01-801 and 901 in Section 5 and *Supplier's Information* in Section 4.

Method.

1. Unscrew the main relieving pressure regulator knob on the Filter/Regulator.
2. Turn on the compressed air supply but not the electric supply.
3. Clip a test meter, range ohms x 1 across the terminals on the pressure switch, PS3300, to detect operation (close on rise).
4. Gradually screw down the main pressure regulator, observing its gauge, until 3.75 BarG is registered. Now adjust setting of pressure switch PSL-9000 (this increases the pressure at which the switch changes over) until it operates. See *Supplier's Information* in Section 4 for adjustment settings.
5. Reverse the adjuster, finding the mid-point. Now gently unscrew the main pressure regulator, observing the pressure at which PSL-9000 operates. As pressure falls through 3.75 BarG, change over should occur. Adjust until this condition is met, and then reset the pressure regulator up to 5.5barG.
6. Remove the test meter leads.

6.2.5 Set "Container Clamped" Sensor

The purpose of this unit is to monitor the clamping pressure holding the container in the machine. It is, in effect, a supply to pressure switch PS3300, consisting of three elements:

A flow control regulator

A pressure regulator

Breaks in the line produced by the sensing pads on the diagonal air check bungs, sited in the top of the cage.

As the container rises to the air check sensing pads, their holes are sealed off by the container framework. The clamping pressure therefore increases. Pressure switch PS3300 trips when 1.7barG is reached. The flow regulator limits the air loss during the lift cycle before the top of the container framework makes contact with the sensing pads.

Method

1. Connect the output from pressure regulator direct to the input PS3300.
2. Fully unwind the pressure regulator setting knob on pressure regulator to stop (min. pressure setting).
3. Open the flow control valve fully.
4. Adjust the setting on pressure switch PS3300 (This increases the pressure at which the switch changes over).
5. Clip a test meter, range ohms x 1 across the terminals on the pressure switch, PS3300, to detect operation (close on rise).
6. Turn on the compressed air supply if not already, and ensure the pressure as displayed on the meter is 5.5 BarG.
7. Manually override solenoid valve XV3300.
8. Screw down the pressure regulator setting knob on pressure regulator observing its pressure gauge, until 2barG is reached. Once reached, lock-off the knob.
9. Turn off the compressed air supply, wait for the pressure to fall, and then reapply.
10. If the main air pressure does not go back up to 2barG, readjust pressure regulator knob setting.
11. Using the test meter, adjust the setting on pressure switch PSL3300 until the contacts close.
12. Turn off the compressed air. As the pressure falls, at approximately 1.4 barG the switch contacts open.
13. Fully close the flow control needle valve.
14. Apply the compressed air again.
15. Observing the test meter and gauge, gradually open the flow control needle valve – ensuring that the gauge rises and the switch contacts close at approximately 1.4 to 1.75 barG.

16. Turn off the compressed air.
17. Manually reset solenoid valve XV3300 to closed.
18. Disconnect the direct pipe link between pressure regulator output and switch PS3300 input.
19. Remove the test meter leads.
20. The flow regulator is initially set at four full turns open from closed, this flow setting can be increased when the machine is run automatically if the observed time between the final stroke with bin and the input signal indicating 'bin clamped' exceeds four seconds.
21. The 'container clamped' sensor is now set.

6.2.6 Set "Lifting Frame" Proximity Switch.

IMPORTANT - The underside of the bin lifting platen must be adjusted to be parallel to the floor across its diagonally opposite corners. Failure to do this will cause loading difficulties and in extreme cases damage to the screw jacks.

Method

1. Because the machine protocol does not allow manual or automatic rotation unless PS3300 gives a 'clamped' signal, setting the lifting platen involves shorting out this switch.
2. Any links installed must be removed after setting.
3. Turn on the compressed air supply and mains power.
4. Manually operate solenoid valve XV3000A to drive lifting frame fully up in to the cage until stalled in top position. Do not reset control valve to centre position.
5. Press the "Controls On" push button.
6. Put the blender into manual mode, and hold down the jog forwards key on the operator interface unit to slowly rotate the cage until the 'cage vertical' switch flag arm, bolted to the main-shaft between the gearbox & bearing, has past XS2200. Once past, release the jog forwards key to bring the cage to a stop, and then press the hold down the reverse key. This action will then cause the cage to slowly reverse until XSS2200 detects the presence of the flag whereon the cage will automatically stop in its correct automated positioning mode.
7. Again using the air motor control solenoid valve XV300B, manually operate the drive lifting frame down out of the cage to within 100mm of the floor.
8. Measure the vertical distance from the floor to the underside of the diagonally opposing jacking legs.
9. This dimension should be within 3mm for all.
10. If not it must be corrected by adjusting the 'cage vertical' switch flag arm. Advancing the flag in the direction of final rotation stops the cage sooner and retarding stops the cage later.
11. Re run this procedure from the beginning until the frame is parallel to the floor.
12. The height of the frame must now be set.

13. It is important that the frame rests on the floor to absorb the impact loading caused by carelessly loading bins dropped too quickly into the cage frame pockets.
14. Turn off the motor isolator and turn on mains power to power up proximity switches XS2200 and XS2201.
15. Manually override the air motor control valve to drive the frame down until it touches the floor – observe the input indicator and adjust the 'frame down' flag until it shows 'operated'.
16. Return machine to operational by first ensuring any links used are removed.

Proving Settings

1. Clear the area.
2. Switch on the local motor isolator.
3. Set the timer to 20 seconds and the RPM to 3.
4. Load a container into the cage.
5. Close the Blender Room Gate and transfer Key A to the Operator Control Panel (Panel now enabled).
6. Press "Controls On" push button, the "Controls On " lamp will illuminate.
7. Select automatic operation and a blend cycle. This starts a complete blending cycle.
8. Allow the machine to clamp the bin, rotate, time out, continue past the vertical position, reverse, come to a stop at the vertical and unclamp.
9. Using the interlock key, re-enter the compound and observe if the cage is vertical.
10. If the diagonally opposite frame corners are not resting on the floor, the 'down flag' must be lifted by the appropriate amount. The ideal setting leaves the frame firmly resting on the floor when the jack drive stops – beware that too much over-run may bend the jacks.

6.3 U5 Mill (M01)

The U5 Mill is mounted on a Frame/Trolley Assembly prior to despatch by Buck systems and includes the following principle attachments

Hopper Assembly

250 mm Dia. Buck 'C' Valve (Active Half) assembly with vacuum generators

Before bring the Mill into service, check and ensure the Harting (plug & socket) electrical and pneumatic connections are secure and undamaged.

Operation & Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

SECTION 7

Certification

See Volume 3

Operation and Maintenance Manual
SP2000 Blender, Post Hoist & Mill by Buck Systems

Blank Page