



# ZFO 16, zeolite trap





Similar Image

#### **ZFO 16, zeolite trap**

■ Prevents operating fluid backflow on the intake side

Technical Data	ZFO 16, zeolite trap
Conductance at 1 · 10 <sup>-2</sup>	0.3 l/s
Conductance at 100 hPa	31 l/s
Conductance at 1 hPa	0.7 l/s
Connection flange (in)	DN 16 ISO-KF
Connection flange (out)	DN 16 ISO-KF
Filling quantity	0.5
For pumping speed up to	5 m³/h   2.94 cfm   83.33 l/min
Heating rod	No
Mounting orientation	0° (HV flange top) – 90°
Weight with contents	1.5 kg   3.31 lb

Order number	
ZFO 16	PK Z70 003

#### **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

### **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems: We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a perfect vacuum solution? Please contact us:

Pfeiffer Vacuum GmbH Headquarters · Germany T +49 6441 802-0 info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

